

Product data sheet

Characteristics

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
 Http://www.100y.com.tw

CA3SK11BD

contactor - TeSys K, D, S - CA3-SK - 10 A -
 instantaneous - 24 V DC



Main

Range of product	Mini-control relay
Product or component type	Control relay
Device short name	CA3SK
Contactor application	Control circuit
Utilisation category	DC-13
Control circuit type	DC
Coil type	Standard
Coil technology	Without integral suppression device
Pole contact composition	1 NO + 1 NC
Control circuit voltage	24 V DC
Connections - terminals	Connector 1 1,5...6 mm ² solid Connector 2 1,5...4 mm ² solid Connector 1 0,5...6 mm ² flexible without Connector 2 0,35...2,5 mm ² flexible without Connector 1 0,35...6 mm ² flexible with Connector 2 0,35...1,5 mm ² flexible with

Complementary

Contact operation	Mechanically linked IEC 60947-5-1
Control circuit voltage limits	0.85...1.1 U _c 50 °C operational >= 0.2 U _c 50 °C drop-out
[U _i] rated insulation voltage	690 V IEC 60947 690 V BS 5424 690 V VDE 0110 group C 690 V CSA 22-2 No 14 690 V UL 508
Tightening torque	0,8 N.m connector pozidriv 1 mm
[U _e] rated operational voltage	<= 690 V DC
[I _{th}] conventional free air thermal current	10 A ≤ 55 °C
Associated fuse rating	10 A gI ≤ 690 V IEC 60947 10 A gI ≤ 690 V VDE 0660
Inrush power in W	2,2 W 20 °C
Hold-in power consumption in W	2,2 W 20 °C
Mechanical durability	10000000 cycles
Operating rate	1200 cyc/h 20 °C
Operating time	4...6 ms coil de-energisation and NO opening 6...8 ms coil de-energisation and NC closing 8...12 ms coil energisation and NO closing 10...18 ms coil energisation and NC opening
Non-overlap time	1,5 ms on energisation between NC and NO contacts 1,5 ms on de-energisation between NC and NO contacts
Height	56 mm
Width	27 mm
Depth	55,5 mm
Product weight	0,132 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Standards	BS 5424 IEC 60947 NF C 63-110 VDE 0660
Product certifications	CSA UL
IP degree of protection	IP2x VDE 0106
Protective treatment	TC IEC 60068
Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	-50...70 °C
Operating altitude	2000 m without
Heat dissipation	2,2 W
RoHS EUR conformity date	0718
RoHS EUR status	Compliant

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)