

S2 Relay Series

Axial style reed relay



The S2 reed relay series from Cynergy3 has been developed for applications where PCB mounting is not possible.

The relay can be mounted using a variety of methods and orientations to suit particular applications. The terminal pins are flexible enough to allow bending for assembly into equipment.

Available with either a 10W or 50W contact in a pressurised reed switch or a 100VA contact in a vacuum reed switch.

- Variable mounting options
- 10W, 50W and 100VA contact options
- Reliable reed switch contacts

Contact Specification	Conditions	Units	S2-03P	S2-XXP	S2-XXE
Material			Ruthenium	Rhodium	Rhodium
Switch atmosphere			Pressurised	Pressurised	Vacuum
Isolation across contacts		Volts DC	200	500	1000
Switching power max.	Resistive load	Watts	10	50	-
Switching power max.	Resistive load	VA	-	70	100
Switching voltage DC max.	Resistive load	Volts DC	200	350	350
Switching voltage AC max.	Resistive load	Volts AC RMS	140	300	300
Switching current DC max.	Resistive load	mA DC	250	700	1000
Switching current AC max.	Resistive load	mA AC RMS	250	500	1000
Carry current max.		Amps DC/AC RMS	1	2.5	2.5
Contact capacitance max.	Open	Pico Farad (pF)	0.3	0.5	0.5
Initial contact resistance max.	@Nominal coil voltage	Milliohms (mΩ)	100	100	100
Insulation resistance		Ohms (Ω)	10E10	10E10	10E10
Life time operations	Hot switching resistive load	Operations 50% duty cycle	10E7 (12V DC, 4mA)	10E6 (350V DC, 1mA)	10E7 (500V DC, 1mA)
	Dry switching	Operations 50% duty cycle	10E8	10E9	

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Coil Specification			3V	5V	12V	24V
Must operate voltage	@20°C	Volts DC	2.25	3.7	9	19
Must release voltage	@20°C	Volts DC	0.5	1	2	3
Operate time inc bounce	@20°C	Milliseconds	0.1	1.0	1	11
Release time inc bounce	@20°C	Milliseconds	0.07	0.5	0.5	0.5
Resistance	@20°C	Ohms	250	160	1000	1000

Note: The operate / release voltage and coil resistance will change at a rate of 0.4% per degree C. Values are stated at room temperature (20 degrees C)

Relay Specification			
Isolation contact /coil min.		Volts DC	1000
Operating temp range		°C	-40 to +85
Storage temp range		°C	-40 to +125

Standard Parts	Coil Volts VDC	Switching Power	Isolation VDC	Switch Atmosphere
S2-03P	3	10W	200	Pressurised
S2-05P	5	70VA	500	Pressurised
S2-12P	12	70VA	500	Pressurised
S2-24P	24	70VA	500	Pressurised
S2-05E	5	100VA	1000	Vacuum
S2-12E	12	100VA	1000	Vacuum
S2-24E	24	100VA	1000	Vacuum

Custom versions can be made for particular applications. Please contact Cynergy3 with your requirements.

Mechanical Dimensions

