

Part Number	2N3569
Military/High-Rel	N
V(BR)CEO (V)	40
V(BR)CBO (V)	80
I(C) Max. (A)	500m
Absolute Max. Power Diss. (W)	300m
Maximum Operating Temp (°C)	125x
I(CBO) Max. (A)	50u
@V(CBO) (V) (Test Condition)	40
V(CE)sat Max. (V)	.25
@I(C) (A) (Test Condition)	150m
@I(B) (A) (Test Condition)	15m
h(FE) Min. Current gain.	100
h(FE) Max. Current gain.	300
@I(C) (A) (Test Condition)	150m
@V(CE) (V) (Test Condition)	1.0
f(T) Min. (Hz) Transition Freq	60M
@I(C) (A) (Test Condition)	50m
@V(CE) (V) (Test Condition)	10
C(obo) (Max) (F)	20p
@V(CB) (V) (Test Condition)	10
@Freq. (Hz) (Test Condition)	140M
Package Style	TO-105
Mounting Style	T
Pinout Equivalence Code	3-12
Description	

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)