


# .050" Medium Flex Life Cable

28 AWG Stranded, PVC

3539 Series



- Flex life of 10 million cycles at 1 3/4 inch diameter
- 19 strands of tinned copper provide extended flex life for dynamic applications
- 28 AWG wire on .050 inch centers permits mass termination to a broad line of IDC connectors
- Zippable for branching or discrete termination

Date Modified: February 19, 1999

TS-0058-09  
Sheet 1 of 2

18



## Physical

### Insulation

Material: Polyvinyl Chloride (PVC)  
Color: Gray

### Marking

Standard: None

Canadian Option:  AWM 2651 105C 300V VW1 3M NU  AWM IA 105C 300V FT1  
EU <50V

**Conductors:** 28 AWG 19 X 40 [ 19 X 0.079 ] Tinned Stranded Copper

## Electrical

**Voltage Rating:** USA: 300V      Canada: 300V      EU: <50V

**Insulation Resistance:**  $> 1 \times 10^{10} \Omega/10 \text{ ft. [ 3m ]}$

**Characteristic Impedance** Unbalanced: 106  $\Omega$

**Capacitance** Unbalanced: 13.3 pF/ft. [ 43.8 pF/m ]

**Inductance** Unbalanced: .15  $\mu\text{H/ft. [ 0.49 } \mu\text{H/m ]}$

**Propagation Delay** Unbalanced: 1.42 ns/ft. [ 4.66 ns/m ]

**Velocity of Propagation** Unbalanced: 72%

Note: Unbalanced is measured between ground-signal-ground conductors.

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-34970699  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

## Environmental

**Temperature Rating:** -20°C to +105°C

**Flammability Rating:** USA: VW-1      Canada: FT1

UL File No.: E42769, Style No.: 2651

### 3M Interconnect Solutions Division

6801 River Place Blvd.  
Austin, TX 78726-9000


For technical, sales or ordering information call  
**800-225-5373**

# .050" Medium Flex Life Cable

## 28 AWG Stranded, PVC

3539 Series

Number of Conductors	3M Part Number	Dimension A	Dimension B
09	<b>3539/09</b>	0.450 ± .010 [ 11.43 ]	0.400 ± .007 [ 10.16 ]
10	<b>3539/10</b>	0.500 ± .010 [ 12.70 ]	0.450 ± .007 [ 11.43 ]
14	<b>3539/14</b>	0.700 ± .010 [ 17.78 ]	0.650 ± .007 [ 16.51 ]
15	<b>3539/15</b>	0.750 ± .010 [ 19.05 ]	0.700 ± .007 [ 17.78 ]
16	<b>3539/16</b>	0.800 ± .015 [ 20.32 ]	0.750 ± .011 [ 19.05 ]
20	<b>3539/20</b>	1.000 ± .015 [ 25.40 ]	0.950 ± .011 [ 24.13 ]
24	<b>3539/24</b>	1.200 ± .015 [ 30.48 ]	1.150 ± .011 [ 29.21 ]
25	<b>3539/25</b>	1.250 ± .015 [ 31.75 ]	1.200 ± .011 [ 30.48 ]
26	<b>3539/26</b>	1.300 ± .015 [ 33.02 ]	1.250 ± .011 [ 31.75 ]
30	<b>3539/30</b>	1.500 ± .020 [ 38.10 ]	1.450 ± .015 [ 36.83 ]
34	<b>3539/34</b>	1.700 ± .020 [ 43.18 ]	1.650 ± .015 [ 41.91 ]
36	<b>3539/36</b>	1.800 ± .020 [ 45.72 ]	1.750 ± .015 [ 44.45 ]
37	<b>3539/37</b>	1.850 ± .020 [ 46.99 ]	1.800 ± .015 [ 45.72 ]
40	<b>3539/40</b>	2.000 ± .020 [ 50.80 ]	1.950 ± .015 [ 49.53 ]
50	<b>3539/50</b>	2.500 ± .020 [ 63.50 ]	2.450 ± .015 [ 62.23 ]
60	<b>3539/60</b>	3.000 ± .020 [ 76.20 ]	2.950 ± .015 [ 74.93 ]
64	<b>3539/64</b>	3.200 ± .020 [ 81.28 ]	3.150 ± .015 [ 80.01 ]




勝特力材料 886-3-5753170  
 胜特力电子(上海) 86-21-34970699  
 胜特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

Inch [mm]			
Tolerance Unless Noted			
	.0	.00	.000
Inch	±.1	±.01	±.005

[ ] Dimensions for Reference only

Note: Red marking on one edge of cable designates wire #1.

### Ordering Information



Note: Available in standard lengths of 100 feet or 300 feet per roll, please specify when ordering.

TS-0058-09  
Sheet 2 of 2

### 3M Interconnect Solutions Division

6801 River Place Blvd.  
Austin, TX 78726-9000

For technical, sales or ordering information call  
**800-225-5373**