

产品参数

低烟無滷電纜電纜LOW SMOKE NON HALOGEN WIRE&CABLE

構造:
Construction:



UL Style 3385 CAS AWM IA
 額定溫度: 105°C
 額定電壓: 300V
 參考標準: UL758,UL1581
 認證檔案號:E350758(XUTAI)

FILENO:E350758
 Rated temperature: 105°C
 Rated voltage: 300V
 Reference standard:UL Subject 758,UL1581
 File NO: E350758(XUTAI)

印字Marking:

AWM E350758 3385 xxAWG 105°C300V VW-1 XUTAI C AWM I A 105°C300V xxAWG FT2 LM

產品說明:

導體使用單支或絞銅線,34-10AWG鍍錫銅或裸銅線
 FR-PE絕緣
 通過WV-1及FT1/FT2,垂直耐燃測試或水平燃燒測試

Product Description

Solid or stranded,tinned or bare copper conductor34-10AWG
 FR-PE insulation
 Passes UL WV-1&cul FT1/FT2 vetrical flame testor

應用:

用于電子、電器設備內部連線

Application:

For internal wiring of electronic and electrical equipment

產品構造和典型性能參數(Product Data & Typical properties):

UL Style & CSA Type	導體Conductor			絕緣Insulation		Maximum Resistance 最大 導體直流電阻 (Kft20°C)	Minimum Resistance 最小 導體電阻 (-kmt.20°C)	Dielectric Strength 耐壓強度 (ACV, 1min)
	規格 Size (AWG)	構造 Construction (No/mm)	外徑 Out-Dia (mm)	厚度 Thick (mm)	外徑 Out-Dia (mm)			
UL3385 (Stranded) 絞線	34	7/0.05	0.15	0.38	0.80	586	100	2000
	32	7/0.080	0.25	0.38	0.90	586.00	100	2000
	30	7/0.100	0.31	0.38	1.10	381.00	100	2000
	28	7/0.127	0.38	0.38	1.20	239.00	100	2000
	26	7/0.160	0.48	0.38	1.30	150.00	100	2000
	24	11/0.160	0.61	0.38	1.45	94.20	100	2000
	22	17/0.160	0.76	0.38	1.60	59.40	100	2000
	20	21/0.178	0.94	0.38	1.85	36.70	100	2000
	18	34/0.178	1.19	0.38	2.10	23.20	100	2000
	16	26/0.250	1.49	0.38	2.35	14.60	100	2000
	14	41/0.250	1.19	0.38	2.85	8.96	100	2000
	12	65/0.250	1.49	0.38	/	5.64	100	2000
	10	105/0.250	2.95	0.38	/	3.55	100	2000