

Audio & Video

Speaker & Microphone

SPC-300/200



Description

1. 99..996% highly pure OFC conductor wire or OFC conductor multi-stranded with Tinned copper wire.
2. Conductor wires are stranded to cut down inductance and capacitance.
3. Flat design enable it to be installed under carpet.
4. The characteristics of low distortion, wide dynamic range and sweat sound quality..

SPC-100



Application:

Applies to the connection of speakers to amplifier in sound system.

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Part No.	Description
SPC100	3/35/0.12mm(105C)x2F, OD: 4.0x8.0mm
SPC200	7/15/0.10mm(105C)x2F,OD: 4.0x8.0mm
SPC300	(4/48/0.1mm, BC)+(3/48/0.11mm, TC) OD:5.0x10.0mm



Description

1. Conductor with highly pure OFC conductor
2. Insulation with high density foam PE
3. High density OFC braiding coverage to cut down inductance and capacitance.
4. Soft and highly flexible PVC jacket.

Application:

Apart from home use, it also applies to professional show occasion such as broadcasting studios and music.

