


Features

- Guard Ring Die Construction for Transient Protection
- Low Power Loss, High Efficiency
- High Surge Capability
- Very Low Forward Voltage Drop
- For Use in Low Voltage, High Frequency Inverters, OR'ing, and Polarity Protection Applications
- Plastic Material: UL Flammability Classification Rating 94V-0

Mechanical Data

- Case: POWERMITE®3 Molded Plastic
- Moisture sensitivity: Level 1 per J-STD-020A
- Terminals: Solderable per MIL-STD-202, Method 208
- Polarity: See Diagram
- Marking: See Sheet 2
- Weight: 0.072 grams (approx.)

UNDER DEVELOPMENT



POWERMITE®3		
Dim	Min	Max
A	4.03	4.09
B	6.40	6.61
C	.889 NOM	
D	1.83 NOM	
E	1.10	1.14
G	.178 NOM	
H	5.01	5.17
J	4.37	4.43
K	.178 NOM	
L	.71	.77
M	.36	.46
P	1.73	1.83
All Dimensions in mm		

Maximum Ratings @ T_A = 25°C unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

Characteristic	Symbol	Value	Unit
Peak Repetitive Reverse Voltage	V _{RRM}	40	V
Working Peak Reverse Voltage	V _{RWM}		
DC Blocking Voltage	V _R		
RMS Reverse Voltage	V _{R(RMS)}	28	V
Average Rectified Output Current (See also Figure 5)	I _o	5	A
per element		10	
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave Superimposed on Rated Load Per Package (JEDEC Method), total device	I _{FSM}	50	A
Typical Thermal Resistance Junction to Soldering Point Per Element	R _{θJS}	2.5	°C/W
Operating Temperature Range	T _j	-55 to +125	°C
Storage Temperature Range	T _{STG}	-55 to +150	°C

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Electrical Characteristics @ $T_A = 25^\circ\text{C}$ unless otherwise specified

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Breakdown Voltage (Note 1)	$V_{(BR)R}$	40	—	—	V	$I_R = 500\mu\text{A}$
Forward Voltage (Note 1)	Per Element V_F	—	0.45 0.39 0.53 0.50	0.48 0.42 0.575 0.55	V	$I_F = 5\text{A}, T_j = 25^\circ\text{C}$ $I_F = 5\text{A}, T_j = 100^\circ\text{C}$ $I_F = 10\text{A}, T_j = 25^\circ\text{C}$ $I_F = 10\text{A}, T_j = 100^\circ\text{C}$
Peak Reverse Current (Note 1)	Per Element I_R	—	35 4 10 2	150 10 80 5	μA mA μA mA	$V_R = 35\text{V}, T_j = 25^\circ\text{C}$ $V_R = 35\text{V}, T_j = 100^\circ\text{C}$ $V_R = 17.5\text{V}, T_j = 25^\circ\text{C}$ $V_R = 17.5\text{V}, T_j = 100^\circ\text{C}$
Total Capacitance	Per Element C_T	—	375	—	pF	$f = 1.0\text{MHz}, V_R = 4.0\text{V DC}$


Notes: 1. Short duration test pulse used to minimize self-heating effect.

Ordering Information (Note 2)

Device	Packaging	Shipping
SBM1040CT-13	POWERMITE®3	5000/Tape & Reel


Notes: 2. For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

Marking Information




SBM1040CT = Product type marking code
 D11 = Manufacturers' code marking
 YYWW = Date code marking
 YY = Last digit of year ex: 2 for 2002
 WW = Week code 01 to 52

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



V_F , INSTANTANEOUS FORWARD VOLTAGE (mV)
 Fig. 1 Typical Forward Characteristics, Per Element



V_R , INSTANTANEOUS REVERSE VOLTAGE (V)
 Fig. 2 Typical Reverse Characteristics, Per Element

UNDER DEVELOPMENT




Fig. 3 Max Non-Repetitive Peak Fwd Surge Current




Fig. 4 Typical Capacitance vs. Reverse Voltage, Per Element




Fig. 5 DC Forward Current Derating




Fig. 6 Forward Power Dissipation

- Notes:
1. $T_A = T_{SOLDERING\ POINT}$, $R_{\theta JS} = 2.5^\circ C/W$, $R_{\theta SA} = 0^\circ C/W$.
 2. Device mounted on GETEK substrate, 2"x2", 2 oz. copper, double-sided, cathode pad dimensions 0.75" x 1.0", anode pad dimensions 0.25" x 1.0". $R_{\theta JA}$ in range of 20-40°C/W.
 3. Device mounted on FR-4 substrate, 2"x2", 2 oz. copper, single-sided, pad layout as per Diodes Inc. suggested pad layout document AP02001 which can be found on our website at <http://www.diodes.com/datasheets/ap02001.pdf>. $R_{\theta JA}$ in range of 85-115°C/W.

UNDER DEVELOPMENT

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

POWERMITE is a registered trademark of Microsemi Corporation.