



Micro Commercial Components

Micro Commercial Components  
 20736 Marilla Street Chatsworth  
 CA 91311  
 Phone: (818) 701-4933  
 Fax: (818) 701-4939

## TIP110/111/112

### Features

- The complementary PNP types are the TIP115/116/117 respectively
- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0 and MSL Rating 1
- Marking: Part number

### Silicon NPN

### Darlington Power Transistor


#### Absolute Maximum Ratings @ T<sub>a</sub> = 25°C (unless otherwise noted)

Symbol	Parameter	Value	Unit
V <sub>CB0</sub> TIP110 TIP111 TIP112	Collector-base voltage (Open emitter)	60 80 100	V
V <sub>CE0</sub> TIP110 TIP111 TIP112	Collector-emitter voltage (Open base)	60 80 100	V
V <sub>EBO</sub>	Emitter-base Voltage(Open collector)	5	V
I <sub>C</sub>	Collector Current	2	A
I <sub>CM</sub>	Collector Current Pulse	4	A
I <sub>B</sub>	Base Current	0.05	A
P <sub>C</sub>	Total Device Dissipation(T <sub>a</sub> =25°C)	2	W
	Total Device Dissipation(T <sub>c</sub> =25°C)	50	W
T <sub>J</sub>	Junction Temperature	150	°C
T <sub>STG</sub>	Storage Temperature Range	-65 to +150	°C

#### Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Max	Units
V <sub>CE(SUS)</sub> TIP110 TIP111 TIP112	Collector-emitter sustaining voltage (I <sub>C</sub> =30mA; I <sub>B</sub> =0)	60 80 100		V
V <sub>CE(sat)</sub>	Collector-emitter Saturation Voltage (I <sub>C</sub> =2A; I <sub>B</sub> =0.008A)		2.5	V
V <sub>BE</sub>	Base-emitter Voltage (I <sub>C</sub> =2A; V <sub>CE</sub> =4V)		2.8	V
I <sub>CB0</sub> TIP110 TIP111 TIP112	Collector cut-off current (V <sub>CB</sub> =60V; I <sub>E</sub> =0) (V <sub>CB</sub> =80V; I <sub>E</sub> =0) (V <sub>CB</sub> =100V; I <sub>E</sub> =0)	1		mA
I <sub>CE0</sub> TIP110 TIP111 TIP112	Collector cut-off current (V <sub>CE</sub> =30V; V <sub>EB</sub> =0) (V <sub>CE</sub> =40V; V <sub>EB</sub> =0) (V <sub>CE</sub> =50V; V <sub>EB</sub> =0)	2		mA
I <sub>EBO</sub>	Emitter cut-off current (V <sub>EB</sub> =5V; I <sub>C</sub> =0)		2.0	mA
h <sub>FE</sub>	DC current gain (I <sub>C</sub> =1A; V <sub>CE</sub> =4V) (I <sub>C</sub> =2A; V <sub>CE</sub> =4V)	1000 500		
C <sub>OB</sub>	Output capacitance (I <sub>E</sub> =0; V <sub>CB</sub> =-10V, f=0.1MHz)		100	PF

### TO-220AB



DIM	DIMENSIONS				NOTE
	INCHES		MM		
A	.560	.625	14.22	15.88	
B	.380	.420	9.65	10.67	
C	.140	.190	3.56	4.82	
D	.020	.045	0.51	1.14	
F	.139	.161	3.53	4.09	∅
G	.190	.110	2.29	2.79	
H	---	.250	---	6.35	
J	.012	.025	0.30	0.64	
K	.500	.580	12.70	14.73	
L	.045	.060	1.14	1.52	
N	.190	.210	4.83	5.33	
Q	.100	.135	2.54	3.43	
R	.080	.115	2.04	2.92	
S	.045	.055	1.14	1.39	
T	.230	.270	5.84	6.86	
U	----	.050	----	1.27	
V	.045	----	1.15	----	

Notes:1.High Temperature Solder Exemption Applied, see EU Directive Annex 7.



Micro Commercial Components

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

## Ordering Information

Device	Packing
(Part Number)-BP	Bulk;1Kpcs/Box

### \*\*\*IMPORTANT NOTICE\*\*\*

*Micro Commercial Components Corp.* reserve the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp.* does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages.

### \*\*\*APPLICATIONS DISCLAIMER\*\*\*

Products offer by *Micro Commercial Components Corp.* are not intended for use in Medical, Aerospace or Military Applications.

[www.mccsemi.com](http://www.mccsemi.com)