

# Power Transistor (60V, 3A)


勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-34970699  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

## 2SD2394

### ●Features

- 1) Low saturation voltage.  
(Typ.  $V_{CE(sat)} = 0.3V$  at  $I_C / I_B = 2A / 0.2A$ )
- 2) Excellent DC current gain characteristics.
- 3) Wide SOA (safe operating area).

### ●External dimensions (Units : mm)



### ●Absolute maximum ratings (Ta = 25°C)

| Parameter                   | Symbol    | Limits     | Unit       |
|-----------------------------|-----------|------------|------------|
| Collector-base voltage      | $V_{CBO}$ | 80         | V          |
| Collector-emitter voltage   | $V_{CEO}$ | 60         | V          |
| Emitter-base voltage        | $V_{EBO}$ | 7          | V          |
| Collector current           | $I_C$     | 3          | A(DC)      |
|                             | $I_{CP}$  | 6          | A(Pulse) * |
| Collector power dissipation | $P_C$     | 2          | W          |
|                             |           | 25         | W(Tc=25°C) |
| Junction temperature        | $T_J$     | 150        | °C         |
| Storage temperature         | $T_{stg}$ | -55 ~ +150 | °C         |

\* Single pulse, Pw=100ms

### ●Packaging specifications and hFE

| Type                         | 2SD2394  |
|------------------------------|----------|
| Package                      | TO-220FN |
| hFE                          | EF       |
| Code                         | -        |
| Basic ordering unit (pieces) | 500      |

### ●Electrical characteristics (Ta = 25°C)

| Parameter                            | Symbol        | Min. | Typ. | Max. | Unit    | Conditions                           |
|--------------------------------------|---------------|------|------|------|---------|--------------------------------------|
| Collector-base breakdown voltage     | $BV_{CBO}$    | 80   | -    | -    | V       | $I_C = 50\mu A$                      |
| Collector-emitter breakdown voltage  | $BV_{CEO}$    | 60   | -    | -    | V       | $I_C = 1mA$                          |
| Emitter-base breakdown voltage       | $BV_{EBO}$    | 7    | -    | -    | V       | $I_E = 50\mu A$                      |
| Collector cutoff current             | $I_{CBO}$     | -    | -    | 10   | $\mu A$ | $V_{CB} = 60V$                       |
| Emitter cutoff current               | $I_{EBO}$     | -    | -    | 10   | $\mu A$ | $V_{EB} = 7V$                        |
| Collector-emitter saturation voltage | $V_{CE(sat)}$ | -    | -    | 1    | V       | $I_C / I_B = 2A / 0.2A$              |
|                                      | $V_{CE(sat)}$ | -    | -    | 0.8  | V       |                                      |
| Base-emitter saturation voltage      | $V_{BE(sat)}$ | -    | -    | 1.5  | V       | $I_C / I_B = 2A / 0.2A$ *            |
| DC current transfer ratio            | $h_{FE}$      | 100  | -    | 320  | -       | $V_{CE} / I_C = 5V / 0.5A$           |
| Transition frequency                 | $f_r$         | -    | 8    | -    | MHz     | $V_{CE} = 5V, I_E = -0.5A, f = 5MHz$ |
| Output capacitance                   | $C_{ob}$      | -    | 35   | -    | pF      | $V_{CB} = 10V, I_E = 0A, f = 1MHz$ * |

\* Measured using pulse current.