

CentralTM Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

MPS8598
MPS8599

PNP SILICON TRANSISTOR

JEDEC TO-92 CASE (EBC)

勝特力電材超市-龍山店 886-3-5773766
勝特力電材超市-光復店 886-3-5729570
勝特力電子(上海) 86-21-34970699
勝特力電子(深圳) 86-755-83298787
<http://www.100y.com.tw>

DESCRIPTION

The CENTRAL SEMICONDUCTOR MPS8598, MPS8599 types are Epoxy Molded Silicon PNP Transistors designed for general purpose audio amplifier applications and complementary circuits. The NPN complementary types are MPS8098 and MPS8099.

MAXIMUM RATINGS (T_A=25°C)

	SYMBOL	MPS8598	MPS8599	UNITS
Collector-Base Voltage	V _{CBO}	60	80	V
Collector-Emitter Voltage	V _{CEO}	60	80	V
Emitter-Base Voltage	V _{EBO}	5.0	5.0	V
Collector Current	I _C	500	500	mA
Power Dissipation	P _D	625	625	mW
Operating and Storage				
Junction Temperature	T _J , T _{stg}	-65 to +150		°C
Thermal Resistance	θ _{JA}	200		°C/W

ELECTRICAL CHARACTERISTICS (T_A=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	MPS8598		MPS8599		UNITS
		MIN	MAX	MIN	MAX	
I _{CBO}	V _{CB} =Rated V _{CBO}		0.1		0.1	μA
I _{CEO}	V _{CE} =60V		0.1		0.1	μA
I _{EBO}	V _{BE} =4.0V		0.1		0.1	μA
BV _{CBO}	I _C =100μA	60		80		V
BV _{CEO}	I _C =10mA	60		80		V
BV _{EBO}	I _C =10μA	5.0		5.0		V
V _{CE(SAT)}	I _C =100mA, I _B =5.0mA		0.4		0.4	V
V _{CE(SAT)}	I _C =100mA, I _B =10mA		0.3		0.3	V
V _{BE(ON)}	V _{CE} =5.0V, I _C =1.0mA	0.5	0.7	-	-	V
V _{BE(ON)}	V _{CE} =5.0V, I _C =10mA	-	-	0.6	0.8	V
h _{FE}	V _{CE} =5.0V, I _C =1.0mA	100	300	100	300	
h _{FE}	V _{CE} =5.0V, I _C =10mA	100		100		
h _{FE}	V _{CE} =5.0V, I _C =100mA	75		75		
f _T	V _{CE} =5.0V, I _C =10mA, f=100MHz	150		150		MHz
C _{ob}	V _{CB} =5.0V, I _E =0, f=1.0MHz		8.0		8.0	pF
C _{ib}	V _{CB} =0.5V, I _C =0, f=1.0MHz		30		30	pF

OUTSTANDING SUPPORT AND SUPERIOR SERVICES



PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centrasemi.com

勝特力電材超市-龍山店 886-3-5773766
勝特力電材超市-光復店 886-3-5729570
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
<http://www.100y.com.tw>

Worldwide Field Representatives:

www.centrasemi.com/wwreps

Worldwide Distributors:

www.centrasemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centrasemi.com/terms