

# 2SD1559

Silicon NPN Triple Diffused

# HITACHI

ADE-208-914 (Z)

1st. Edition


Sep. 2000

## Application


Low frequency power amplifier complementary pair with 2SB1079

## Outline

TO-3P



1. Base
2. Collector (Flange)
3. Emitter



勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-34970699  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

## Absolute Maximum Ratings (Ta = 25°C)

Item	Symbol	Ratings	Unit
Collector to base voltage	$V_{CBO}$	100	V
Collector to emitter voltage	$V_{CEO}$	100	V
Emitter to base voltage	$V_{EBO}$	7	V
Collector current	$I_C$	20	A
Collector peak current	$I_{C(peak)}$	30	A
Base current	$I_B$	3	A
Collector power dissipation	$P_C^{*1}$	100	W
Junction temperature	$T_j$	150	°C
Storage temperature	$T_{stg}$	-55 to +150	°C


Note: 1. Value at  $T_C = 25^\circ\text{C}$ .

## Electrical Characteristics (Ta = 25°C)


Item	Symbol	Min	Typ	Max	Unit	Test conditions
Collector to base breakdown voltage	$V_{(BR)CBO}$	100	—	—	V	$I_C = 0.1 \text{ mA}, I_E = 0$
Collector to emitter breakdown voltage	$V_{(BR)CEO}$	100	—	—	V	$I_C = 25 \text{ mA}, R_{BE} = \infty$
Collector to emitter sustain voltage	$V_{CEO(sus)}$	100	—	—	V	$I_C = 200 \text{ mA}, R_{BE} = \infty^{*1}$
Emitter to base breakdown voltage	$V_{(BR)EBO}$	7	—	—	V	$V_{EB} = 50 \text{ mA}, I_C = 0$
Collector cutoff current	$I_{CBO}$	—	—	100	$\mu\text{A}$	$V_{CB} = 100 \text{ V}, I_E = 0$
	$I_{CEO}$	—	—	1.0	mA	$V_{CE} = 80 \text{ V}, R_{BE} = \infty$
DC current transfer ratio	$h_{FE}$	1000	—	20000		$V_{CE} = 3 \text{ V}, I_C = 10 \text{ A}^{*1}$
Collector to emitter saturation voltage	$V_{CE(sat)1}$	—	—	2.0	V	$I_C = 10 \text{ A}, I_B = 20 \text{ mA}^{*1}$
Base to emitter saturation voltage	$V_{BE(sat)1}$	—	—	2.5	V	
Collector to emitter saturation voltage	$V_{CE(sat)2}$	—	—	3.0	V	$I_C = 20 \text{ A}, I_B = 200 \text{ mA}^{*1}$
Base to emitter saturation voltage	$V_{BE(sat)2}$	—	—	3.5	V	
Turn on time	$t_{on}$	—	1.0	—	$\mu\text{s}$	$I_C = 10 \text{ A}, I_{B1} = -I_{B2} = 20 \text{ mA}$
Storage time	$t_{stg}$	—	9.0	—	$\mu\text{s}$	
Fall time	$t_f$	—	3.0	—	$\mu\text{s}$	

Note: 1. Pulse test.


Maximum Collector Dissipation Curve




Area of Safe Operation






Typical Output Characteristics





DC Current Transfer Ratio vs. Collector Current





Package Dimensions

Unit: mm



Hitachi Code	TO-3P
JEDEC	—
EIAJ	Conforms
Mass (reference value)	5.0 g

**勝特力材料 886-3-5753170**  
**勝特力电子(上海) 86-21-34970699**  
**勝特力电子(深圳) 86-755-83298787**  
[Http://www.100y.com.tw](http://www.100y.com.tw)