

# International **IR** Rectifier


Data Sheet No. PD60260

## IRS2108/IRS21084(S)PbF HALF-BRIDGE DRIVER

### Features

- Floating channel designed for bootstrap operation
- Fully operational to +600 V
- Tolerant to negative transient voltage,  $dV/dt$  immune
- Gate drive supply range from 10 V to 20 V
- Undervoltage lockout for both channels
- 3.3 V, 5 V, and 15 V input logic compatible
- Cross-conduction prevention logic
- Matched propagation delay for both channels
- High-side output in phase with HIN input
- Low-side output out of phase with LIN input
- Logic and power ground +/- 5 V offset
- Internal 540 ns deadtime, and programmable up to 5  $\mu$ s with one external  $R_{DT}$  resistor (IRS21084)
- Lower  $di/dt$  gate driver for better noise immunity
- RoHS compliant

### Packages




### Description

The IRS2108/IRS21084 are high voltage, high speed power MOSFET and IGBT drivers with dependent high- and low-side referenced output channels. Proprietary HVIC and latch immune CMOS technologies enable ruggedized monolithic construction. The logic input is compatible with standard CMOS or LSTTL output, down to 3.3 V logic. The output drivers feature a high pulse current buffer stage designed for minimum driver cross-conduction. The floating channel can be used to drive an N-channel power MOSFET or IGBT in the high-side configuration which operates up to 600 V.

### Feature Comparison

| Part      | Input logic | Cross-conduction prevention logic | Deadtime (ns)           | Ground Pins          | $t_{on}/t_{off}$ (ns) |
|-----------|-------------|-----------------------------------|-------------------------|----------------------|-----------------------|
| 2106/2301 | HIN/LIN     | no                                | none                    | COM                  | 220/200               |
| 21064     |             |                                   |                         | V <sub>ss</sub> /COM |                       |
| 2108      |             |                                   |                         | COM                  |                       |
| 21084     | HIN/LIN     | yes                               | Internal 540            | V <sub>ss</sub> /COM | 220/200               |
| 2109/2302 |             |                                   | Programmable 540 - 5000 | COM                  |                       |
| 21094     |             |                                   | Internal 540            | V <sub>ss</sub> /COM |                       |
| 2304      | HIN/LIN     | yes                               | Internal 100            | COM                  | 160/140               |

### Typical Connection



International  
**IR** Rectifier

## IRS2108/IRS21084(S)PbF

### Absolute Maximum Ratings

Absolute maximum ratings indicate sustained limits beyond which damage to the device may occur. All voltage parameters are absolute voltages referenced to COM. The thermal resistance and power dissipation ratings are measured under board mounted and still air conditions.

| Symbol              | Definition                                                            |                | Min.                  | Max.                  | Units |
|---------------------|-----------------------------------------------------------------------|----------------|-----------------------|-----------------------|-------|
| V <sub>B</sub>      | High-side floating absolute voltage                                   |                | -0.3                  | 625                   | V     |
| V <sub>S</sub>      | High-side floating supply offset voltage                              |                | V <sub>B</sub> - 25   | V <sub>B</sub> + 0.3  |       |
| V <sub>HO</sub>     | High-side floating output voltage                                     |                | V <sub>S</sub> - 0.3  | V <sub>B</sub> + 0.3  |       |
| V <sub>CC</sub>     | Low-side and logic fixed supply voltage                               |                | -0.3                  | 25                    |       |
| V <sub>LO</sub>     | Low-side output voltage                                               |                | -0.3                  | V <sub>CC</sub> + 0.3 |       |
| DT                  | Programmable deadtime pin voltage (IRS21084 only)                     |                | V <sub>SS</sub> - 0.3 | V <sub>CC</sub> + 0.3 |       |
| V <sub>IN</sub>     | Logic input voltage (H <sub>IN</sub> & $\overline{L}$ <sub>IN</sub> ) |                | V <sub>SS</sub> - 0.3 | V <sub>CC</sub> + 0.3 |       |
| V <sub>SS</sub>     | Logic ground (IRS21084 only )                                         |                | V <sub>CC</sub> - 25  | V <sub>CC</sub> + 0.3 |       |
| dV <sub>S</sub> /dt | Allowable offset supply voltage transient                             |                | —                     | 50                    | V/ns  |
| P <sub>D</sub>      | Package power dissipation @ TA ≤ +25 °C                               | (8 lead PDIP)  | —                     | 1.0                   | W     |
|                     |                                                                       | (8 lead SOIC)  | —                     | 0.625                 |       |
|                     |                                                                       | (14 lead PDIP) | —                     | 1.6                   |       |
|                     |                                                                       | (14 lead SOIC) | —                     | 1.0                   |       |
| R <sub>thJA</sub>   | Thermal resistance, junction to ambient                               | (8 lead PDIP)  | —                     | 125                   | °C/W  |
|                     |                                                                       | (8 lead SOIC)  | —                     | 200                   |       |
|                     |                                                                       | (14 lead PDIP) | —                     | 75                    |       |
|                     |                                                                       | (14 lead SOIC) | —                     | 120                   |       |
| T <sub>J</sub>      | Junction temperature                                                  |                | —                     | 150                   | °C    |
| T <sub>S</sub>      | Storage temperature                                                   |                | -50                   | 150                   |       |
| T <sub>L</sub>      | Lead temperature (soldering, 10 seconds)                              |                | —                     | 300                   |       |

### Recommended Operating Conditions

The input/output logic timing diagram is shown in Fig. 1. For proper operation the device should be used within the recommended conditions. The  $V_S$  and  $V_{SS}$  offset rating are tested with all supplies biased at a 15 V differential.

| Symbol   | Definition                                        | Min.                 | Max.       | Units      |
|----------|---------------------------------------------------|----------------------|------------|------------|
| $V_B$    | High-side floating supply absolute voltage        | $V_S + 10$           | $V_S + 20$ | V          |
| $V_S$    | High-side floating supply offset voltage          | Note 1               | 600        |            |
| $V_{HO}$ | High-side floating output voltage                 | $V_S$                | $V_B$      |            |
| $V_{CC}$ | Low-side and logic fixed supply voltage           | 10                   | 20         |            |
| $V_{LO}$ | Low-side output voltage                           | 0                    | $V_{CC}$   |            |
| $V_{IN}$ | Logic input voltage                               | IRS2108<br>COM       | $V_{CC}$   |            |
|          |                                                   | IRS21084<br>$V_{SS}$ | $V_{CC}$   |            |
| DT       | Programmable deadtime pin voltage (IRS21084 only) | $V_S$                | $V_{CC}$   |            |
| $V_{SS}$ | Logic ground (IRS21084 only)                      | -5                   | 5          | $^\circ C$ |
| $T_A$    | Ambient temperature                               | -40                  | 125        |            |

Note 1: Logic operational for  $V_S$  of -5 V to +600 V. Logic state held for  $V_S$  of -5 V to  $-V_{BS}$ . (Please refer to the Design Tip DT97-3 for more details).

International  
**IR** Rectifier

## IRS2108/IRS21084(S)PbF

### Dynamic Electrical Characteristics

$V_{BIAS}$  ( $V_{CC}$ ,  $V_{BS}$ ) = 15 V,  $V_{SS}$  = COM,  $C_L$  = 1000 pF,  $T_A$  = 25 °C,  $DT$  =  $V_{SS}$  unless otherwise specified.

| Symbol    | Definition                                                                             | Min. | Typ. | Max. | Units   | Test Conditions                          |
|-----------|----------------------------------------------------------------------------------------|------|------|------|---------|------------------------------------------|
| $t_{on}$  | Turn-on propagation delay                                                              | —    | 220  | 300  | ns      | $V_S = 0$ V                              |
| $t_{off}$ | Turn-off propagation delay                                                             | —    | 200  | 280  |         | $V_S = 0$ V or 600 V                     |
| MT        | Delay matching $ t_{on} - t_{off} $                                                    | —    | 0    | 30   |         |                                          |
| $t_r$     | Turn-on rise time                                                                      | —    | 100  | 220  |         | $V_S = 0$ V                              |
| $t_f$     | Turn-off fall time                                                                     | —    | 35   | 80   |         | $R_{DT} = 0 \Omega$                      |
| DT        | Deadtime: LO turn-off to HO turn-on (DTLO-HO) &<br>HO turn-off to LO turn-on (DTHO-LO) | 400  | 540  | 680  | $\mu s$ | $R_{DT} = 200 \text{ k}\Omega$ (IR21084) |
|           |                                                                                        | 4    | 5    | 6    |         |                                          |
| MDT       | Deadtime matching = $ DTLO-HO - DTHO-LO $                                              | —    | 0    | 60   | ns      | $R_{DT} = 0 \Omega$                      |
|           |                                                                                        | —    | 0    | 600  |         | $R_{DT} = 200 \text{ k}\Omega$ (IR21084) |

### Static Electrical Characteristics



$V_{BIAS}$  ( $V_{CC}$ ,  $V_{BS}$ ) = 15 V,  $V_{SS}$  = COM,  $DT = V_{SS}$  and  $T_A$  = 25 °C unless otherwise specified. The  $V_{IL}$ ,  $V_{IH}$ , and  $I_{IN}$  parameters are referenced to  $V_{SS}/COM$  and are applicable to the respective input leads: HIN and LIN. The  $V_O$ ,  $I_O$ , and  $R_{on}$  parameters are referenced to COM and are applicable to the respective output leads: HO and LO.

| Symbol                     | Definition                                                         | Min. | Typ. | Max. | Units   | Test Conditions                              |
|----------------------------|--------------------------------------------------------------------|------|------|------|---------|----------------------------------------------|
| $V_{IH}$                   | Logic "1" input voltage for HIN & logic "0" for LIN                | 2.5  | —    | —    | V       | $V_{CC} = 10$ V to 20 V                      |
| $V_{IL}$                   | Logic "0" input voltage for HIN & logic "1" for LIN                | —    | —    | 0.8  |         |                                              |
| $V_{OH}$                   | High level output voltage, $V_{BIAS} - V_O$                        | —    | 0.05 | 0.2  |         | $I_O = 2$ mA                                 |
| $V_{OL}$                   | Low level output voltage, $V_O$                                    | —    | 0.02 | 0.1  |         |                                              |
| $I_{LK}$                   | Offset supply leakage current                                      | —    | —    | 50   | $\mu A$ | $V_B = V_S = 600$ V                          |
| $I_{QBS}$                  | Quiescent $V_{BS}$ supply current                                  | 20   | 75   | 130  |         | $V_{IN} = 0$ V or 5 V                        |
| $I_{QCC}$                  | Quiescent $V_{CC}$ supply current                                  | 0.4  | 1.0  | 1.6  | mA      | $V_{IN} = 0$ V or 5 V<br>$R_{DT} = 0 \Omega$ |
| $I_{IN+}$                  | Logic "1" input bias current                                       | —    | 5    | 20   | $\mu A$ | $HIN = 5$ V, $LIN = 0$ V                     |
| $I_{IN-}$                  | Logic "0" input bias current                                       | —    | —    | 5    |         | $HIN = 0$ V, $LIN = 5$ V                     |
| $V_{CCUV+}$<br>$V_{BSUV+}$ | $V_{CC}$ and $V_{BS}$ supply undervoltage positive going threshold | 8.0  | 8.9  | 9.8  | V       |                                              |
| $V_{CCUV-}$<br>$V_{BSUV-}$ | $V_{CC}$ and $V_{BS}$ supply undervoltage negative going threshold | 7.4  | 8.2  | 9.0  |         |                                              |
| $V_{CCUVH}$<br>$V_{BSUVH}$ | Hysteresis                                                         | 0.3  | 0.7  | —    |         |                                              |
| $I_{O+}$                   | Output high short circuit pulsed current                           | 120  | 290  | —    | mA      | $V_O = 0$ V,<br>$PW \leq 10 \mu s$           |
| $I_{O-}$                   | Output low short circuit pulsed current                            | 250  | 600  | —    |         | $V_O = 15$ V,<br>$PW \leq 10 \mu s$          |

International  
**IR** Rectifier

## IRS2108/IRS21084(S)PbF

### Functional Block Diagram



International  
**IR** Rectifier

## IRS2108/IRS21084(S)PbF

### Lead Definitions

| Symbol          | Description                                                                                                         |
|-----------------|---------------------------------------------------------------------------------------------------------------------|
| HIN             | Logic input for high-side gate driver output (HO), in phase (referenced to COM for IRS2108 and VSS for IRS21084)    |
| LIN             | Logic input for low-side gate driver output (LO), out of phase (referenced to COM for IRS2108 and VSS for IRS21084) |
| DT              | Programmable deadtime lead, referenced to VSS (IR21084 only)                                                        |
| VSS             | Logic ground (IRS21084 only)                                                                                        |
| V <sub>B</sub>  | High-side floating supply                                                                                           |
| HO              | High-side gate driver output                                                                                        |
| V <sub>S</sub>  | High-side floating supply return                                                                                    |
| V <sub>CC</sub> | Low-side and logic fixed supply                                                                                     |
| LO              | Low-side gate driver output                                                                                         |
| COM             | Low-side return                                                                                                     |

### Lead Assignments

|                                               |                                                |
|-----------------------------------------------|------------------------------------------------|
| <p>8 Lead PDIP</p> <p><b>IRS2108PbF</b></p>   | <p>8 Lead SOIC</p> <p><b>IRS2108SPbF</b></p>   |
| <p>14 Lead PDIP</p> <p><b>IRS21084PbF</b></p> | <p>14 Lead SOIC</p> <p><b>IRS21084SPbF</b></p> |

International  
**IR** Rectifier

## IRS2108/IRS21084(S)PbF




Figure 1. Input/Output Timing Diagram





Figure 2. Switching Time Waveform Definitions






Figure 3. Deadtime Waveform Definitions

International  
**IR** Rectifier


## IRS2108/IRS21084(S)PbF




**Figure 4A. Turn-On Propagation Delay vs. Temperature**



**Figure 4B. Turn-On Propagation Delay vs. Supply Voltage**



**Figure 5A. Turn-Off Propagation Delay vs. Temperature**



**Figure 5B. Turn-Off Propagation Delay vs. Supply Voltage**

International  
**IR** Rectifier

## IRS2108/IRS21084(S)PbF




Figure 6A. Turn-On Rise Time vs. Temperature




Figure 6B. Turn-On Rise Time vs. Supply Voltage




Figure 7A. Turn-Off Fall Time vs. Temperature




Figure 7B. Turn-Off Fall Time vs. Input voltage

International  
**IR** Rectifier

## IRS2108/IRS21084(S)PbF




Figure 8A. Deadtime vs. Temperature




Figure 8B. Deadtime vs. Supply Voltage




Figure 8C. Deadtime vs. R<sub>DT</sub>  
 (IR21084 Only)






Figure 9A. Logic "1" Input Voltage  
 vs. Temperature

International  
**IR** Rectifier


## IRS2108/IRS21084(S)PbF




**Figure 9B. Logic "1" Input Voltage vs. Supply Voltage**



**Figure 10A. Logic "0" Input Voltage vs. Temperature**




**Figure 10B. Logic "0" Input Voltage vs. Supply Voltage**




**Figure 11A. High Level Output Voltage vs. Temperature**

International  
**IR** Rectifier


## IRS2108/IRS21084(S)PbF




**Figure 11B. High Level Output Voltage vs. Supply Voltage**



**Figure 12A. Low Level Output Voltage vs. Temperature**



**Figure 12B. Low Level Output Voltage vs. Supply Voltage**



**Figure 13A. Offset Supply Leakage Current vs. Temperature**

International  
**IR** Rectifier

## IRS2108/IRS21084(S)PbF




Figure 13B. Offset Supply Leakage Current vs. Temperature




Figure 14A.  $V_{BS}$  Supply Current vs. Temperature




Figure 14B.  $V_{BS}$  Supply Current vs. Supply Voltage






Figure 15A.  $V_{CC}$  Supply Current vs. Temperature

International  
**IOR** Rectifier


## IRS2108/IRS21084(S)PbF




**Figure 15B. V<sub>CC</sub> Supply Current vs. Supply Voltage**



**Figure 16A. Logic "1" Input Current vs. Temperature**




**Figure 16B. Logic "1" Input Current vs. Supply Voltage**




**Figure 17A. Logic "0" Input Bias Current vs. Temperature**

International  
**IR** Rectifier


## IRS2108/IRS21084(S)PbF




**Figure 17B. Logic "0" Input Bias Current vs. Voltage**



**Figure 18. V<sub>CC</sub> Undervoltage Threshold (+) vs. Temperature**



**Figure 19. V<sub>CC</sub> Undervoltage Threshold (-) vs. Temperature**



**Figure 20. V<sub>BS</sub> Undervoltage Threshold (+) vs. Temperature**

International  
**IR** Rectifier

## IRS2108/IRS21084(S)PbF




Figure 21.  $V_{BS}$  Undervoltage Threshold (-) vs. Temperature




Figure 22A. Output Source Current vs. Temperature




Figure 22B. Output Source Current vs. Supply Voltage




Figure 23A. Output Sink Current vs. Temperature

International  
**IR** Rectifier

## IRS2108/IRS21084(S)PbF




Figure 23B. Output Sink Current vs. Supply Voltage




Figure 24. Maximum V<sub>s</sub> Negative Offset vs. Supply Voltage




Figure 25. IRS2108 vs. Frequency (IRFBC20),  
 $R_{gate}=33\ \Omega$ ,  $V_{CC}=15\ V$




Figure 26. IRS2108 vs. Frequency (IRFBC30),  
 $R_{gate}=22\ \Omega$ ,  $V_{CC}=15\ V$

International  
**IR** Rectifier

## IRS2108/IRS21084(S)PbF




Figure 27. IRS2108 vs. Frequency (IRFBC40),  
 $R_{gate}=15\ \Omega$ ,  $V_{CC}=15\ V$




Figure 28. IRS2108 vs. Frequency (IRFPE50),  
 $R_{gate}=10\ \Omega$ ,  $V_{CC}=15\ V$




Figure 29. IRS21084 vs. Frequency (IRFBC20),  
 $R_{gate}=33\ \Omega$ ,  $V_{CC}=15\ V$




Figure 30. IRS21084 vs. Frequency (IRFBC30),  
 $R_{gate}=22\ \Omega$ ,  $V_{CC}=15\ V$

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-34970699  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

International  
**IR** Rectifier

## IRS2108/IRS21084(S)PbF




Figure 31. IRS21084 vs. Frequency (IRFBC40),  
 $R_{gate}=15\ \Omega$ ,  $V_{CC}=15\ V$




Figure 32. IRS21084 vs. Frequency (IRFPE50),  
 $R_{gate}=10\ \Omega$ ,  $V_{CC}=15\ V$




Figure 33. IRS2108S vs. Frequency (IRFBC20),  
 $R_{gate}=33\ \Omega$ ,  $V_{CC}=15\ V$




Figure 34. IRS2108S vs. Frequency (IRFBC30),  
 $R_{gate}=22\ \Omega$ ,  $V_{CC}=15\ V$

International  
**IR** Rectifier

## IRS2108/IRS21084(S)PbF




Figure 35. IRS2108S vs. Frequency (IRFBC40),  
 $R_{gate}=15\ \Omega$ ,  $V_{CC}=15\ V$




Figure 36. IRS2108S vs. Frequency (IRFPE50),  
 $R_{gate}=10\ \Omega$ ,  $V_{CC}=15\ V$




Figure 37. IRS21084S vs. Frequency (IRFBC20),  
 $R_{gate}=33\ \Omega$ ,  $V_{CC}=15\ V$




Figure 38. IRS21084S vs. Frequency (IRFBC30),  
 $R_{gate}=22\ \Omega$ ,  $V_{CC}=15\ V$

International  
**IR** Rectifier

## IRS2108/IRS21084(S)PbF




Figure 39. IRS21084S vs. Frequency (IRFBC40),  
 $R_{gate}=15\ \Omega$ ,  $V_{CC}=15\ V$






Figure 40. IRS21084S vs. Frequency (IRFPE50),  
 $R_{gate}=10\ \Omega$ ,  $V_{CC}=15\ V$

International  
**IOR** Rectifier



## IRS2108/IRS21084(S)PbF

### Case outlines



International  
**IR** Rectifier


## IRS2108/IRS21084(S)PbF



International  
**IR** Rectifier


## IRS2108/IRS21084(S)PbF

**Tape & Reel**  
**8-lead SOIC**



CARRIER TAPE DIMENSION FOR 8SOICN

| Code | Metric |       | Imperial |       |
|------|--------|-------|----------|-------|
|      | Min    | Max   | Min      | Max   |
| A    | 7.90   | 8.10  | 0.311    | 0.318 |
| B    | 3.90   | 4.10  | 0.153    | 0.161 |
| C    | 11.70  | 12.30 | 0.46     | 0.484 |
| D    | 5.45   | 5.55  | 0.214    | 0.218 |
| E    | 6.30   | 6.50  | 0.248    | 0.255 |
| F    | 5.10   | 5.30  | 0.200    | 0.208 |
| G    | 1.50   | n/a   | 0.059    | n/a   |
| H    | 1.50   | 1.60  | 0.059    | 0.062 |




REEL DIMENSIONS FOR 8SOICN

| Code | Metric |        | Imperial |        |
|------|--------|--------|----------|--------|
|      | Min    | Max    | Min      | Max    |
| A    | 329.60 | 330.25 | 12.976   | 13.001 |
| B    | 20.95  | 21.45  | 0.824    | 0.844  |
| C    | 12.80  | 13.20  | 0.503    | 0.519  |
| D    | 1.95   | 2.45   | 0.767    | 0.096  |
| E    | 98.00  | 102.00 | 3.858    | 4.015  |
| F    | n/a    | 18.40  | n/a      | 0.724  |
| G    | 14.50  | 17.10  | 0.570    | 0.673  |
| H    | 12.40  | 14.40  | 0.488    | 0.566  |

International  
**IR** Rectifier


## IRS2108/IRS21084(S)PbF

**Tape & Reel**  
**14-lead SOIC**



CARRIER TAPE DIMENSION FOR 14SOICN

| Code | Metric |       | Imperial |       |
|------|--------|-------|----------|-------|
|      | Min    | Max   | Min      | Max   |
| A    | 7.90   | 8.10  | 0.311    | 0.318 |
| B    | 3.90   | 4.10  | 0.153    | 0.161 |
| C    | 15.70  | 16.30 | 0.618    | 0.641 |
| D    | 7.40   | 7.60  | 0.291    | 0.299 |
| E    | 6.40   | 6.60  | 0.252    | 0.260 |
| F    | 9.40   | 9.60  | 0.370    | 0.378 |
| G    | 1.50   | n/a   | 0.059    | n/a   |
| H    | 1.50   | 1.60  | 0.059    | 0.062 |



REEL DIMENSIONS FOR 14SOICN


| Code | Metric |        | Imperial |        |
|------|--------|--------|----------|--------|
|      | Min    | Max    | Min      | Max    |
| A    | 329.60 | 330.25 | 12.976   | 13.001 |
| B    | 20.95  | 21.45  | 0.824    | 0.844  |
| C    | 12.80  | 13.20  | 0.503    | 0.519  |
| D    | 1.95   | 2.45   | 0.767    | 0.096  |
| E    | 98.00  | 102.00 | 3.858    | 4.015  |
| F    | n/a    | 22.40  | n/a      | 0.881  |
| G    | 18.50  | 21.10  | 0.728    | 0.830  |
| H    | 16.40  | 18.40  | 0.645    | 0.724  |

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-34970699  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

International  
**IR** Rectifier

## IRS2108/IRS21084(S)PbF

### LEADFREE PART MARKING INFORMATION



### ORDER INFORMATION

|                                       |                                         |
|---------------------------------------|-----------------------------------------|
| 8-Lead PDIP IRS2108PbF                | 14-Lead PDIP IRS21084PbF                |
| 8-Lead SOIC IRS2108SPbF               | 14-Lead SOIC IRS21084SPbF               |
| 8-Lead SOIC Tape & Reel IRS2108STRPbF | 14-Lead SOIC Tape & Reel IRS21084STRPbF |

International  
**IR** Rectifier

SOIC8 &14 are MSL2 qualified.  
This product has been designed and qualified for the industrial level.  
Qualification standards can be found at [www.irf.com](http://www.irf.com)  
**IR WORLD HEADQUARTERS:** 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105  
Data and specifications subject to change without notice. 12/4/2006