

*QFP variations e.g. BQFP..

Series IC51 (Clamshell)
 QFP, PQFP, TQFP and MQUAD®

0.4mm to 1.27 Pitch

Specifications

- Insulation Resistance: 1,000MΩ min. at 100V DC
- Dielectric Withstanding Voltage: for 1 minute (socket depended)
- Contact Resistance: 30mΩ max. at 10mA/20mV max.
- Operating Temperature Range: -40°C to +150°C (for type PEI/PSF)
 -55°C to +170°C (for type PES)
 -55°C to +170°C (for type PEI)
- Mating Cycles: 10,000 insertions min.

Materials and Finish

- Housing: Polysulphone (PSF), glass-filled
 Polyethersulphone (PES), glass-filled
 Polyetherimide (PEI), glass-filled
- Contacts: Beryllium Copper (BeCu)
- Plating: Gold over Nickel



Part Number (Details)

IC51 - 064 4 - 807

Series No.	064	4	807
No. of Contact Pins			
Number of Sides with Contacts			
Design Number			

As specifications for this product differ by pitch and material-mix, please contact our Sales Department for detailed information.

Series IC357 and IC402 (Open Top)
 Quad Flat Package (QFP) with 2-Point Contact Type


0.4 to 0.8mm Pitch

Specifications

- Insulation Resistance: 1,000MΩ min. at 500V DC, pitch 0.4 to 0.8
- Dielectric Withstanding Voltage: 100V AC for 1 minute, pitch 0.5 to 0.8
- Contact Resistance: 30mΩ max. at 10mA/20mV max.
- Operating Temperature Range: -40°C to +150°C
- Mating Cycles: 10,000 insertions min.
- Contact Force: 20g to 45g per pin

Materials and Finish

- Housing: Polyetherimide (PEI), glass-filled
 Polyethersulphone (PES) glass-filled
- Contacts: Beryllium Copper (BeCu)
- Plating: Gold over Nickel



Part Number (Details)

IC357 - 100 4 - 002 *

Series No.	100	4	002	*
No. of Contact Pins				
Number of Sides with Contacts				
Design Number				
Positioning Pin				
N = Without Positioning Pin				
P = With Positioning Pin				

Series IC234 (Open Top)
 Quad Flat Package (QFP) with Shoulder Contact Type


0.4 to 0.8mm Pitch

Specifications

- Insulation Resistance: 1,000MΩ min. at 100V DC pitch 0.4, 0.5
 1,000MΩ min. at 500V DC pitch 0.65, 0.8
- Dielectric Withstanding Voltage: 100V AC for 1 minute pitch 0.4, 0.5
 500V AC for 1 minute pitch 0.65
 700V AC for 1 minute pitch 0.8
- Contact Resistance: 30mΩ max. at 10mA/20mV max.
- Operating Temperature Range: -40°C to +150°C
- Contact Force: 20g to 80g per pin
- Mating Cycles: 10,000 insertions min.

Materials and Finish

- Housing: Polyetherimide (PEI), glass-filled
 Polyethersulphone (PES) glass-filled
- Contacts: Beryllium Copper (BeCu)
- Plating: Gold over Nickel



Part Number (Details)

IC234 - 120 4 - 017 *

Series No.	120	4	017	*
No. of Contact Pins				
Number of Sides with Contacts				
Design Number				
Positioning Pin				
N = Without Positioning Pin				
P = With Positioning Pin				
K = Protection Key **				

** Protection Key: Prevents IC from releasing during transportation



Series IC200 / IC201 / IC216 / IC217 / IC218 / IC248 (Open Top)
Quad Flat Packages (QFP)

0.4 to 0.8mm Pitch


Specifications

- Insulation Resistance: 1,000MΩ min. at 500V DC or 1,000MΩ min. at 100V DC
- Dielectric Withstanding Voltage: 100/500/700V AC for 1 minute
- Contact Resistance: 30mΩ max. at 10mA/20mV max.
- Operating Temperature Range: -40°C to +170°C and -40°C to +150°C
- Contact Force: 20g to 80g per pin
- Mating Cycles: 10,000 insertions min.

The information above is typical for this Series for individual specifications please contact Yamaichi

Materials and Finish

- Housing: Polyetherimide (PEI), glass-filled
Polyphenylenesulfide (PPS), glass-filled
- Contacts: Beryllium Copper (BeCu)
- Plating: Gold over Nickel



Part Number (Details)

IC200 - 128 4 - 001 * - *

Series No.	IC200
No. of Contact Pins	128
Number of Sides with Contacts	4
Design Number	001
Positioning Pin:	
N = Without Positioning Pin	
P = With Positioning Pin	
Protection Key**	
K = With Protection Key	
Unmarked = Without Protection Key	

**Protection Key: Prevents IC from releasing during transportation

Series IC500 (Open Top)
Quad Flat Package (QFP) with 2-Point Contact Type


0.5 to 0.8mm Pitch

Specifications

- Insulation Resistance: 1,000MΩ min. at 100V DC pitch 0.5
1,000MΩ min. at 500V DC pitch 0.65, 0.8
- Dielectric Withstanding Voltage: 100V AC for 1 minute pitch 0.5
500V AC for 1 minute pitch 0.65
700V AC for 1 minute pitch 0.8
- Contact Resistance: 30mΩ max. at 10mA/20mV max.
- Operating Temperature Range: -40°C to +150°C
- Contact Force: 20g to 80g per pin
- Mating Cycles: 10,000 insertions min.

Materials and Finish

- Housing: Polyetherimide (PEI), glass-filled
Polyethersulphone (PES) glass-filled
- Contacts: Beryllium Copper (BeCu)
- Plating: Gold over Nickel




Part Number (Details)


IC500 - 064 4 - 008 *

Series No.	IC500
No. of Contact Pins	064
Number of Sides with Contacts	4
Design Number	008
Positioning Pin	
N = Without Positioning Pin	
P = With Positioning Pin	
K = Protection Key	


Contact Styles




Series IC51




Series IC357




Series IC234



Series IC (kelvin)







Series IC2**



Series IC500

Applicable Dimensions

Outline IC Body Dimensions



Outline Open Top Socket Dimensions

Outline Clamshell Socket Dimensions

□ 0.40mm Pitch

Part Number	Pitch	Pin Count	IC Dimensions				Socket Dimensions G X H	Package Type CL= Clamshell OT = Open Top
			Body A x B	Tip-to-Tip C x D	Parallel Clamp E	1/2 - IC height F		
IC51-0644-1972	0.4	64	7.0 x 7.0	9.0 x 9.0	8.25	-	35.0 x 32.0	CL
IC234-0804-055	0.4	80	10.0 x 10.0	12.0 x 12.0	-	0.7375	30.0 x 30.0	OT
IC234-1004-045	0.4	100	12.0 x 12.0	14.0 x 14.0	-	0.56	35.0 x 32.0	OT
IC51-1004-1919-*	0.4	100	12.0 x 12.0	14.0 x 14.0	13.30	-	36.0 x 42.5	CL
IC234-1204-022 *	0.4	120	14.0 x 14.0	16.0 x 16.0	-	0.762	34.0 x 34.0	OT
IC51-1204-1596	0.4	120	14.0 x 14.0	16.0 x 16.0	15.35	-	36.0 x 42.5	CL
IC51-1204-1812	0.4	120	14.0 x 14.0	16.0 x 16.0	-	-	36.0 x 42.5	CL
IC234-1284-043 *	0.4	128	14.0 x 14.0	16.0 x 16.0	-	0.56	34.0 x 34.0	OT
IC357-1284-056	0.4	128	14.0 x 14.0	16.0 x 16.0	-	0.65	34.0 x 34.0	OT
IC357-1284-076	0.4	128	14.0 x 14.0	16.0 x 16.0	-	0.45	34.0 x 34.0	OT
IC51-1284-1702	0.4	128	14.0 x 14.0	16.0 x 16.0	15.40	-	36.0 x 42.5	CL
IC51-1284-1702-2	0.4	128	14.0 x 14.0	16.0 x 16.0	15.40	-	36.0 x 42.5	CL
IC51-1284-1788	0.4	128	14.0 x 14.0	16.0 x 16.0	15.30	0.70	39.0 x 42.5	CL
IC234-1444-053 *	0.4	144	16.0 x 16.0	18.0 x 18.0	-	0.54	36.0 x 36.0	OT
QFP11T144-001	0.4	144	16.0 x 16.0	18.0 x 18.0	17.20	-	39.0 x 42.5	CL
IC234-1564-038P-2	0.4	156	14.0 x 14.0	16.0 x 16.0	-	0.76	38.0 x 44.0	OT
IC234-1764-059 *	0.4	176	20.0 x 20.0	22.0 x 22.0	-	0.67	40.0 x 40.0	OT
IC51-1764-1995	0.4	176	14.0 x 20.0	22.0 x 22.0	21.30	-	46.0 x 50.0	CL
IC51-1764-1995-6	0.4	176	20.0 x 20.0	22.0 x 22.0	21.20	-	46.0 x 50.0	CL
IC234-2164-050 *	0.4	216	20.0 x 20.0	26.0 x 26.0	-	0.67	44.0 x 44.0	OT
IC234-2164-066-*	0.4	216	20.0 x 20.0	26.0 x 26.0	-	0.67	44.0 x 44.0	OT
IC51-2164-1887	0.4	216	24.0 x 24.0	26.0 x 26.0	25.30	-	50.0 x 48.0	CL
IC51-2164-1887-10	0.4	216	24.0 x 24.0	26.0 x 26.0	25.30	-	50.0 x 48.0	CL
IC234-2564-020 *	0.4	256	24.0 x 24.0	30.0 x 30.0	-	0.67	48.0 x 48.0	OT
IC234-2564-078 *	0.4	256	24.0 x 24.0	30.0 x 30.0	-	0.67	48.0 x 48.0	OT
IC51-2564-1668	0.4	256	28.0 x 28.0	31.2 x 31.2	30.00	-	56.0 x 62.0	CL
IC51-2564-1668-10	0.4	256	28.0 x 28.0	30.0 x 30.0	29.40	-	56.0 x 62.0	CL
IC51-2564-1668-6	0.4	256	27.2 x 27.2	29.8 x 29.8	30.00	-	56.0 x 62.0	CL
IC51-2564-1668-8	0.4	256	28.0 x 28.0	30.6 x 30.6	30.00	-	56.0 x 62.0	CL

□ 0.50mm Pitch

IC51-0324-805	0.5	32	5.0 x 5.0	7.0 x 7.0	6.20	-	28.0 x 31.0	CL
IC234-0484-034 *	0.5	48	7.0 x 7.0	9.0 x 9.0	-	0.47	26.6 x 26.6	OT
IC234-0484-039 *	0.5	48	7.0 x 7.0	9.0 x 9.0	-	0.74	26.6 x 26.6	OT
IC357-0484-078 *	0.5	48	7.0 x 7.0	9.0 x 9.0	-	0.45	22.0 x 22.0	OT
IC51-0484-806	0.5	48	7.0 x 7.0	9.0 x 9.0	8.20	-	29.0 x 32.0	CL
IC51-0484-806-2	0.5	48	7.0 x 7.0	9.0 x 9.0	8.30	-	29.0 x 32.0	CL
IC201-0644-003 *	0.5	64	10.0 x 10.0	12.0 x 12.0	-	0.70	30.0 x 36.0	OT
IC201-0644-040 *	0.5	64	10.0 x 10.0	12.0 x 12.0	-	0.67	28.7 x 28.7	OT
IC234-0644-027 *	0.5	64	10.0 x 10.0	12.0 x 12.0	-	0.66	29.6 x 29.6	OT
IC234-0644-122 *	0.5	64	10.0 x 10.0	12.0 x 12.0	-	0.66	29.6 x 29.6	OT



0.50mm Pitch (cont'd)



Part Numbers	Pitch	Pin Count	A x B	C x D	E	F	G x H	Type
IC357-0644-068	0.5	64	10.0 x 10.0	12.0 x 12.0	-	0.6375	26.2 x 26.2	OT
IC500-0644-008	0.5	64	10.0 x 10.0	12.0 x 12.0	-	0.67	29.6 x 29.6	OT
IC51-0644-807	0.5	64	10.0 x 10.0	12.0 x 12.0	11.30	-	32.0 x 35.0	CL
IC51-807 AC-15764	0.5	64	10.0 x 10.0	13.2 x 13.2	12.00	-	32.0 x 35.0	CL
IC201-0804-014 *-*	0.5	80	12.0 x 12.0	14.0 x 14.0	-	0.62	29.0 x 29.0	OT
IC234-0804-011 *	0.5	80	12.0 x 12.0	14.0 x 14.0	-	0.45	29.0 x 29.0	OT
IC234-0804-026 *	0.5	80	12.0 x 12.0	14.0 x 14.0	-	0.67	31.6 x 31.6	OT
IC357-0804-074	0.5	80	12.0 x 12.0	14.0 x 14.0	-	0.6375	29.0 x 29.0	OT
IC357-0804-096	0.5	80	12.0 x 12.0	14.0 x 14.0	-	0.6375	29.0 x 29.0	OT
IC51-0804-808	0.5	80	12.0 x 12.0	14.0 x 14.0	13.30	-	34.0 x 37.0	CL
IC51-0804-808-2	0.5	80	12.0 x 12.0	14.0 x 14.0	13.20	-	34.0 x 37.0	CL
IC51-0804-808-4	0.5	80	12.0 x 12.0	14.0 x 14.0	13.40	-	34.0 x 37.0	CL
IC201-1004-008 *-*	0.5	100	14.0 x 14.0	16.0 x 16.0	-	0.60	32.2 x 31.0	OT
IC201-1004-043 *	0.5	100	14.0 x 14.0	16.0 x 16.0	-	0.45	31.0 x 31.0	OT
IC234-1004-023 *	0.5	100	14.0 x 14.0	16.0 x 16.0	-	0.67	33.6 x 33.6	OT
IC357-1004-002	0.5	100	14.0 x 14.0	16.0 x 16.0	-	0.50	31.9 x 31.9	OT
IC357-1004-014	0.5	100	14.0 x 14.0	16.0 x 16.0	-	0.55	31.9 x 31.9	OT
IC357-1004-053	0.5	100	14.0 x 14.0	16.0 x 16.0	-	0.55	31.9 x 31.9	OT
IC402-1004-002*	0.5	100	14.0 x 20.0	16.0 x 22.0	-	0.70	29.8 x 23.8	OT
IC500-1004-004	0.5	100	14.0 x 14.0	16.0 x 16.0	-	0.68	33.6 x 33.6	OT
IC51-1004-809	0.5	100	14.0 x 14.0	16.0 x 16.0	15.30	-	39.0 x 39.0	CL
IC51-1004-809-14	0.5	100	14.0 x 14.0	16.0 x 16.0	15.30	-	39.0 x 39.0	CL
IC51-1004-809-2	0.5	100	14.0 x 14.0	16.0 x 16.0	15.30	-	39.0 x 39.0	CL
IC51-1004-809-6	0.5	100	14.0 x 14.0	16.0 x 16.0	15.30	-	39.0 x 39.0	CL
IC51-809 KS-13929	0.5	100	14.0 x 14.0	17.2 x 17.2	15.90	-	39.0 x 39.0	CL
IC234-1204-058 *	0.5	120	16.0 x 16.0	18.0 x 18.0	--	0.67	35.6 x 35.6	OT
IC51-1204-1652	0.5	120	15.93 x 15.93	17.35 x 17.35	17.60	-	40.0 x 43.0	CL
IC201-026 KS-13784	0.5	128	20.0 x 20.0	22.0 x 22.0	-	0.69	37.0 x 36.7	OT
IC248-1284-007 *-*	0.5	128	14.0 x 20.0	16.0 x 22.0	-	0.67	37.4 x 43.4	OT
IC357-1284-033*	0.5	128	14.0 x 20.0	22.0 x 22.0	-	1.10	31.0 x 37.0	OT
IC500-1284-007	0.5	128	14.0 x 20.0	16.0 x 22.0	-	0.625	33.6 x 39.6	OT
IC51-1284-1433	0.5	128	14.0 x 20.0	16.0 x 22.0	15.2x21.2	-	46.0 x 43.0	CL
IC51-1284-1433-10	0.5	128	14.0 x 20.0	17.2 x 23.2	16.4x22.4	-	46.0 x 43.0	CL
IC51-1284-1433-19	0.5	128	14.0 x 20.0	17.9 x 23.9	16.4x22.4	-	46.0 x 43.0	CL
IC201-1444-026 *-2	0.5	144	20.0 x 20.0	22.0 x 22.0	-	0.69	37.0 x 37.0	OT
IC201-1444-034 *	0.5	144	20.0 x 20.0	22.0 x 22.0	-	0.65	37.0 x 37.0	OT
IC234-1444-007 *	0.5	144	20.0 x 20.0	22.0 x 22.0	-	-	-	OT
IC234-1444-016 *	0.5	144	20.0 x 20.0	22.0 x 22.0	-	0.8370	37.0 x 37.0	OT
IC402-1444-003*	0.5	144	20.0 x 20.0	22.0 x 22.0	21.30	0.80	30.0 x 30.0	OT
IC500-1444-002P-2	0.5	144	20.0 x 20.0	22.0 x 22.0	-	0.68	37.0 x 37.0	OT
IC51-1444-1354	0.5	144	20.0 x 20.0	22.0 x 22.0	21.30	1.00	43.0 x 47.0	CL
IC51-1444-1354-7	0.5	144	20.0 x 20.0	22.0 x 22.0	21.30	0.50	43.0 x 47.0	CL
IC51-1604-1350	0.5	160	24.0 x 24.0	26.0 x 26.0	25.30	-	46.0 x 50.0	CL
IC201-1764-033	0.5	176	24.0 x 24.0	26.0 x 26.0	-	0.67	40.0 x 46.0	OT
IC234-1764-002 *	0.5	176	24.0 x 24.0	26.0 x 26.0	-	1.00	46.0 x 46.0	OT
IC234-1764-005 *	0.5	176	24.0 x 24.0	26.0 x 26.0	-	1.00	46.0 x 46.0	OT
IC234-1764-121 *	0.5	176	24.0 x 24.0	26.0 x 26.0	-	1.00	40.0 x 46.0	OT
IC357-1764-061	0.5	176	24.0 x 24.0	26.0 x 24.0	-	0.615	41.0 x 41.0	OT
IC357-1764-081	0.5	176	24.0 x 24.0	26.0 x 24.0	-	0.6375	36.0 x 36.0	OT
IC357-1764-087	0.5	176	24.0 x 24.0	26.0 x 24.0	-	0.735	41.0 x 41.0	OT
IC357-1764-094	0.5	176	24.0 x 24.0	26.0 x 24.0	-	0.735	41.0 x 41.0	OT
IC51-1764-1505	0.5	176	24.0 x 24.0	26.0 x 26.0	25.30	0.90	46.0 x 50.0	CL
IC51-1764-1505-10	0.5	176	24.0 x 24.0	26.0 x 26.0	25.30	0.50	46.0 x 50.0	CL
IC51-1764-1505-5	0.5	176	24.0 x 24.0	26.0 x 26.0	25.30	0.50	46.0 x 50.0	CL
IC200-2084-009 *-*	0.5	208	28.0 x 28.0	31.2 x 31.2	-	1.40	51.2 x 52.2	OT
IC200-2084-010 *-*	0.5	208	28.0 x 28.0	30.6 x 30.6	-	1.40	50.6 x 50.6	OT
IC201-2084-001 *-*	0.5	208	28.0 x 28.0	30.0 x 30.0	-	1.50	45.0 x 45.0	OT
IC201-2084-029 *	0.5	208	28.0 x 28.0	30.6 x 30.6	-	1.67	45.6 x 45.6	OT
IC201-2084-096	0.5	208	28.0 x 28.0	30.0 x 30.0	-	0.55	45.0 x 45.0	OT
IC357-2084-019P-2	0.5	208	28.0 x 28.0	30.6 x 30.6	-	-	45.6 x 45.6	OT

Gullwing-Leads - QFP


cont'd next page

Applicable Dimensions


Outline IC Body Dimensions



Outline Open Top Socket Dimensions



Outline Clamshell Socket Dimensions



0.50mm Pitch (continued)

Part Number	Pitch	Pin Count	IC Dimensions				Socket Dimensions G X H	Package Type CL= Clamshell OT = Open Top
			Body A x B	Tip-to-Tip C x D	Parallel Clamp E	1/2 - IC height F		
IC51-2084-1052-*	0.5	208	28.0 x 28.0	-	-	-	52.0 x 58.0	CL
IC51-2084-1052-1	0.5	208	28.0 x 28.0	30.0 x 30.0	29.30	-	52.0 x 58.0	CL
IC51-2084-1052-13	0.5	208	28.0 x 28.0	30.6 x 30.6	29.70	-	52.0 x 58.0	CL
IC51-2084-1052-35	0.5	208	28.0 x 28.0	31.2 x 31.2	29.95	-	52.0 x 58.0	CL
IC51-2084-1052-36	0.5	208	28.0 x 28.0	30.0 x 30.0	29.30	-	52.0 x 58.0	CL
IC51-2084-1052-9	0.5	208	28.0 x 28.0	30.6 x 30.6	29.70	-	52.0 x 58.0	CL
IC51-2084-1052-55	0.5	208	28.0 x 28.0	30.6 x 30.6	29.95	-	52.0 x 58.0	CL
IC51-2084-1509	0.5	208	27.7 x 27.7	31.2 x 31.2	29.80	-	52.0 x 58.0	CL
IC51-2084-1566	0.5	208	28.0 x 28.0	31.2 x 31.2	30.30	-	52.0 x 58.0	CL
IC217-2404-007 *	0.5	240	32.0 x 32.0	34.6 x 34.6	-	1.75	56.1 x 56.1	OT
IC234-2404-030 *	0.5	240	32.0 x 32.0	34.6 x 34.6	-	2.06	51.6 x 51.6	OT
IC51-2404-1655-2	0.5	240	32.0 x 32.0	34.6 x 34.6	33.80	-	56.0 x 62.0	CL
IC201-2564-002 *-2	0.5	256	28.0 x 40.0	30.6 x 40.6	-	1.50	45.6 x 57.6	OT
IC51-2724-1727	0.5	272	35.9 x 35.9	37.4 x 37.4	37.60	-	58.0 x 72.0	CL
IC201-3044-004	0.5	304	40.0 x 40.0	42.6 x 42.6	-	1.50	57.6 x 57.6	OT
IC51-3044-1471-2	0.5	304	39.95 x 39.95	42.6 x 42.6	41.90	-	66.0 x 72.0	CL
IC51-3044-1471-5	0.5	304	39.64 x 39.64	42.6 x 42.6	41.90	-	66.0 x 72.0	CL

0.635mm Pitch

IC51-1004-827	0.635	100	22.86 x 22x86	22.35 x 22.35	-	-	47.5 x 34.0	OT
IC211-1324-002 *-*	0.635	132	24.10 x 24.10	28.0 x 28.0	-	-	47.4 x 47.4	OT
IC51-1324-828	0.635	132	27.94 x 27.94	27.43 x 27.43	-	-	53.5 x 40.0	OT
IC51-1964-1952	0.635	196	34.29 x 34.29	58.0 x 58.0	-	-	70.0 x 83.0	OT

0.65mm Pitch

IC51-0484-652	0.65	48	6.0 x 9.0	7.4 x 8.8	7.00	-	34.0 x 34.5	CL
QFP11T052-004 A102221*	0.65	52	10.0 x 10.0	13.2 x 13.2	13.30	-	34.0 x 37.0	CL
IC234-0564-084 *	0.65	56	10.0 x 10.0	12.8 x 12.8	-	1.50	29.3 x 29.3	OT
IC51-0564-680	0.65	56	10.0 x 10.0	13.2 x 13.2	11.80	-	34.0 x 35.5	CL
IC357-0644-077	0.65	64	12.0 x 12.0	14.0 x 14.0	-	0.6375	29.0 x 29.0	OT
IC51-0644-1586	0.65	64	12.0 x 12.0	15.3 x 15.3	13.90	-	36.0 x 39.0	CL
IC51-0644-1602	0.65	64	12.0 x 12.0	14.0 x 14.0	13.10	-	20.0 x 42.0	CL
IC51-0684-734	0.65	68	10.0 x 14.0	13.2 x 17.2	11.80 x 15.80	-	37.0 x 41.0	CL
IC201-0804-005 *-*	0.65	80	14.0 x 20.0	17.9 x 23.9	-	1.22	32.9 x 38.9	OT
IC201-0804-012 *-*	0.65	80	14.0 x 14.0	17.2 x 17.2	-	0.92	29.2 x 32.2	OT
IC234-0804-019 *	0.65	80	14.0 x 14.0	16.8 x 16.8	-	1.35	32.2 x 32.2	OT
IC357-0804-003	0.65	80	14.0 x 14.0	17.2 x 17.2	-	0.50	31.9 x 31.9	OT



0.65mm Pitch (cont'd)

Part Numbers	Pitch	Pin Count	A x B	C x D	E	F	G x H	Type
IC500-0804-005	0.65	80	14.0 x 14.0	16.0 x 16.0	-	1.07	32.0 x 32.2	OT
IC51-0804-711	0.65	80	14.0 x 14.0	17.2 x 17.2	15.80	-	37.0 x 41.0	CL
IC51-0804-795	0.65	80	14.0 x 14.0	16.0 x 16.0	15.30	-	37.0 x 41.0	CL
IC51-0804-956-2	0.65	80	14.0 x 14.0	17.2 x 17.2	16.40	-	34.0 x 42.5	CL
IC51-795 KS-13930	0.65	80	14.0 x 14.0	17.2 x 17.2	15.90	-	37.0 x 41.0	CL
QFP11T080-008	0.65	80	14.0 x 14.0	16.0 x 16.0	15.30	-	39.0 x 39.5	CL
IC201-1004-016 *-*	0.65	100	14.0 x 20.0	17.9 x 23.9	-	1.28	32.9 x 38.9	OT
IC201-1004-028 *	0.65	100	14.0 x 20.0	17.2 x 23.2	-	1.20	32.2 x 38.2	OT
IC201-1004-050 *	0.65	100	14.0 x 20.0	16.0 x 22.0	-	0.75	31.0 x 37.0	OT
IC234-0644-006 *	0.65	100	14.0 x 20.0	16.0 x 22.0	-	0.875	31.0 x 37.0	OT
IC234-1004-008 *	0.65	100	14.0 x 20.0	18.15 x 24.15	-	1.33	32.2 x 38.2	OT
IC234-1004-009 *	0.65	100	14.0 x 20.0	18.15 x 24.15	-	1.33	32.2 x 38.2	OT
IC234-1004-013 *	0.65	100	14.0 x 20.0	17.2 x 23.2	-	1.35	32.2 x 38.2	OT
IC234-1004-014 *	0.65	100	14.0 x 20.0	16.0 x 22.0	-	0.67	32.2 x 38.2	OT
IC234-1004-015 *	0.65	100	14.0 x 20.0	16.75 x 22.75	-	0.67	32.2 x 38.2	OT
IC234-1004-028 *	0.65	100	14.0 x 20.0	18.4 x 24.4	-	1.33	32.2 x 38.2	OT
IC234-1004-033 *	0.65	100	14.0 x 20.0	17.9 x 23.9	-	1.33	32.2 x 38.2	OT
IC51-1004-814-1	0.65	100	14.0 x 20.0	17.9 x 23.9	17.0 x 23.0	-	34.0 x 42.5	CL
IC51-1004-814-2	0.65	100	14.0 x 20.0	17.2 x 23.2	16.4 x 22.4	-	34.0 x 42.5	CL
IC51-1004-814-6	0.65	100	14.0 x 20.0	17.2 x 23.2	15.8 x 21.8	-	34.0 x 42.5	CL
IC51-1004-814-7	0.65	100	14.0 x 20.0	17.2 x 23.2	16.4 x 22.4	-	34.0 x 42.5	CL
IC51-814 KS-12033	0.65	100	14.0 x 20.0	17.2 x 23.2	16.4 x 22.4	-	34.0 x 42.5	CL
IC234-1124-093 *	0.65	112	24.0 x 24.0	23.2 x 23.2	-	1.30	38.2 x 38.2	OT
IC500-1124-001	0.65	112	20.0 x 20.0	22.0 x 22.0	-	0.68	38.2 x 38.2	OT
IC51-1124-1036-2	0.65	112	20.0 x 20.0	23.2 x 23.2	22.30	-	34.0 x 42.5	CL
IC51-1124-1036-YED	0.65	112	20.0 x 20.0	22.0 x 22.0	21.00	-	34.0 x 42.5	CL
IC201-006 AC-04462	0.65	144	28.0 x 28.0	31.2 x 31.2	-	1.65	46.2 x 46.2	OT
IC51-1444-1014	0.65	144	28.0 x 28.0	31.2 x 31.2	30.40	-	44.0 x 57.0	CL
IC51-1444-1014-3	0.65	144	28.0 x 28.0	31.2 x 31.2	30.40	-	44.0 x 57.0	CL
IC201-1604-006 *-*	0.65	160	28.0 x 28.0	31.2 x 31.2	-	1.65	46.2 x 46.2	OT
IC234-1604-018 *	0.65	160	27.9 x 27.9	32.0 x 32.0	-	1.48	47.6 x 47.6	OT
IC234-1604-032 *	0.65	160	28.0 x 28.0	30.6 x 30.6	-	1.66	47.6 x 47.6	OT
IC51-1604-845-1	0.65	160	28.0 x 28.0	31.6 x 31.6	30.60	-	44.0 x 57.0	CL
IC51-1604-845-2	0.65	160	28.0 x 28.0	31.6 x 31.6	30.60	-	44.0 x 57.0	CL
IC51-1604-845-4	0.65	160	28.0 x 28.0	31.2 x 31.2	30.20	-	44.0 x 57.0	CL
IC51-1604-845-8	0.65	160	28.0 x 28.0	31.2 x 31.2	30.20	-	44.0 x 57.0	CL
IC51-1604-926	0.65	160	29.0 x 29.0	30.2 x 31.4	30.40	-	44.0 x 57.0	CL



Gullwing-Leads - QFP

0.80mm Pitch

Part Number	Pitch	Pins	A x B	C x D	E	F	G x H	Type
IC234-0324-044 *	0.8	32	7.0 x 7.0	9.0 x 9.0	-	0.67	26.6 x 26.6	OT
IC51-0324-1498	0.8	32	7.0 x 7.0	9.0 x 9.0	8.4	-	30.0 x 35.5	CL
IC51-0324-354	0.8	32	7.4 x 7.4	9.8 x 9.8	8.4	-	30.0 x 37.5	CL
IC234-0444-037 *	0.8	44	10.0 x 10.0	12.0 x 12.0	-	0.45	29.6 x 29.6	OT
IC234-0444-054 *	0.8	44	9.95 x 9.95	12.8 x 12.8	-	1.35	29.6 x 29.5	OT
IC248-0444-001 *	0.8	44	10.0 x 10.0	13.2 x 13.2	-	0.80	27.0 x 27.0	OT
IC51-0444-1195-3	0.8	44	10.0 x 10.0	12.6 x 12.6	11.5	-	40.0 x 40.0	CL
IC51-0444-467	0.8	44	10.0 x 10.0	13.9 x 13.9	11.5	-	40.0 x 40.0	CL
QFP11T044-001	0.8	44	10.0 x 10.0	12.0 x 12.0	11.3	-	32.0 x 35.0	CL
IC51-0444-798	0.8	44	10.0 x 10.0	13.9 x 13.9	12.9	-	40.0 x 40.0	CL
IC51-0444-825	0.8	44	10.0 x 10.0	12.6 x 12.6	11.8	-	40.0 x 40.0	CL
IC51-467.AC-15687	0.8	44	10.0 x 10.0	12.0 x 12.0	11.6	-	37.5 x 37.5	CL
IC51-467.KS-11787	0.8	44	10.0 x 10.0	12.0 x 12.0	11.6	-	37.5 x 37.5	CL
IC51-467.KS-11247	0.8	44	10.0 x 10.0	13.2 x 13.2	12.1	-	40.0 x 40.0	CL
IC51-081-KS-14028	0.8	48	12.0 x 12.0	15.3 x 15.3	14.0	-	36.0 x 39.0	CL
IC51-0564-924	0.8	56	10.0 x 14.0	13.2 x 17.2	11.8 x 15.8	-	37.0 x 41.0	CL


cont'd next page

Outline IC Body Dimensions



Outline Open Top
 Socket Dimensions

Applicable Dimensions



Outline Clamshell
 Socket Dimensions

0.80mm Pitch (cont'd)

Part Number	Pitch	Pin Count	IC Dimensions				Socket Dimensions G X H	Package Type CL= Clamshell OT = Open Top
			Body A x B	Tip-to-Tip C x D	Parallel Clamp E	1/2 - IC height F		
IC51-0604-361	0.8	60	16.0 x 16.0	18.3 x 18.3	16.5	-	37.0 x 44.0	CL
IC51-0604-468	0.8	60	14.0 x 14.0	17.2 x 17.2	15.8	-	38.0 x 43.0	CL
IC234-0644-024 *	0.8	64	14.0 x 14.0	16.8 x 16.8	-	1.40	32.2 x 32.2	OT
IC51-0644-1240-2	0.8	64	14.0 x 14.0	16.5 x 16.5	15.0	-	42.5 x 34.0	CL
IC51-0644-692-*	0.8	64	14.0 x 14.0	-	-	-	22.0 x 26.0	CL
IC51-0644-824-1	0.8	64	14.0 x 14.0	17.2 x 17.2	15.8	-	30.0 x 42.5	CL
IC51-0644-824-2	0.8	64	14.0 x 14.0	17.9 x 17.9	16.7	-	30.0 x 4 2.5	CL
IC51-0644-824-3	0.8	64	14.0 x 14.0	16.2 x 16.2	15.4	-	30.0 x 4 2.5	CL
IC51-0644-824-5	0.8	64	14.0 x 14.0	16.0 x 16.0	15.2	-	30.0 x 42.5	CL
IC218-0724-001 *-*	0.8	72	13.2 x 18.0	18.8 x 23.6	-	0.90	31.8 x 36.6	OT
IC51-0724-698	0.8	72	16.0 x 20.0	18.2 x 23.1	16.6 x 21.5	-	36.0 x 44.5	CL
IC201-0804-032 *	0.8	80	14.0 x 20.0	17.2 x 23.2	-	-	38.2 x 38.2	OT
IC218-0804-002 *-*	0.8	80	14.0 x 20.0	19.2 x 25.2	-	0.95	31.0 x 38.2	OT
IC218-0804-007 *	0.8	80	14.0 x 14.0	16.0 x 16.0	-	-	32.2 x 29.2	OT
IC234-0804-001 *	0.8	80	14.0 x 20.0	19.1 x 25.1	-	1.60	32.2 x 32.2	OT
IC51-0804-819-1	0.8	80	14.0 x 20.0	17.9 x 23.9	16.9 x 22.9	-	34.0 x 42.5	CL
IC51-0804-819-2	0.8	80	14.0 x 20.0	17.6 x 23.6	16.3 x 22.3	-	34.0 x 42.5	CL
IC51-0804-819-6	0.8	80	14.0 x 20.0	16.8 x 22.8	15.6 x 21.6	-	34.0 x 42.5	CL
IC51-0804-819-8	0.8	80	14.0 x 20.0	17.2 x 23.8	16.9 x 22.9	-	24.0 x 42.5	CL
IC51-819.KS-12720	0.8	80	14.0 x 20.0	17.2 x 23.2	16.0 x 22.0	-	34.0 x 42.5	CL
IC234-1204-017 *	0.8	120	28.0 x 28.0	31.2 x 31.2	-	1.70	46.2 x 46.2	OT
IC234-1204-065 *	0.8	120	28.0 x 28.0	32.8 x 32.8	-	1.63	48.4 x 48.4	OT
IC51-1204-1497	0.8	120	28.0 x 28.0	29.7 x 29.7	30.5	-	60.0 x 58.0	CL
IC51-1204-1646	0.8	120	28.0 x 28.0	31.2 x 31.2	30.8	-	57.0 x 30.6	CL
IC200-1284-001 *-*	0.8	128	28.0 x 28.0	32.0 x 32.0	-	1.50	52.0 x 52.0	OT
IC51-1284-844-1	0.8	128	28.0 x 28.0	31.2 x 31.2	30.6	-	44.0 x 57.0	CL
IC234-017 AC-11315	0.8	128	28.0 x 28.0	31.2 x 31.2	-	1.70	34.0 x 34.0	OT
IC51-1284-617	0.8	128	29.0 x 29.0	31.2 x 31.2	30.60	-	44.0 x 57.0	CL
IC51-1284-976-*	0.8	128	28.0 x 28.0	31.2 x 31.2	30.6	-	44.0 x 57.0	CL

1.00mm Pitch

IC51-0444-615	1.0	44	14.0 x 14.0	17.2 x 17.2	15.80	-	34.0 x 42.5	CL
IC51-0444-621	1.0	44	14.0 x 14.0	17.9 x 17.9	17.00	-	34.0 x 42.5	CL
IC51-621 KS-8966	1.0	44	14.0 x 14.0	17.9 x 17.9	17.00	-	34.0 x 42.5	CL
IC51-0604-497-2	1.0	60	16.0 x 20.0	17.9 x 23.9	17.0 x 23.0	-	34.0 x 42.5	CL
IC201-0644-019 *-*	1.0	64	14.0 x 20.0	17.9 x 23.9	-	1.22	32.9 x 38.9	OT
IC51-0644-472	1.0	64	14.0 x 20.0	19.6 x 23.6	16.2 x 22.2	-	34.0 x 42.5	CL
IC51-0644-820-1	1.0	64	14.0 x 20.0	18.7 x 24.7	17.0 x 23.0	-	32.9 x 38.9	CL
IC51-0644-820-2	1.0	64	14.0 x 20.0	17.6 x 23.6	16.3 x 22.3	-	34.0 x 42.5	CL
IC51-0644-820-3	1.0	64	14.0 x 20.0	18.0 x 24.0	16.9 x 22.9	-	34.0 x 42.5	CL
IC51-0644-820-4	1.0	64	14.0 x 20.0	17.2 x 23.2	15.8 x 21.8	-	34.0 x 42.5	CL
IC51-820-2 KS-9376	1.0	64	14.0 x 20.0	17.2 x 23.2	17.0 x 23.0	-	34.0 x 42.5	CL