

PROXIMITY SENSOR

SPECIFICATION

- DC type with short circuit protection and polarity reversed protection.
- AC type with surge absorbing circuit may avoid surge damaged.
- High solid compact structure IP-67 suited to be applied in the poor circumstance.
- All models with operation LED, easy to adjust.
- With 2M length cable.

PICTURE	ITEM NO.	METHOD	SENSING DISTANCE	VOLTAGE	INDEX OF ITEM NUMBER
	LS-04N	NPN	4.0mm	10~30 VDC	EX: PS-04N B-V ① ②③④⑤ ① TYPE PS: SQUARE TYPE PL: LONG TYPE PP: PLATE TYPE SP: SMALL PLATE TYPE LS: RECTANGLE BS: MICRO TYPE ② SENSING DISTANCE 02: 2.0mm 04: 4.0mm 05: 5.0mm 08: 8.0mm 10: 10.0mm 15: 15.0mm ③ OUTPUT METHOD N: NPN P: PNP S: SCR ④ OUTPUT STATUS B: NCTYPE NON: NO TYPE ⑤ SENSING DIRECTION V: VERTICALTYPE NON: HORIZONTAL TYPE
	LS-04P	PNP			
	LS-04N-V	NPN			
	LS-04P-V	PNP			
	PS-04N	NPN	4.0mm	10~30 VDC	
	PS-04P	PNP			
	PS-04N-V	NPN			
	PS-04P-V	PNP			
	BS-02N	NPN	2.0mm	10~30 VDC	
	BS-02P	PNP	4.0mm		
	BS-04N	NPN			
	BS-04P	PNP			
	SP-05N	NPN	5.0mm	10~30 VDC	
	SP-05P	PNP	8.0mm		
	SP-08N	NPN			
	SP-08P	PNP			
	PP-05N	NPN	5.0mm	10~30 VDC	
	PP-05P	PNP	8.0mm		
	PP-08N	NPN			
	PP-08P	PNP			
	PS-05N	NPN	5.0mm	10~30 VDC	
	PS-05P	PNP	8.0mm		
	PS-08N	NPN			
	PS-08P	PNP			
	PL-05N	NPN	5.0mm	10~30 VDC	
	PL-05P	PNP	8.0mm		
	PL-08N	NPN			
	PL-08P	PNP			
	PS-05S	SCR	5.0mm	90~250 VAC	
	PS-08S		8.0mm		
	PS-10N	NPN	10.0mm	10~30 VDC	
	PS-10P	PNP	15.0mm		
	PS-15N	NPN			
	PS-15P	PNP			
	PS-10S	SCR	10.0mm	90~250 VAC	
	PS-15S		15.0mm		

