





勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

U-IRD



AC Current Sensor

Classification	General Purpose CTL Series									
Model	A: CTL-12-S36-10 B: CTL-12-S56-10 C: CTL-12-S56-20			A: CTL-12-S36-10L1 B: CTL-12-S56-10L		A: CTL-24-TE B: CTL-24-TE#B		A: CTL-36-S56-10B1 B: CTL-36-S56-20		
Shape										
Features/Application	12 Midium. size PCB/Panel mounting			12 Midium. size Output leadwire type		24 Mid. size Output leadwire type		36 High current		
Dimensions(mm)	40W x 40H x 15t			40W x 40H x 15t		56 x 13.5t		92W x 70H x 20t		
Hole Dia. (mm)	12			12		24		36		
Part No.	A	B	C	A	B	A	B	A	B	
Winding (Turn)	1000	1000	2000	1000	1000	1000	1000	1000	2000	
Max.Current (continuous)	240A	220A	260A	240A	220A	320A	400A	600A	600A	
No saturation Limit	400A	600A	800A	400A	600A	600A	1000A	2000A	2000A	
Current Range (Recomended)	0.1A ~ 280A	0.1A ~ 300A	0.1A ~ 320A	0.1A ~ 280A	0.1A ~ 300A	0.1A ~ 320A	0.1A ~ 500A	0.1A ~ 800A	0.1A ~ 800A	
Remarks	Option: Holder Connector set			Option: Holder		Option: Holder				