

3M™ Pak 100 Wiremount Plug, .100" x .100", 10 Contacts, Open End, 4610-6050



No ejector/latch system, Polarization for notch B, Mounting flange body style. Available option is 3448 Strain Relief ordered separately.

3M Id : 80-6101-7049-2

GTIN(UPC/EAN) : 0 00 54007 20493 0

Additional Information

- Shrouded to protect against physical and chemical pin damage
- Accepts flat cable or discrete wire
- Military (with 3518 polarizing key) and centerbump polarization available

For more information, refer to TS0086 (TS-0086).

Characteristics

Conductor Accommodation	26 & 28 AWG Solid or Stranded
Contact Material	Copper Alloy
Contact Termination Area Plating	None
Contact Underplating	100 µ" [2.54 µm] Nickel
Contact Wiping Area Plating	30 µ" [0.76 µm] Gold
Current Rating	1 Ampere
Insulation Color	Gray
Insulation Flammability Rating	UL 94V-0
Insulation Material	Glass Filled Polyester (PBT)
Insulation Resistance	>1 X 10 ⁹ Ohms @ 500 Vdc
Interface Grid	.100" x .100"
Interface Style	Rectangular Plug
Latch/Ejector Type	None
Markings	3M Logo, Part Identification Number, and Contact Position Numbers
Mounting Option	Mounting Flanges - Slotted
Non-Operating Temperature	-55 to 105 Degree Celsius
Number of Contact Rows	2
Number of Contacts	10
Polarization	Military & Center Bump
Separable	Yes
Termination Method	Insulation Displacement
Termination Style	Multiple Wires
Trademark Name	3M
Withstanding Voltage	1000 Vrms at Sea Level

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)