

Durable, efficient, low-priced

- optimal price-/performance relationship
- high welding capacity, speed, and quality
- field tested electronics, service friendly
- maintenance-free Servo drive motor
- stepless adjustment of pressure, speed, and temperature
- stable, lightweight and compact design
- material welding range: PE-LD, PE-HD, PE-C, PVC-P, PP, ECB, EVA, TPO



Simple, reliable operation combined with the maintenance-free servo motor and field tested electronics. The Comon is designed for the most demanding jobsites.

Technical Data

Voltage	V	230
Frequency	Hz	50/60
Power consumption	kW	2,1
Temperature	°C	20-460
Speed	m/min	0,8-5,0
Welding pressure	N	max. 1400
Size (l x w x h)	mm	460x 300x 330
Seam dimensions (other sizes available on request)	mm	15-15-15
Weight	kg	14
Markings	CE	

耐用耐操 高效率 低價位

- 最佳價格/性能本益比
- 高度焊接性能，速度和品質
- 完整環境測試電路，貼心的服務
- 容易保養的伺服馬達
- 無段壓力，速度和溫度調整
- 穩定，重量輕，設計紮實
- 材料焊接範圍：PE-LD, PE-HD, PE-C, PVC-P, PP, ECB, EVA, TPO



簡單，可靠的操作，結合容易保養的伺服馬達，和完整的環境測試電子電路。

亢龍(Comon)是專為高要求操作領域設計的焊接機具。



亢龍ComOn規格

適用電壓(V)	V ~	230
功率消耗	Kw	2.1
頻率	Hz	50/60
溫度	°C	20-460
速度	m/min	0.8-5.0
焊接壓力	N	max. 1400
尺寸	mm	460x300x330
縫測線	mm	15-15-15
重量	kg	14
CE		符合CE認證