

Small, powerful, flexible

- temperature stepless adjustable
- adapter tube with heat protection
- for push fit or screw on nozzle
- air supply with blower type HD 140 or SorOn
- connected with blower SorOn for external application



The small welding tool for external air supply with high performance. With heater tube for push fit or screw on nozzles.

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Technical data MarON

Voltage	V	230/120
Frequency	Hz	50/60
Power consumption	kW	1,55/1,6
Temperature	°C	20-650
Min. air flow (20°C)	l/min	40
Size (l x Ø)	mm	300x62, handle Ø 49
Weight	kg	1,2 with cord and hose
Markings		CE

Technical data MarON connected with SorON

Voltage	V	230/120
Frequency	Hz	50/60
Power consumption	kW	1,6
Temperature	°C	20-650
Air flow	l/min	max. ca. 300
Static pressure	Pa	ca. 3000
Weight	kg	2,5
Markings		CE

輕 功能強 適用各種場合

- 無段式溫度調整
- 防燙傷保護管
- 使用推擠式或鎖螺絲風嘴
- 搭配鼓風機型HD140式，亦可搭配SorOn(嫂龍)外出攜帶式組合使用



小型焊接工具外接高性能含加熱管的熱風機搭配使用，另亦可配鎖螺旋噴嘴。

馬龍MarOn規格

適用電壓(V)	V ~	120, 230
功率消耗	kW	1.55, 1.6
頻率	Hz	50/60
溫度	°C	20-650
20°C時之最小空氣流量	l/min	40
外進風口	mm	14.5
風口	mm	32
尺寸 L x Ø	mm	300 x 62, Ø 4.9mm握徑
重量	kg	1.2(含絕緣電線及風管)
CE		符合CE認證

馬龍加嫂龍SorOn規格

適用電壓(V)	V ~	120, 230
功率消耗	kW	1.6
頻率	Hz	50/60
溫度	°C	20-650
空氣流量	l/min	最大 ca. 300
靜壓	Pa	ca. 3000
重量	kg	2.5
CE		符合CE認證