

Fast, efficient quiet

- For welding of thermoplastic tarpaulins, billboards and banners
- High seam production because higher welding speed
- Weld thin material perfect
- Welding parameters can be saved
- Optimal heat transmission with new ceramic wedge
- Latest technology



With new wedge design higher welding speed.
Noise and smoke free.



Technical data

Voltage	VAC	230
Frequency	Hz	50/60
Power consumption	W	1050, 1420 or 1790 depend on wedge width
Temperature	°C (°F)	20-425 (850)
Speed	m/min (feet/min)	0,5-42 (0,5-140)
Size (l x w x h)	mm	540x330x280
Seam width	mm	30, 40 oder 50
Weight	kg (lb)	21,3 (47)
Protection class I		Ⓜ

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Available on request
in 120V

快速 效率 安靜

- 焊接熱塑性防水油布，廣告牌和橫幅。
- 高縫焊接，高速焊接
- 完美的薄料焊接
- 焊接參數可以保存
- 新型陶瓷切割刀帶來最佳的熱傳導
- 最新技術



以新陶瓷切割刀，高焊接速度。
無噪音及無煙產生。

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



喜龍SeOn規格

適用電壓(V)	V ~	120,230
功率消耗	W	1050, 1420 或 1790 依切割刀寬度而定
頻率	Hz	50/60
溫度	°C	20-425
速度	m/min	0.5-42
尺寸(長x寬x高)	mm	540x330x280
風嘴開口	mm	30, 40, 50
重量	kg	21.3
保護級數 I		◎

