

Compact, handy, innovative

- for welding of coated fabrics, foils and tarps
- digital display of speed, temperature and air flow
- automatic drive start system
- high welding speed
- wrinkle-free welding
- new design and new technology



Because more air flow high welding speed.
Available for 20, 30 or 40 mm width welding seam.

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



Technical data

Voltage	VAC	230
Frequency	Hz	50/60
Power consumption	W	2300/2900
Temperature	°C (°F)	20-630 (68-1166)
Speed	m/min (feet/min)	0,5-12 (1,6-39)
Air flow max. (20°C)	l/min	500
Air flow	%	50-100 variable
Noise level	dB	50
Size (l x w x h)	mm	410x260x200
Weight	kg	11,5 with 5 m cord
Protection class I		⊕



ATC

Available on request
in 120 V.

Version with integrated ATC (Automatic-Track-Control) for running always by itself at the edge of the overlap available on request.

塔普龍 TARPON

紮實
操作便利
創新機型



- 焊接含塗層的織物，熱熔性塑料和油布等
- 以數字顯示速度，溫度和空氣流通
- 自動驅動，啟動系統
- 高焊接速度
- 無皺焊接
- 新設計，新技術

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

追求更多風量，高速焊接
可用於20，30或40毫米寬焊接縫。



塔普龍TarpOn規格

適用電壓(V)	V ~	120,230
功率消耗	Kw	2300/2900
頻率	Hz	50/60
溫度	°C	20-630
速度	m/min	0.5-12
20°C時之最大空氣流量	l/min	500
空氣流量	%	50-100 可變
噪音水平	dB	50
尺寸	mm	410x260x200
重量	kg	11.5 (含絕緣電線)
保護級數 I		⊙

-ATC(自動軌道控制)可執行邊緣的軌道要求