

Hakko 808-KIT Desoldering Gun Kit



Features

- Thin, comfortable grip and low vibration
- Simple and inexpensive pump maintenance
- Tip-to-ground potential difference no greater than 2mV
- Tip-to-ground resistance no greater than 2 ohms
- Adjustable temperature control (380°C - 480°C / 715°F - 895°F)
- Includes lightweight carrying case and hot sock

Kit Includes

- Gun: Model 808-5
- Carrying Case: Model C1099
- Hot Sock: Model 605M
- Standard Nozzle A1005 (Nozzle dia. 1.0mm)

Description

The Hakko 808 is a handy, portable desoldering tool with a built-in vacuum pump. No separate station is required.

This unique Hakko design places the pump and motor above, not inside, the grip. Vibration is kept to a minimum, and the grip is thin and easy to

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

hold. Delicate tasks are performed with greater ease; the tool can be used for long periods without operator fatigue.

The new, miniature, high-performance diaphragm pump is housed in the chamber at the rear of the Hakko 808. Pump maintenance is quick and easy—simply remove the cover. If repairs are ever needed, replacement parts are inexpensive.

Specifications

Part No.	P-808-KIT
Power Consumption	100W with 80W heating element
Heating Element	Ceramic heater
Motor Output	6.5W
Temperature	380°C - 480°C (715°F - 895°F)
Temperature Stability (at idle)	±5°C/±9°F
Tip-to-Ground Resistance	Under 2 ohms
Tip-to-Ground Potential	Under 2mV
Vacuum Pump	Double-cylinder diaphragm pump
Vacuum Pressure	600 mmHg (24 in. Hg)
Suction Flow	10 l/min.
Dimensions (w/o Case)	170(H) x 235(W) mm (6.7(H) x 9.3(W) in.)
Weight (w/o case)	420 g (0.9 lb.)
Standard Nozzle	A1005 (Nozzle dia. 1.0mm)

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)