

FR100/FR110/FR120 吸錫線



Variety of Desoldering wire

- ◆ Regular type
- ◆ Unflux type
- ◆ No clean type



Features:

- ✦ Fast thermal transmission for superior performance at lower temperature.
- ✦ Pure copper braid.
- ✦ Available in regular, unflux and no clean type.
- ✦ Come in various width for different application.

Specifications:

Three different

- ✦ Regular type: Rosin flux treated copper braid
- ✦ Unflux type: Untreated copper braid
- ✦ No clean type: Low residue flux treated copper braid Using (ESD SAFE package)

✦ Removal for thru-hole...



✦ Removal for bridging...



勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

➤ Regular type -Flux-

Part No.	Name/Description
FR100-00	HAKKO WICK <REGULAR> 1.5MX0.6MM
FR100-01	HAKKO WICK <REGULAR> 1.5MX0.9MM
FR100-02	HAKKO WICK <REGULAR> 1.5MX1.4MM
FR100-03	HAKKO WICK <REGULAR> 1.5MX1.9MM
FR100-04	HAKKO WICK <REGULAR> 1.5MX2.5MM
FR100-05	HAKKO WICK <REGULAR> 1.5MX3.3MM

➤ Unflux type -Unflux-

Part No.	Name/Description
FR110-00	HAKKO WICK <UNFLUXED> 1.5MX0.6MM
FR110-02	HAKKO WICK <UNFLUXED> 1.5MX1.4MM
FR110-03	HAKKO WICK <UNFLUXED> 1.5MX1.9MM
FR110-04	HAKKO WICK <UNFLUXED> 1.5MX2.5MM
FR110-05	HAKKO WICK <UNFLUXED> 1.5MX3.3MM

➤ No clean type -Low residue flux- ESD SAFE package

Part No.	Name/Description
FR120-00	HAKKO WICK <NO CLEAN> 1.5MX0.6MM
FR120-01	HAKKO WICK <NO CLEAN> 1.5MX0.9MM
FR120-02	HAKKO WICK <NO CLEAN> 1.5MX1.4MM
FR120-03	HAKKO WICK <NO CLEAN> 1.5MX1.9MM
FR120-04	HAKKO WICK <NO CLEAN> 1.5MX2.5MM
FR120-05	HAKKO WICK <NO CLEAN> 1.5MX3.3MM

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)