

MCBs RX³ 4500

thermal magnetic MCBs from 3 A to 63 A
B and C curves



4 021 55

4 021 90

4 022 09



Dimensions **see e-catalogue**

Conform to IEC 60898-1

Do not accept auxiliaries, and add-on modules

Breaking capacity:

[4500] - IEC 60898-1 - 230/400 V~

4.5 kA - IEC 60947-2 - 230/400 V~

[6000] - IEC 60898-1 - 127/220 V~

6 kA - IEC 60947-2 - 127/220 V~

Pack	Cat.Nos		Nominal rating In (A)	Number of modules
	B curve	C curve		
10	4 021 02	4 021 51	3	1
10	4 021 03	4 021 52	6	1
10	4 021 04	4 021 53	10	1
10		4 021 54	13	1
10	4 021 05	4 021 55	16	1
10	4 021 06	4 021 56	20	1
10	4 021 07	4 021 57	25	1
10	4 021 08	4 021 58	32	1
10	4 021 09	4 021 59	40	1
10	4 021 10	4 021 60	50	1
10	4 021 11	4 021 61	63	1

Single pole 230/400 V~

Pack	Cat.Nos		Nominal rating In (A)	Number of modules
	B curve	C curve		
5	4 021 21	4 021 82	3	2
5	4 021 22	4 021 83	6	2
5	4 021 23	4 021 84	10	2
5		4 021 85	13	2
5	4 021 24	4 021 86	16	2
5	4 021 25	4 021 87	20	2
5	4 021 26	4 021 88	25	2
5	4 021 27	4 021 89	32	2
5	4 021 28	4 021 90	40	2
5	4 021 29	4 021 91	50	2
5	4 021 30	4 021 92	63	2

2-pole 230/400 V~

Pack	Cat.Nos		Nominal rating In (A)	Number of modules
	B curve	C curve		
1	4 021 31	4 021 93	3	3
1	4 021 32	4 021 94	6	3
1	4 021 33	4 021 95	10	3
1		4 021 96	13	3
1	4 021 34	4 021 97	16	3
1	4 021 35	4 021 98	20	3
1	4 021 36	4 021 99	25	3
1	4 021 37	4 022 00	32	3
1	4 021 38	4 022 01	40	3
1	4 021 39	4 022 02	50	3
1	4 021 40	4 022 03	63	3

3-pole 400 V~

Pack	Cat.Nos		Nominal rating In (A)	Number of modules
	B curve	C curve		
1	4 021 41	4 022 04	3	4
1	4 021 42	4 022 05	6	4
1	4 021 43	4 022 06	10	4
1		4 022 07	13	4
1	4 021 44	4 022 08	16	4
1	4 021 45	4 022 09	20	4
1	4 021 46	4 022 10	25	4
1	4 021 47	4 022 11	32	4
1	4 021 48	4 022 12	40	4
1	4 021 49	4 022 13	50	4
1	4 021 50	4 022 14	63	4

4-pole 400 V~

NEW

MCBs RX³ 6000

thermal magnetic MCBs from 3 A to 63 A
B and C curves



4 023 14

4 023 38



Dimensions **see e-catalogue**

Conform to IEC 60898-1

Do not accept auxiliaries, and add-on modules

Breaking capacity:

[6000] - IEC 60898-1 - 230/400 V~

6 kA - IEC 60947-2 - 230/400 V~

[10000] - IEC 60898-1 - 127/220 V~

10 kA - IEC 60947-2 - 127/220 V~

Pack	Cat.Nos		Nominal rating In (A)	Number of modules
	B curve	C curve		
10	4 022 69	4 023 09	3	1
10	4 022 70	4 023 10	6	1
10	4 022 71	4 023 11	10	1
10		4 023 12	13	1
10	4 022 72	4 023 13	16	1
10	4 022 73	4 023 14	20	1
10	4 022 74	4 023 15	25	1
10	4 022 75	4 023 16	32	1
10	4 022 76	4 023 17	40	1
10	4 022 77	4 023 18	50	1
10	4 022 78	4 023 19	63	1

Single pole 230/400 V~

Pack	Cat.Nos		Nominal rating In (A)	Number of modules
	B curve	C curve		
5	4 022 79	4 023 20	3	2
5	4 022 80	4 023 21	6	2
5	4 022 81	4 023 22	10	2
5		4 023 23	13	2
5	4 022 82	4 023 24	16	2
5	4 022 83	4 023 25	20	2
5	4 022 84	4 023 26	25	2
5	4 022 85	4 023 27	32	2
5	4 022 86	4 023 28	40	2
5	4 022 87	4 023 29	50	2
5	4 022 88	4 023 30	63	2

2-pole 230/400 V~

Pack	Cat.Nos		Nominal rating In (A)	Number of modules
	B curve	C curve		
1	4 022 89	4 023 31	3	3
1	4 022 90	4 023 32	6	3
1	4 022 91	4 023 33	10	3
1		4 023 34	13	3
1	4 022 92	4 023 35	16	3
1	4 022 93	4 023 36	20	3
1	4 022 94	4 023 37	25	3
1	4 022 95	4 023 38	32	3
1	4 022 96	4 023 39	40	3
1	4 022 97	4 023 40	50	3
1	4 022 98	4 023 41	63	3

3-pole 400 V~

Pack	Cat.Nos		Nominal rating In (A)	Number of modules
	B curve	C curve		
1	4 022 99	4 023 42	3	4
1	4 023 00	4 023 43	6	4
1	4 023 01	4 023 44	10	4
1		4 023 45	13	4
1	4 023 02	4 023 46	16	4
1	4 023 03	4 023 47	20	4
1	4 023 04	4 023 48	25	4
1	4 023 05	4 023 49	32	4
1	4 023 06	4 023 50	40	4
1	4 023 07	4 023 51	50	4
1	4 023 08	4 023 52	63	4

4-pole 400 V~

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)