



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Model No.	Switching Position		
	ON	NONE	ON
MDP-1	ON	NONE	ON
MDP-2	ON	NONE	(ON)
MDP-3	ON	OFF	ON
MDP-4	(ON)	OFF	(ON)
MDP-5	ON	OFF	(ON)
TERM. COMM.	2-3,5-6	OPEN	2-1,5-4

- SPECIFICATIONS:**
- MOVABLE CONTACT: Copper alloy, silver plated
 - TERMINALS: Copper alloy, silver plated
 - RATING: 3Amps with resistive load @ 125VAC or 28VDC
1.5Amps with resistive load @ 250VAC
 - CONTACT RESISTANCE: 20m-ohms max. initial
 - INSULATION RESISTANCE: 1,000M-ohms min.
 - DIELECTRIC STRENGTH: 1,500V RMS @ sea level
 - ELECTRICAL LIFE: 30,000 make and break cycles at full load
 - OPERATING TEMPERATURE: -30°C to +85°C

ITEM NO.	400-MDP-1-R102M6QE
料號	4MD1R102M6QE

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF TAIWAY ELECTRONICS COMPONENTS LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF TAIWAY ELECTRONICS COMPONENTS LTD.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS ANGULAR TOLERANCE: ±1.0°

DIMENSIONS	TOLERANCE
0.00 TO 10.00mm	±0.20mm
10.01 TO 20.00mm	±0.25mm
20.01 TO 30.00mm	±0.30mm
30.01 -	±0.40mm

USED 用途	400	
FINISH 處理		
SCALE 比例	2 / 1	UNIT 單位 in(mm)
TITLE 名稱	ROCKER SWITCH	
DWG NO. 圖號	400-MDP-1-R102M6QE	SIZE 圖紙 A4
FILE NAME 檔案名稱	4MD16QE.dwg	SHEET 張 1 / 1
		REV. 更改 6