

[产品名称]: 吸盘天线	[增益]: 3.5dBi
[接口类型]: SMA内螺纹内针	[驻波]: ≤ 1.5
[频段范围]: 433MHz	[阻抗]: 50 Ω
[天线尺寸]: 18.5cm (天线) * 100cm (馈线)	[特点]: 吸盘天线



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



1 SMA接口

接口为SMA内螺纹内针



2 含磁底座

底座为磁性材料，
可方便放置在铁质表面，
接口表层镀金。



3 优质线材

密集网状屏蔽层，
减少外界干扰，
提升传输距离和速率



4 衔接紧密

天线与底座之间衔接紧密，
信号更稳定。



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

 网状屏蔽层 **密集**

屏蔽层对比

屏蔽层稀疏 



 镀锡屏蔽层, **不易氧化**



易氧化 

安捷伦E5071C 网络分析仪测试图

