

記憶式電導/TDS/鹽分計 CD-4307SD



特色

- 即時將儀表輸出數據紀錄儲存於 SD 記憶卡，資料可下載到 Excel，座圖表分析 (記憶卡選購)
- **電導範圍** : 0 ~ 199.9 μS ' 0.2 ~ 1.999 mS ' 2 ~ 19.99 mS ' 20 ~ 199.9 mS $\pm 2\%$ (滿刻度)
- **TDS 範圍** : 0 ~ 132.0 ppm ' 132 ~ 1320 ppm ' 1320 ~ 13200 ppm ' 13200 ~ 132000 ppm $\pm 2\%$ (滿刻度)
- **鹽份範圍** : 0 ~ 12.00% $\pm 5\%$ (滿刻度)
- **溫度** : 0 ~ 60.0°C $\pm 0.8^\circ\text{C}$
- 具有自動溫度補償功能
- 可記錄最大值,最小值及讀值鎖定功能..
- RS-232 / USB 輸出介面.(軟體選購)
- **Size** : 177 x 68 x 45mm.

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

CONDUCTIVITY METER TDS, Salt + SD Card data recorder

Description :

SD Card real time data recorder

CONDUCTIVITY METER TDS, Salt

Model : CD-4307SD

- * Real time data recorder, save the data into the SD memory card and can be download to the Excel, extra software is no need.
- * 3 function : Conductivity, TDS, Salt measurement.
- * Conductivity : 200 uS/2 mS/20 mS/ 200 mS.
- * Salt : 0 to 12 % salt (% weight).
- * Automatic temp. compensation.
- * It can select Temp. Coefficient of measurement solution.
- * Separate probe, easy for operation.
- * Carbon rod electrode for long life.
- * Record (Max., Min.), Data hold, zero adjust.
- * RS232/USB computer interface.
- * Patented.
- * Patent: Taiwan, China, Japan, Germany, USA pending.

勝特力材料 886-3-5753170

勝特力电子(上海) 86-21-34970699

勝特力电子(深圳) 86-755-83298787

[Http://www.100y.com.tw](http://www.100y.com.tw)