

Airflow Transducer Model 6332 / 6332D



Features:

- 10 interchangeable probes are available for various applications
- Smart probe technology: easy probe replacement without recalibration of the main unit
- The Model 6332D features digital display
- Selectable output options: 0 to 5 V or 4 to 20 mA
- The Model 6332/6332D Includes 9.8 ft (3m) probe cable

Main Unit Specifications

Model	6332	6332D
Display	—	○
Air Velocity Ranges	20 to 9840 fpm (0.10 to 50.0 m/s) *See Probe Specifications	
Accuracy	+/- 3% of reading	
Analog Output	DC 4 to 20mA or DC 0 to 5V *Selectable	
Power Consumption	Approx. 2.0 W	
Power Supply	DC 12 to 24V or AC 80 to 240V	
Dimensions	W3.1" x H5.0" x D1.2"	
Weight	0.7 lbs (320 g)	

NIST Certificate

AFCAL-V: NIST Certificate with air velocity data per probe

Compatible Probes



0962-00
Uni-Directional Probe
20 to 9840 fpm (0.10 to 50.0 m/s)



0963-00
Uni-Directional Probe
20 to 9840 fpm (0.10 to 50.0 m/s)



0964-01/02
Omni-Directional
20 to 9840 fpm (0.10 to 50.0 m/s)



0965-00/01
Omni-Directional
20 to 9840 fpm (0.10 to 50.0 m/s)



0965-03/04
Omni-Directional
20 to 4920 fpm (0.1 to 25.0 m/s)



0965-07/08
Omni-Directional
20 to 4920 fpm (0.1 to 25.0 m/s)

* See page 13 for more detail

Accessories

- 1504-02:** Probe Cable (2 m)
- 1504-03:** Probe Cable (5 m)
- 1504-04:** Probe Cable (10 m)
- 1504-05:** Probe Cable (20 m)
- 1504-06:** Probe Cable (30 m)

勝特力材料 886-3-5753170
 胜特力电子(上海) 86-21-34970699
 胜特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Airflow Transducer Model 6312

Features:

- Compact body is designed to fit into small spaces or machinery
- Two air velocity probes available
- The Model 6312 Includes 9.8 ft (3m) probe cable

Main Unit Specifications

Model	6312
Air Velocity Ranges	20 to 394 fpm (0.1 to 2.0 m/s) *See Probe Specifications
Accuracy	+/- 0.15 m/s
Analog Output	DC 4 to 20mA
Power Consumption	Approx. 3.1 W
Power Supply	DC 24V
Dimensions	W3.1" x H5.0" x D1.2"
Weight	0.7 lbs (320 g)

Probe Specifications

Model	0941	0942
Air Velocity Ranges	20 to 394 fpm (0.1 to 2.0 m/s)	
Dimensions	W0.4" x H3.0" x D0.2"	∅0.4" x 4.3"



NIST Certificate

AFCAL-V: NIST Certificate with air velocity data per probe

Accessories

- 3673:** Steel Cover