

all in one

CONDUCTIVITY METER

Model : PCD-431

ISO-9001, CE, IEC1010



FEATURES

- * 2 ranges : 2,000 uS, 20 mS.
- * Temperature measurement, °C/°F
- * Automatic temperature compensation.
- * Probe with the meter, all in one.
- * Carbon rode electrode, high reliability.
- * Data hold, Record (max., min.).
- * IP-67 Water resistance, heavy duty.
- * External calibration buttons.
- * DC 1.5V battery (UM-4, AAA) x 4.

產品特點：

- 電導 : 2 ~ 2000uS, 2 ~ 20.00Ms
- TDS: 132 ~ 1320 ppm, 1320 ~ 13200 ppm
- 溫度範圍 : 0 ~ 60 C
- 具有自動溫度補償功能
- 外殼防水等級 IP67
- 可記錄最大值, 最小值及讀值鎖定
- Size: 190 x 40 x 40mm



勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Pen type, all in one, IP-67 CONDUCTIVITY METER

Model : PCD-431

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
 Http://www.100y.com.tw

FEATURES

* All in one pen type conductivity meter provides fast, accurate readings with digital reading.
* Conductivity measurement (uS, mS) or TDS (Total Dissolved Solids, ppm) can be selected.
* Conductivity : Two ranges, 2,000 uS, 20.00 mS.
* TDS : Two ranges, 20,000 ppm, 2,000 ppm.
* Carbon rod electrode for long life.
* Build in temperature sensor, ATC (auto temperature compensation).
* Temperature measurement, °C, °F.
* IP67, water proof and protection.
* LCD with two displays show conductivity and Temp. value at same time.
* Data hold function for freezing the desired value.
* Auto power off to save the battery life.
* Records max. and min. value with recall.
* Microcomputer circuit, intelligent function, high accuracy.
* Compact size, light weight.
* Power supply by DC 1.5 V battery (UM4/AAA) x 4 PCs,
* Available for wide applications, such as aquarium, beverage, fish hatcheries, food processing, photography, laboratory, quality control, school & colleges, swimming pools, water conditions.

Operating Temperature	0 to 50 °C (32 to 140 °F).
Operating Humidity	Less than 80% RH.
Power Supply	DC 1.5V battery (UM-4/AAA) x 4 PCs.
Power Consumption	Approx. 5.7 mA.
Dimension	190 x 40 x 40 mm (7.5 x 1.6 x 1.6 inch).
Weight	171 g/0.38 LB.
Standard Accessories	Instruction Manual..... 1 PC
Power off	Auto shut off saves battery life or manual off by push button. * Power will off automatically after 10 min., if no button be pressed.
Standard Accessories	Instruction Manual..... 1 PC
Optional Accessories	* Soft carrying case with sash (210 x 80 x 50 mm), Model : CA-52A * Hard carrying case (280 x 195 x 65 mm), Model : CA-06 * 1.413 mS Conductivity Standard Solution, Model : CD-14A

SPECIFICATIONS

Display	LCD, size : 20 mm x 28 mm.
Measurement	* Conductivity (uS, mS) * TDS (Total Dissolved Solids, ppm) * Temperature (°C, °F)
Ranges * two ranges * auto range	Conductivity: 2000 uS, 20.00 mS TDS : 2,000 ppm 20,000 ppm
Accuracy * 23 ± 5 °C	± (2% FS + 1 d) * FS : full scale
Temperature Compensation	Automatic from 0 to 60 °C (32 - 140 °F), with temperature compensation factor variable between 0 to 5.0% per C.
Conductivity Probe Structure	Carbon rod electrode for long life.
Data Hold	Freeze the display reading.
Memory Recall	Maximum & Minimum value.
Sampling Time	Approx. 0.8 second.
Circuit	Custom one-chip of microprocessor LSI circuit.
Power off	Auto shut off saves battery life or manual off by push button. * Power will off automatically after 10 min., if no button be pressed.

ELECTRICAL SPECIFICATIONS (23±5 °C)

A. Conductivity

Range	Measurement	Resolution	Accuracy
2000 uS	2 to 2000 uS	1 uS	± (3% F.S. + 1d)
20 mS	2 to 20.00 mS	0.01 mS	* F.S. - Full scale

* Auto range.
 * Temperature Compensation :
 Automatic from 0 to 60 °C (32 - 140 °F), with temperature compensation factor variable between 0 to 5.0% per C.
 * mS - milli Simens * uS - micro Simens * 23±5 °C

B. TDS (Total Dissolved Solids)

Range	Measurement	Resolution	Accuracy
2,000 ppm	132 to 1,320 ppm	1 ppm	± (3% F.S. + 1d)
20,000 ppm	1,320 to 13,200 ppm	10 ppm	* F.S. - Full scale

* Auto range.
 * Temperature Compensation :
 Automatic from 0 to 60 °C (32 - 140 °F), with temperature compensation factor variable between 0 to 5.0% per °C.
 * ppm - parts per million * 23±5 °C

C. Temperature

Function	Measuring Range	Resolution	Accuracy
°C	0 °C to 60 °C	0.1 °C	0.8 °C
°F	32 °F to 140 °F	0.1 °F	1.5 °F

@ 23±5 °C