



Microprocessor Water Quality Monitor

EC-410 / EC-430

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Specifications:

Model		EC-410	EC-430
Measuring Modes		Conductivity, Resistivity and Temperature	
Measuring Range	Conductivity	0.00 μ S/cm~200.0 mS/cm in 5 ranges	
	Resistivity	0.00~20.00M Ω ·cm	
	Temperature	-10~110.0°C	
Resolution	Conductivity	0.01 μ S/cm	
	Resistivity	0.01M Ω ·cm	
	Temperature	0.1°C	
Accuracy	Conductivity	$\pm 1\%$ (± 1 Digit)	
	Resistivity	$\pm 1\%$ (± 1 Digit)	
	Temperature	$\pm 0.5^\circ\text{C}$	
Cell constant		0.01, 0.05, 0.1, 0.5, 10.00cm ⁻¹ fixed, freely selectable 0.008~19.99cm ⁻¹	
Temperature Compensation		Automatic with PT-1000 or NTC 30K or no compensation	
Temperature coefficient	Conductivity	Non-Linear Compensation Linear compensation from 0.00~40.00%	
	Resistivity	Non-Linear Compensation	
Display		LCD display	
Analog output		Isolated DC 4~20 mA corresponding to measurement, max load 500 Ω	
Setting	Contact	-	240 VAC, 0.5A max.
	Activate	-	Hi/Lo one relay output
Ambient temperature		0 ~ 50°C	
Storage temperature		-20 ~ 70°C	
Power Supply		100V~240VAC $\pm 10\%$, 50/60Hz	
Installation		Panel mounting	
Dimensions		48 mm x 96mm x 110 mm (H x W x D), 1/8 DIN	
Cut off dimensions		44 mm x 92 mm (H x W)	
Weight		0.25 kg	

*The specification and appearance of the instrument are subject to change without notice.

Optional Accessories:

Cell:

- 2-Electrode cell
- 4-Electrode cell

Accessories:

- Specific Cable 5M, 10M, 20M, 30M
other length on request.
- 3/4" NPT bypass chamber
- 3/4" T-Connector



2-Electrode



4-Electrode



Cable