

# ST-302 ... Temperature & RH Data Logger

- Sensor:Internal
- Type:Temp/Humidity
- Channel(s) : 2
- Range :-40°C to 85°C
- Accuracy: +/- 0.7°C @ 25°C
- Range : 0-100% RH
- Accuracy : 2.5% RH (10-90% RH)
- Resolution : 12bits
- Datalogger Storage: 60,000(30.000\*2)
- Memory:128K
- Interface:USB
- Dimensions :61\*47\*15

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-54151736  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

Model	ST-301	ST-302	ST-303
Type	Temperature	Temp/Humidity	Voltage/ Current/Thermisto
Channels	1	2	4
Range	-20°C to 70°C	-40°C to 85°C	0~10V
Accuracy	+/- 0.7°C at 21°C +/- 1.27°F at 70°F	+/- 0.7°C@25°C	+/-10mV +/- 1%
Range	NA	0-100% RH	4~20mA
Accuracy	NA	2.5% RH(10-90%Rh)	+/- 0.1mA +/--1%
Range	NA	NA	Thermistor
Accuracy	NA	NA	+/- 0.7°C at 21°C +/- 1.27°F at 70°F
Resolution	12 Bits	12 Bits	12 Bits
Memory	64K	128K	256K
Interface	Serial/RS232	Serial/RS232	Serial/RS232
Datalogger Storage	30,000	Total:60,000 (30,000*2)	Total:60,000 (15,000*5)
Sensor	Internal	Internal	External