

## TM-184

### Precision Temperature/ Humidity Meter

#### 用途

可運用於電子工程,冷凍空調,建築業,生物栽培。

#### FEATURES:

- Relative humidity range from 1% to 99% RH.
- Temperature range from -20°C to 60°C (-4°F~140°F)
- Quick-response capacitance sensor with twist-open protective cover.
- Max/Min and data hold.
- Auto power off with disable function.
- Low battery indication.
- Datalogging capacity: 30,000 records.

#### 功能

- °C 或 °F 單位切換。
- 自動關機。
- 露點溫度測量。
- 濕球溫度測量。

#### 規格



勝特力材料 886-3-5753170  
胜特力电子(上海) 86-21-54151736  
胜特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

SPECIFICATION:	TM-184
Temperature range	-20°C~-60°C (-4°F~140°F)
Temperature Accuracy	+/- 0.5°C (+/-1.8°F) (0.0°C~40.0°C/32.0°F~104°F); other +/-2.0°C/3.6°F
Temperature Resolution	0.1°C/0.1°F
Temperature update rate	1 time/ second
Temperature sensor type	Diode
Relative Humidity range	1.0 %~99.0 %RH
Relative Humidity Accuracy	+/-1%RH(@25.0°C 15%RH~90%RH) +/-2.5%RH (@<15%RH, >90%RH)
Relative Humidity Resolution	0.1% RH
Dew point range	-30°C to 100°C (-22 to 212°F)
Wet Bulb range	0°C to 80°C (32 to 176°F)
Relative Humidity response time	below 10 seconds
LCD display	42mm*32mm(1.655*1.26 inch)
Power supply	DC 9V
Size	130mm*54mm*38mm (L*W*H)
Weight	250g