

MASTECH_M266F 數位交流鉗形鉤錶

MASTECH_Digital AC Clamp Meter



產品特點

- 顯示2000計數
- 勾表開口 Φ 50mm/2.0"
- 導通性蜂鳴器 $<100\Omega$
- 數據鎖定
- 低電量顯示
- 二極體開路電壓2.7V

Features

- Display 2000 counts
- Jaw Opening Φ 50mm/2.0"
- Diode open voltage 2.7V
- Continuity Buzzer $<100\Omega$
- Data Hold
- Low Battery Display

規格	量程	解析度	正確度
直流電壓	2V/20V/200V	1mV/10mV/0.1V	±(0.5%+3)
	1000V	1V	±(0.8%+3)
直流電壓	200V	0.1V	±(1.0%+5)
	750V	1V	±(1.2%+5)
交流電流	200A	0.1A	±(2.5%+5)
	1000A	1A	±(3.0%+10)
電阻	200Ω	0.1Ω	±(1.0%+5)
	2kΩ	1Ω	±(1.0%+8)
	20kΩ	10Ω	±(1.0%+8)
	200kΩ	0.1kΩ	±(1.0%+8)
	2MΩ	1kΩ	±(1.0%+8)
頻率	2kHz	1Hz	±(2.0%+5)
絕緣電阻測試	20MΩ	10kΩ	±(2.0%+2)
	2000MΩ (Note <500M>	1MΩ	±(4.0%+2)
	2000MΩ (Note>500MΩ)	1MΩ	±(5.0%+2)

Specifications	Range	Resolution	Accuracy
DC Voltage	2V/20V/200V	1mV/10mV/0.1V	±(0.5%+3)
	1000V	1V	±(0.8%+3)
AC Voltage	200V	0.1V	±(1.0%+5)
	750V	1V	±(1.2%+5)
AC Current	200A	0.1A	±(2.5%+5)
	1000A	1A	±(3.0%+10)
Resistance	200Ω	0.1Ω	±(1.0%+5)
	2kΩ	1Ω	±(1.0%+8)
	20kΩ	10Ω	±(1.0%+8)
	200kΩ	0.1kΩ	±(1.0%+8)
	2MΩ	1kΩ	±(1.0%+8)
Frequency	2kHz	1Hz	±(2.0%+5)
Insulation Test	20MΩ	10kΩ	±(2.0%+2)
	2000MΩ (Note<500M>	1MΩ	±(4.0%+2)
	2000MΩ (Note>500MΩ)	1MΩ	±(5.0%+2)

- 電 源：1×9V 6F22 電池
- 產品尺寸：235mm×96mm×46mm/9.25"×3.8"×1.8"
- 產品重量：268克/0.59磅
- 認 證：CE / ETL / RoHS
- 安全等級：CAT II 1000V/ CAT III 600V

- Power Supply：1×9V 6F22 Battery
- Product Size：235mm×96mm×46mm/9.25"×3.8"×1.8"
- Product Weight：268g/0.59lb
- Certification：CE / ETL / RoHS
- Safety Rating：CAT II 1000V/ CAT III 600V

Accessories

- 測試導線
- 手提袋
- 電池和用戶手冊
- Test leads
- Carry bag
- Battery and User's manual