

MASTECH_M320 數位萬用表 Pocket Digital Multimeter



產品特點

- 顯示4000計數
- 自動選檔
- 自動關機
- 二極體開路電壓1.5V
- 導通性蜂鳴器 <math> < 50 \pm 20 \Omega </math>
- 數據鎖定
- 低電量顯示

Features

- Display 4000 counts
- Auto Ranging
- Auto Power Off
- Diode Open Voltage 1.5V
- Continuity Buzzer <math> < 50 \pm 20 \Omega </math>
- Data Hold
- Low Battery Display

規格	量程	解析度	準確性
直流電壓	400mV/4V/40V/400V	0.1mV/1mV/10mV/100mV	±(0.5%+3)
	600V	1V	±(0.8%+3)
交流電壓	4V/40V/400V	1mV/10mV/100mV	±(0.8%+4)
	600V	1V	±(1.0%+4)
直流電流	40mA/400mA	0.1mA/1mA/10mA	±(2.0%+3)
交流電流	40mA/400mA	0.1mA/1mA/10mA	±(3.0%+4)
電阻	400Ω/4kΩ/40kΩ/400kΩ/4MΩ	0.1Ω/1Ω/10Ω/0.1kΩ/1kΩ	±(1.0%+3)
	40MΩ	10kΩ	±(2.0%+4)
電容	4nF	1pF	±(5.0%+10)
	40nF	10pF	±(4.0%+5)
	400nF/4uF/40uF/100uF	0.1nF/1nF/10nF/0.1μF	±(3.0%+3)
頻率	10Hz/100Hz/1kHz/10kHz/100kHz	0.01Hz/0.1Hz/1Hz/10Hz/0.1kHz	±(0.5%+3)

Specifications	Range	Resolution	Accuracy
DC Voltage	400mV/4V/40V/400V	0.1mV/1mV/10mV/100mV	±(0.5%+3)
	600V	1V	±(0.8%+3)
AC Voltage	4V/40V/400V	1mV/10mV/100mV	±(0.8%+4)
	600V	1V	±(1.0%+4)
DC Current	40mA/400mA	0.1mA/1mA/10mA	±(2.0%+3)
AC Current	40mA/400mA	0.1mA/1mA/10mA	±(3.0%+4)
Resistance	400Ω/4kΩ/40kΩ/400kΩ/4MΩ	0.1Ω/1Ω/10Ω/0.1kΩ/1kΩ	±(1.0%+3)
	40MΩ	10kΩ	±(2.0%+4)
Capacitance	4nF	1pF	±(5.0%+10)
	40nF	10pF	±(4.0%+5)
	400nF/4uF/40uF/100uF	0.1nF/1nF/10nF/0.1μF	±(3.0%+3)
Frequency	10Hz/100Hz/1kHz/10kHz/100kHz	0.01Hz/0.1Hz/1Hz/10Hz/0.1kHz	±(0.5%+3)

- 電 源 : 2x1.5V 357A(LR44) 電池
- 產品尺寸 : 120mmx70mmx18mm/4.7"x2.75"x0.7"
- 產品重量 : 110克/0.23磅
- 認 證 : CE / ETL / RoHS
- 安全等級 : CATIII 300V / CATII 600V

- Power Supply : 2x1.5V 357A(LR44) Batteries
- Product Size : 120mmx70mmx18mm/4.7"x2.75"x0.7"
- Product Weight : 110g/0.23lb
- Certificate : CE / ETL / RoHS
- Safety Rating : CATIII 300V / CATII 600V