

MASTECH_MS8250D USB 數位萬用表

Digital Multimeter with USB



產品特點

- 顯示6600計數
- 自動選檔
- 手動選檔
- 自動關機
- 相對測量
- 真有效值
- 非接觸式電壓檢測器
- 二極體開路電壓3.2V
- 導通性蜂鳴器 $<50\Omega$
- 最大值/最小值
- 進度條
- 數據鎖定
- 低電量顯示
- 顯示背光
- USB介面Windows OS

Features

- Display 6600 counts
- Auto Ranging
- Manual Ranging
- Auto Power Off
- Relative Measurement
- True RMS
- Non-Contact Voltage Detector
- Diode Open voltage 3.2V
- Continuity Buzzer $<50\Omega$
- MAX/MIN
- Bar Graph
- Data Hold
- Low Battery Display
- Display Backlight
- USB Interface Windows OS

規格	量程	解析度	準確性
直流電壓	660mV	0.1mV	±(0.8%+3)
	6.6V/66V/660V/1000V	1mV/10mV/0.1V/1V	±(0.5%+5)
交流電壓	660mV	0.1mV	±(1.5%+5)
	6.6V/66V	1mV/10mV	±(1.2%+5)
	660V/1000V	0.1V/1V	±(1.0%+3)
直流電流	660μA/6600μA/66mA/660mA	0.1μA/1μA/10μA/0.1mA	±(1.0%+5)
	10A	10mA	±(2.0%+5)
交流電流	660μA/6600μA/66mA/660mA	0.1μA/1μA/0.01mA/0.1mA	±(1.5%+5)
	10A	10mA	±(3.0%+5)
電阻	660Ω/6.6kΩ/66kΩ/660kΩ/6.6MΩ	0.1Ω/1Ω/10Ω/0.1kΩ/1kΩ	±(0.8%+5)
	66MΩ	10kΩ	±(1.5%+5)
電容	6.6nF	1pF	±(4.0%+5)
	66nF/660nF/6.6μF/66μF/660μF	10pF/0.1nF/1nF/10nF/0.1μF	±(3.0%+3)
	6.6mF/66mF	1μF/10μF	±(4.0%+5)
頻率	66Hz/660Hz/6.6kHz/66kHz	0.01Hz/0.1Hz/1Hz/10Hz	±(1.5%+5)
	660kHz/6.6MHz/66MHz	0.1kHz/1kHz/10kHz	±(1.5%+5)
工作週期	0.1%~99.9%	0.1%	±(2.0%+5)

Specifications	Range	Resolution	Accuracy
DC Voltage	660mV	0.1mV	±(0.8%+3)
	6.6V/66V/660V/1000V	1mV/10mV/0.1V/1V	±(0.5%+5)
AC Voltage	660mV	0.1mV	±(1.5%+5)
	6.6V/66V	1mV/10mV	±(1.2%+5)
	660V/1000V	0.1V/1V	±(1.0%+3)
DC Current	660μA/6600μA/66mA/660mA	0.1μA/1μA/10μA/0.1mA	±(1.0%+5)
	10A	10mA	±(2.0%+5)
AC Current	660μA/6600μA/66mA/660mA	0.1μA/1μA/0.01mA/0.1mA	±(1.5%+5)
	10A	10mA	±(3.0%+5)
Resistance	660Ω /6.6kΩ /66kΩ /660kΩ /6.6MΩ	0.1Ω /1Ω /10Ω /0.1kΩ /1kΩ	±(0.8%+5)
	66MΩ	10kΩ	±(1.5%+5)
Capacitance	6.6nF	1pF	±(4.0%+5)
	66nF/660nF/6.6μF/66μF/660μF	10pF/0.1nF/1nF/10nF/0.1μF	±(3.0%+3)
	6.6mF/66mF	1μF/10μF	±(4.0%+5)
Frequency	66Hz/660Hz/6.6kHz/66kHz	0.01Hz/0.1Hz/1Hz/10Hz	±(1.5%+5)
	660kHz/6.6MHz/66MHz	0.1kHz/1kHz/10kHz	±(1.5%+5)
Duty Cycle	0.1%~99.9%	0.1%	±(2.0%+5)

- 電 源 : 1x9V 6F22 電池
- 產品尺寸 : 175mmx86mmx52mm/6.89"x3.38"x2.04"
- 產品重量 : 372克/0.82磅
- 認 證 : CE / ETL / RoHS
- 安全等級 : CAT III 1000V / CATIV 600V

- Power Supply : 1x9V6F22 Battery
- Product Size : 175mmx86mmx52mm/6.89"x3.38"x2.04"
- Product Weight : 372g/0.82lb
- Certificate : CE / ETL / RoHS
- Safety Rating : CAT III 1000V / CATIV 600V

Accessories

- 測試導線
- USB線 接口
- 軟體光碟
- 電池和用戶手冊
- Test leads
- USB interface cable
- Software CD
- Battery and User's manual