sanwa

7 test voltage ranges Insulation Resistance Tester.

勝 特 力 材 料 886-3-5753170 胜特力电子(上海) 86-21-34970699 胜特力电子(深圳) 86-755-83298787

HG561H







CE

Though it is pocket size, when measuring $M\Omega$, the rated current is more than 1 mA.

- ■Automatically-held readings after measuring MΩ
 The LED level meter shows the reading
- ■The instrument makes only necessary voltages enabled between 15V, 25V, 50V, 100V, 125V, 250V, and 500V
- ■Easy-to-read LCD with the fixed decimal point.
- ■Provides the probe that enables you to measure through a hole of a circuit breaker cover.
- ■The lighting lamp illuminates a place to be measured, and the LCD has a backlight.



Safety: JIS C 1302

IEC61010 CAT.III 300V / CAT.II 600V

IEC61557

HG561H	Measuring range	Best accuracy	Resolution
ΜΩ	15V / 25V / 50V 9.99MΩ / 21.0MΩ 100V / 125V / 250V / 500V 9.99MΩ / 99.9MΩ / 110M	±(2%+5)	0.1ΜΩ
Test voltage	15V / 25V / 50V / 100V / 125V / 250V / 500V	Mar.	100
ACV / DCV	600V(AC/DC automatically selectable)	±(1.6%+7)	0.1V
	999.9Ω / 99.99kΩ / 999.9kΩ	±(1.5%+7)	0.1Ω
Insulation (Level meter)	15V / 25V / 50V 5 step(LED illumination or blinking) 100V / 125V / 250V / 500V 7 step(LED illumination or blinking)		
Continuity	Buzzer sounds at less than 30Ω		
Battery	LR03 x 4		
Size / Weight	H139 x W91 x D29mm / 230g		
Standard accessories included	Test Lead(TL-561), Aligator Clip(CL-561), Carrying Case(C-DG3a), Instruction Manual		