



WINDOW-TYPE CURRENT TRANSFORMER,
CLASS 3 50A/5A,
2,5VA PRIMARY CURRENT 50A, 2.5VA

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Similar to image

General technical details:

product designation	window-type current transformers	
Accuracy class / of the current transformer	class 3	
Ratio input current/output current	50/5 A	
Current		
• at the input / rated value	A	50
• secondary side / rated value	A	5
Operating apparent output / rated value	V·A	2.5
Ambient temperature		
• during operating	°C	-10 ... +55
Item designation		
• according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		T
• according to DIN EN 61346-2		T

Mechanical design:

Width / of the push-through bus bar		
• in case of 1 bus bar / maximum	mm	12
Outer diameter / of the push-through conductor / maximum	mm	17.5
Protection class IP		IP20

Depth	mm	80
Height	mm	74.5
Width	mm	48
Type of mounting	screw fixing	
Design of the electrical connection / secondary side	screw-type terminals	
Product equipment / touch-protection	Yes	

Certificates/approvals:

**General Product
Approval**

Declaration of Conformity



GOST



EG-Konf.