

UNI-T®

UT200 SERIES **Modern Digital Clamp Meters** **UT200A ■ UT200B**



EN:61010-1
 EN:61326-1
 EN:61010-2-032



■ UT200A

SPECIFICATIONS

Specifications	Range	Best Accuracy	
Model		UT200A	UT200B
AC Current (A)	2A/20A/200A 20A/200A/600A	± (1.5%+5)	± (1.5%+5)
AC Voltage (V)	600V	± (1.5%+5)	± (1.5%+5)
DC Voltage (V)	600V	± (1%+3)	± (1%+3)
Resistance (Ω)	20KΩ	±(1%+4)	±(1%+4)
Features			
Display Count		1999	1999
Manual Range		✓	✓
Jaw Capacity		28mm	28mm
Diode		✓	✓
Continuity Buzzer		✓	✓
Low Battery Indication		✓	✓
Data Hold		✓	✓
LCD Backlight		✓	✓
Input Impedance for DCV	Around 10MΩ	✓	✓

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	35.6mm × 18mm
Product Color	Red and Grey
Product Net Weight	260g
Product Size	208mm × 76mm × 30mm
Standard Accessories	Battery, Test Lead, Carrying Bag
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	540mm × 490mm × 335mm (0.087 CBM Per Standard Carton)
Standard Carton Gross Weight	23 Kg



■ UT200B

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)