

Scotch®

69 Glass Cloth Electrical Tape

Data Sheet



Product Description

Scotch® 69 Glass Cloth Electrical Tape is a white glass tape with a high-temperature thermosetting silicone adhesive. It has been designed for use in 600-volt dry location applications requiring both high mechanical strength and resistance to high temperatures. The thermosetting adhesive provides an increased bond, once applied in areas of high ambient temperatures. This tape has a class "H" 180°C (356°F) temperature rating.

Meets requirements of:

- Military Specification No. MIL-I-19166C
- UL Recognized Component listing for 200°C (Guide OANZ2, File E17385)
- CSA Accepted Component 180°C file LR93411

Applications

- Insulating electric and induction type furnace power supply leads
- Securing high-temperature, non-PSA insulation such as asbestos and glass) in high-temperature areas
- Securing Scotch® 77 Fire Retardant Electric Arc Proofing Tape
- Replacing Scotch® 27 Tape in locations where a higher temperature tape is needed
- Splicing wire that is rated 150°C (302°F), 180°C (356°F), SF and SFF
- Reinsulating and repairing coils on mining machines
- Reinforcing insulation in electrical installation where heavy loads cause high heat and breakdown of original insulation (e.g. motor control exciter feeds.
- Splicing silicone-covered glass wire where splices require more abrasion resistance and mechanical strength than can be provided by silicone tapes.

- Insulating Class "H" dry-type transformer leads
- Insulating splices made on SA type wire in heat treat areas.

Typical Data/Physical Properties

Test Method Typical Value*

Physical Properties

| | |
|---------------------------------|-------------------------|
| Thickness ASTM D-1000 | 7.5 mils (0,19mm) |
| Tensile Strength ASTM D-1000 | 150 lbs/in (26 kN/m) |
| Elongation ASTM D-1000 | 5% at break |
| Adhesion ASTM D-1000 | 40 oz/in (0,44 kN/m) |

Electrical Properties

| | |
|---|-------------------------|
| Dielectric Breakdown ASTM D-1000 | 3500V |
| Insulation Resistance ASTM D-1000 | 250 megohms @ 96% RH |
| Electrolytic Corrosion Factor 3M Test Method | 1.0 |

***These are typical values and should not be used for specification purposes.**

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Shelf life

Scotch® 69 Glass Cloth Electrical Tape has a 3-year shelf life from date of manufacture when stored under the following recommended storage conditions. Store behind present stock in a clean dry place at a temperature of 70°F and 40-50% relative humidity. Good stock rotation is recommended.

Availability

This glass cloth electrical tape is available from your local authorized 3M electrical distributor in the following sizes:

1/2 in. x 66 ft. (12,7 mm x 19,8m)

3/4 in. x 66 ft. (19 mm x 19.8m) rolls

勝特力材料 886-3-5753170

勝特力电子(上海) 86-21-34970699

勝特力电子(深圳) 86-755-83298787

[Http://www.100y.com.tw](http://www.100y.com.tw)

3M