

932F-UL 鐵氟龍膠帶

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



產品描述

932F Tape, construction is a PTFE film tapes which is one face with a heat-resistant silicon adhesive. 200°C temperature rating, anchoring bonding motor & transformers. The idea insulation tape for dielectric sealing and embossing engineered for use as high temperature. Ground insulation also offer a wear resistant anti-stick release surface in heat-sealing equipment

產品特性

具有 UL 認證,及耐酸鹼和耐高溫, 及低磨擦不沾粘的特性

產品規格

SIZE

Type width (mm)

The abovementioned data represent the average obtained in our laboratory.

Suggestion for use and final results on our best technical experiences but cannot be intended as our commitment or liability. The user will determine the suitability of the product and the method of application for each specific use

TECHNICAL CHARACTERISTICS:

Construction	PTFE film
Backing thickness (mm)	0.05
Overall thickness (mm)	0.085 ± 0.01
Standard color	Dark brown
Standard length (M)	10
Peel adhesion (gf / 25mm)	1000 ↑
Peel adhesion to own back (gf / 25mm)	600 ↑
Tensile strength (kgf / 10mm)	8
Elongation (%)	140
Breakdown voltage (KV)	9.5
Electrolytic corrosion coefficient	1.0
Class of insulation (°C)	Class H 180°C
Type of adhesive	Silicon
Flammability	UL 510 FR

- UL Recognized flame retardant
- UL Recognized class 200°C
- Separator for heat-sealing
- Anti-adhesion means against paste and adhesive materials
- Solvent resistant with thermosetting
- Conveyers for bread and confectionery

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)