

Dow Corning Silicone Trading (Shanghai) Co., Ltd.

Version No. 1.3 Revision Date: 27.08.2008

Page No.: 1/7

Material Safety Data Sheet

SYLGARD(R) 3-6605 THERMAL CONDUCTIVE ELASTOMER, KIT (PART B information is below)

1. IDENTIFICATION OF THE PRODUCT AND OF THE COMPANY

1.1 Product Name: SYLGARD(R) 3-6605 THERMAL CONDUCTIVE ELASTOMER, KIT (PART B

information is below)

1.2 Manufacturer's Product Code: 01913867

1.3 Chemical Classification: Silicone

1.4 Dangerous Goods Classification: Not applicable.

勝 特 力 材 料 886-3-5753170 胜特力电子(上海) 86-21-34970699 胜特力电子(深圳) 86-755-83298787

Http://www.100y.com.tw

2. COMPOSITION / INFORMATION ON INGREDIENTS

2.1 Chemical characterization: Mixture

2.2 Physical Form: Viscous Liquid

2.3 Color: Gray

2.4 Use: Sealant and adhesive

2.5 Hazardous Ingredients*:

Chemical Name CAS No. 96 (w/w) Symbols & Health Risk Phrases

No hazardous ingredients.

*According to European Commission Directive 1999/45/EC (Article 3 [3])

3. HAZARDS IDENTIFICATION

3.1 Overall Hazard Not hazardous.

Classification:

3.2 Hazard Information: Not hazardous.

Keep container in a well-ventilated place.

Keep away from sources of ignition - no smoking.

Avoid contact with skin and eyes.

3.3 Route of Exposure: Inhalation, skin contact and accidental ingestion.

3.4 Possible Health Effects:

Acute

Eyes: Direct contact may cause mild irritation.

Skin: No significant irritation expected from a single short-term exposure.

Inhalation: No significant effects expected from a single short-term exposure.

Page No.: 2/7 Version No. 1.3

SYLGARD(R) 3-6605 THERMAL CONDUCTIVE ELASTOMER, KIT (PART B information is below)

Low ingestion hazard in normal use. **Ingestion:**

Chronic

Repeated or prolonged exposure may cause irritation. Skin:

Inhalation: No known applicable information.

Ingestion: Repeated ingestion or swallowing large amounts may injure internally.

3.5 Signs and Symptoms of

Overexposure:

No significant adverse effects from a single exposure expected from normal use.

4. FIRST AID MEASURES

4.1 **Eves:** Immediately flush with water for 15 minutes.

4.2 Skin: No first aid should be needed. 4.3 No first aid should be needed. **Inhalation: Ingestion:** 4.4 Get medical attention.

Treat according to person's condition and specifics of exposure. 4.5 **Comments:**

4.6 Note to physicians: Treat symptomatically. For further information, the medical practitioner should contact

Dow Corning Silicone Trading (Shanghai) Co., Ltd.

5. FIRE FIGHTING MEASURES

5.1 Flammability: Non-flammable. 5.2 **Flash Point:** > 101 °C (Closed Cup) 5.3 **Autoignition temperature:** Not determined.

5.4 **Lower Flammability**

Limit:

Not determined.

Upper Flammability Limit: Not determined. 5.5 None.

5.6 **Hazardous Properties:**

5.7 On large fires use AFFF alcohol compatible foam or water spray (fog). On small fires use **Extinguishing Media:**

> AFFF alcohol compatible foam, CO2 or water spray (fog). Water can be used to cool fire exposed containers. Most fire extinguishing media will cause hydrogen evolution. When the fire is put out, hydrogen may accumulate in poorly ventilated or confined areas and result in flash fire or explosion if ignited. Foam blankets may also trap hydrogen or

勝 特 力 材 料 886-3-5753170

胜特力电子(上海) 86-21-34970699

胜特力电子(深圳) 86-755-83298787

Http://www.100y.com.tw

flammable vapors, with the possibility of subsurface explosion.

5.8 Special Fire Fighting Determine the need to evacuate or isolate the area according to your local emergency plan.

Use water spray to keep fire exposed containers cool. Self-contained breathing apparatus **Procedures and Equipment:**

and protective clothing should be worn in fighting large fires involving chemicals.

5.9 **Hazardous Combustion** Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide.

Products: Formaldehyde. Metal oxides. Hydrogen.

5.10 **Unsuitable Extinguishing** Dry powder. Do not allow extinguishing medium to contact container contents.

Media:

6. ACCIDENTAL RELEASE MEASURES

Page No.: 3/7 Version No. 1.3

SYLGARD(R) 3-6605 THERMAL CONDUCTIVE ELASTOMER, KIT (PART B information is below)

6.1 **Personal Precautions:** Avoid eye contact. Do not take internally.

Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or **Environmental**

Precautions: other appropriate barriers.

Methods for Cleaning up: Determine whether to evacuate or isolate the area according to your local emergency plan.

Observe all personal protective equipment recommendations described in this MSDS. If diked material can be pumped, store recovered material in appropriate container. Materials in contact with water, moisture, acids or bases have the potential to generate hydrogen gas. Recovered material should be stored in a vented container. Clean up remaining materials from spill with suitable absorbant. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which laws and regulations are applicable.

7. HANDLING AND STORAGE

7.1 **Handling Precautions:** Use with adequate ventilation. Avoid eye contact. Do not take internally. Exercise good

industrial hygiene practice. Wash after handling, especially before eating, drinking or

smoking.

7.2 Product evolves minute quantities of flammable hydrogen gas which can accumulate. Storage Conditions:

> Adequately ventilate to maintain vapors well below flammability limits and exposure guidelines. Do not repackage. Do not store in glass containers which may shatter due to pressure build up. Clogged container vents may increase pressure build up. Keep container

closed and store away from water or moisture.

7.3 **Unsuitable Packaging**

Materials:

Do not store in or use glass containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 **Industrial Hygiene Standards:**

Ingredients

None known.

8.2 **Engineering Controls**

> **Local Ventilation: General Ventilation:** Recommended.

8.3 **Personal Protective Equipment for Routine Handling**

No respiratory protection should be needed. WWW.100Y.COM.TW **Respiratory protection:**

Suitable Respirator: None should be needed.

勝 特 力 材 料 886-3-5753170 胜特力电子(上海) 86-21-34970699 胜特力电子(深圳) 86-755-83298787

Http://www. 100y. com. tw

Page No.: 4/7 Version No. 1.3

SYLGARD(R) 3-6605 THERMAL CONDUCTIVE ELASTOMER, KIT (PART B information is below)

Eye protection: Use proper protection - safety glasses as a minimum.

Hand protection: No special protection needed.

Skin protection: Washing at mealtime and end of shift is adequate.

Hygiene Measures: Exercise good industrial hygiene practice. Wash after handling, especially before eating,

drinking or smoking.

Personal Protective Equipment for Spills

No respiratory protection should be needed. **Respiratory protection:**

Eye protection: Use proper protection - safety glasses as a minimum.

Skin protection: Washing at mealtime and end of shift is adequate.

Precautionary Measures: Avoid eye contact. Do not take internally. Use reasonable care.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require

added precautions. For further information regarding aerosol inhalation toxicity, please refer to the guidance document regarding the use of silicone-based materials in aerosol applications that has been developed by the silicone industry

(www.SEHSC.com) or contact the Dow Corning customer service group.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Viscous Liquid **Physical Form:**

9.2 Color: Grav 9.3 Odor: Odorless

pH: 9.4 Not determined. Not determined. 9.5 Solubility in Water: 9.6 **Boiling Point:** > 35C/95F

9.7 **Melting Point:** Not determined. > 101 °C (Closed Cup) 9.8 **Flash Point:** 9.9 **Autoignition temperature:** Not determined.

9.10 **Explosive properties:** No 9.11 **Oxidizing properties:** No

9.12 Vapor Pressure @ 25°C: Not determined.

9.13 **Specific Gravity:** 2.1

9.14 Octanol/water partition Not determined.

coefficient:

9.15 Vapour Density (air=1): Not determined. 9.16 500 Poise Viscosity: 9.17 Not determined. **Molecular Weight:**

> The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

特力材料886-3-5753170 胜特力电子(上海) 86-21-34970699

胜特力电子(深圳) 86-755-83298787

Http://www.100y.com.tw

Page No.: 5/7 Version No. 1.3 Revision Date: 27.08.2008

勝 特 力 材 料 886-3-5753170

胜特力电子(上海) 86-21-34970699

胜特力电子(深圳) 86-755-83298787

Http://www. 100y. com. tw

SYLGARD(R) 3-6605 THERMAL CONDUCTIVE ELASTOMER, KIT (PART B information is below)

10. STABILITY AND REACTIVITY

10.1 Stability: Stable under normal usage conditions. Material may decompose (generating heat and gas)

if exposed to temperatures in excess of 250 degree C.

10.2 Reactivity

Conditions to Avoid: None

Materials to Avoid: Water, alcohols, acidic or basic materials, and many metals or metallic compounds, when

in contact with product, liberate flammable hydrogen gas, which can form explosive

mixtures in air. Can react with strong oxidising agents.

Hazardous Decomposition Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide.

Products: Formaldehyde. Metal oxides. Hydrogen. **Hazardous Polymerization:** Hazardous polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

11.1 Possible Health Effects: Refer to Section 3.411.2 Sensitizing Effects: None known.

11.3 Mutagenic Effects: None known.
11.4 Reproductive Effects: None known.
11.5 Carcinogenic Effects: None known.

11.6 Other Health Hazard No known applicable information.

Information:

The above listed potential effects of overexposure are based on actual data, the results of studies performed upon similar compositions, component data, and/or expert review of the products.

12. ECOLOGICAL INFORMATION

12.1 Environmental Fate and Distribution:

Siloxanes are removed from water by sedimentation or binding to sewage sludge. In soil, siloxanes are degraded.

12.2 Environmental Effects:

No adverse effects on aquatic organisms.

Bioaccumulation: No bioaccumulation potential.

12.3 Fate and Effects in Waste Water Treatment Plants:

Removed > 90% by binding onto sewage sludge. No adverse effects on bacteria. The siloxanes in this product do not contribute to the BOD.

12.4 Additional Environmental Information:

Degradation: Additional environmental information on the silicone component is available on request.



Dow Corning Silicone Trading (Shanghai) Co., Ltd.

Version No. 1.3 Revision Date: 27.08.2008

Page No.: 6/7

Material Safety Data Sheet

SYLGARD(R) 3-6605 THERMAL CONDUCTIVE ELASTOMER, KIT (PART B information is below)

13. DISPOSAL CONSIDERATIONS

13.1 Product Disposal: Dispose of in accordance with local regulations.

13.2 Packaging Disposal: Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

14.1 Road and Rail Transport:

Not applicable.

14.2 Sea Transport (IMDG):

Not subject to IMDG code.

14.3 Air Transport (IATA):

Not subject to IATA regulations.

勝 特 力 材 料 886-3-5753170 胜特力电子(上海) 86-21-34970699 胜特力电子(深圳) 86-755-83298787

Http://www. 100y. com. tw

15. REGULATORY INFORMATION

15.1 Applicable Laws:

Provisions of the Regulations for the Safe Handling of Chemicals in the Workplace, particularly those relating to the safe use, production, storage and transportation of dangerous chemicals.

15.2 Chemical Inventories:

AICS: All ingredients listed or exempt.

DSL: Consult your local Dow Corning office.

EINECS: All ingredients listed or exempt.

IECSC: All ingredients listed or exempt.

KECL: All ingredients listed, exempt or notified.

MITI: All components are listed on ENCS or its exempt rule.

PICCS: Consult your local Dow Corning office.

TSCA: All chemical substances in this material are included on or exempted from listing on the

TSCA Inventory of Chemical Substances.

16. OTHER INFORMATION

Contact Point: Technical Information Center (86 21)37747110
Prepared by: Dow Corning Silicone Trading (Shanghai) Co., Ltd.



Page No.: 7/7 Version No. 1.3 Revision Date: 27.08.2008

SYLGARD(R) 3-6605 THERMAL CONDUCTIVE ELASTOMER, KIT (PART B information is below)

This information is offered in good faith as typical values and not as a product specification. No warranty, expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

(R) indicates Registered Trademark

W.100Y.COM.T

WWW.100Y.COM

勝 特 力 材 料 886-3-5753170 胜特力电子(上海) 86-21-34970699 胜特力电子(深圳) 86-755-83298787 Http://www.100v.com.tw