

**Dow Corning Silicone Trading (Shanghai) Co., Ltd.**  
**Material Safety Data Sheet**

Page No.: 1/7  
Version No. 1.6  
Revision Date: 05.09.2008

**SYLGARD(R) 577 PRIMERLESS SILICONE ADHESIVE KIT (CURING AGENT information is below)**

**1. IDENTIFICATION OF THE PRODUCT AND OF THE COMPANY**

- 1.1 Product Name:** SYLGARD(R) 577 PRIMERLESS SILICONE ADHESIVE KIT (CURING AGENT information is below)
- 1.2 Manufacturer's Product Code:** 01755811
- 1.3 Chemical Classification:** Silicone
- 1.4 Dangerous Goods Classification:** Not applicable.

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-34970699  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

**2. COMPOSITION / INFORMATION ON INGREDIENTS**

- 2.1 Chemical characterization:** Mixture
- 2.2 Physical Form:** Liquid
- 2.3 Color:** Black
- 2.4 Use:** Silicone rubber curing agent
- 2.5 Hazardous Ingredients\*:**

<u>Chemical Name</u>	<u>CAS No.</u>	<u>% (w/w)</u>	<u>Symbols &amp; Health Risk Phrases</u>
----------------------	----------------	----------------	--

No hazardous ingredients.

\*According to European Commission Directive 1999/45/EC (Article 3 [3])

**3. HAZARDS IDENTIFICATION**

- 3.1 Overall Hazard Classification:** Not hazardous.
- 3.2 Hazard Information:** Not hazardous.  
Keep container in a well-ventilated place.  
Do not keep the container sealed.  
Keep away from sources of ignition - no smoking.  
Avoid contact with skin and eyes.
- 3.3 Route of Exposure:** Inhalation, skin contact and accidental ingestion.
- 3.4 Possible Health Effects:**
- |              |   |
|--------------|---|
| <u>Acute</u> |   |
| <u>Eyes:</u> | Direct contact may cause temporary redness and discomfort.            |
| <u>Skin:</u> | No significant irritation expected from a single short-term exposure. |

**Dow Corning Silicone Trading (Shanghai) Co., Ltd.**  
**Material Safety Data Sheet**

Page No.: 2/7  
Version No. 1.6  
Revision Date: 05.09.2008

**SYLGARD(R) 577 PRIMERLESS SILICONE ADHESIVE KIT (CURING AGENT information is below)**

<b>Inhalation:</b>	No significant effects expected from a single short-term exposure.
<b>Ingestion:</b>	Low ingestion hazard in normal use.
<b>Chronic</b>	
<b>Skin:</b>	No known applicable information.
<b>Inhalation:</b>	No known applicable information.
<b>Ingestion:</b>	Repeated ingestion or swallowing large amounts may injure internally.
<b>3.5 Signs and Symptoms of Overexposure:</b>	No significant adverse effects from a single exposure expected from normal use.

#### 4. FIRST AID MEASURES

<b>4.1 Eyes:</b>	Immediately flush with water.
<b>4.2 Skin:</b>	No first aid should be needed.
<b>4.3 Inhalation:</b>	No first aid should be needed.
<b>4.4 Ingestion:</b>	Get medical attention.
<b>4.5 Comments:</b>	Treat symptomatically.
<b>4.6 Note to physicians:</b>	Treat symptomatically. For further information, the medical practitioner should contact Dow Corning Silicone Trading (Shanghai) Co., Ltd.

#### 5. FIRE FIGHTING MEASURES

<b>5.1 Flammability:</b>	Non-flammable.
<b>5.2 Flash Point:</b>	102 °C (Seta Closed Cup)
<b>5.3 Autoignition temperature:</b>	Not determined.
<b>5.4 Lower Flammability Limit:</b>	Not determined.
<b>5.5 Upper Flammability Limit:</b>	Not determined.
<b>5.6 Hazardous Properties:</b>	None.
<b>5.7 Extinguishing Media:</b>	On large fires use AFFF alcohol compatible foam or water spray (fog). On small fires use AFFF alcohol compatible foam, CO2 or water spray (fog). Water can be used to cool fire exposed containers. Most fire extinguishing media will cause hydrogen evolution. When the fire is put out, hydrogen may accumulate in poorly ventilated or confined areas and result in flash fire or explosion if ignited. Foam blankets may also trap hydrogen or flammable vapors, with the possibility of subsurface explosion.
<b>5.8 Special Fire Fighting Procedures and Equipment:</b>	Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool. Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals.
<b>5.9 Hazardous Combustion Products:</b>	Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde. Silicon dioxide. Hydrogen.
<b>5.10 Unsuitable Extinguishing Media:</b>	Dry powder. Do not allow extinguishing medium to contact container contents.

**勝特力材料 886-3-5753170**  
**勝特力电子(上海) 86-21-34970699**  
**勝特力电子(深圳) 86-755-83298787**  
[Http://www.100y.com.tw](http://www.100y.com.tw)

#### 6. ACCIDENTAL RELEASE MEASURES

**Dow Corning Silicone Trading (Shanghai) Co., Ltd.**  
**Material Safety Data Sheet**

Page No.: 3/7  
Version No. 1.6  
Revision Date: 05.09.2008

**SYLGARD(R) 577 PRIMERLESS SILICONE ADHESIVE KIT (CURING AGENT information is below)**

- |                                       |  |
|---------------------------------------|--|
| <b>6.1 Personal Precautions:</b>      | Avoid eye contact. Do not take internally.   |
| <b>6.2 Environmental Precautions:</b> | Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers.  |
| <b>6.3 Methods for Cleaning up:</b>   | Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protective equipment recommendations described in this MSDS. If diked material can be pumped, store recovered material in appropriate container. Materials in contact with water, moisture, acids or bases have the potential to generate hydrogen gas. Recovered material should be stored in a vented container. Clean up remaining materials from spill with suitable absorbant. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which laws and regulations are applicable. |

## 7. HANDLING AND STORAGE

- |  |   |
|--|---|
| <b>7.1 Handling Precautions:</b>           | Use with adequate ventilation. Avoid eye contact. Do not take internally. Exercise good industrial hygiene practice. Wash after handling, especially before eating, drinking or smoking.  |
| <b>7.2 Storage Conditions:</b>             | Product evolves minute quantities of flammable hydrogen gas which can accumulate. Adequately ventilate to maintain vapors well below flammability limits and exposure guidelines. Do not repackage. Do not store in glass containers which may shatter due to pressure build up. Clogged container vents may increase pressure build up. Keep container closed and store away from water or moisture. |
| <b>7.3 Unsuitable Packaging Materials:</b> | Do not store in or use glass containers.  |

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Industrial Hygiene Standards:

**Ingredients**

None known.

**CAS No.**

**Exposure Limits**

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-34970699  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

### 8.2 Engineering Controls

**Local Ventilation:**

Recommended.

**General Ventilation:**

Recommended.

### 8.3 Personal Protective Equipment for Routine Handling

**Respiratory protection:**

No respiratory protection should be needed.

**Suitable Respirator:**

None should be needed.

**Dow Corning Silicone Trading (Shanghai) Co., Ltd.**  
**Material Safety Data Sheet**

Page No.: 4/7  
Version No. 1.6  
Revision Date: 05.09.2008

**SYLGARD(R) 577 PRIMERLESS SILICONE ADHESIVE KIT (CURING AGENT information is below)**

<b>Eye protection:</b>	Use proper protection - safety glasses as a minimum.
<b>Hand protection:</b>	No special protection needed.
<b>Skin protection:</b>	Washing at mealtime and end of shift is adequate.
<b>Hygiene Measures:</b>	Exercise good industrial hygiene practice. Wash after handling, especially before eating, drinking or smoking.

#### 8.4 Personal Protective Equipment for Spills

<b>Respiratory protection:</b>	No respiratory protection should be needed.
<b>Eye protection:</b>	Use proper protection - safety glasses as a minimum.
<b>Skin protection:</b>	Washing at mealtime and end of shift is adequate.
<b>Precautionary Measures:</b>	Avoid eye contact. Do not take internally. Use reasonable care.
<b>Comments:</b>	If this product is heated to > 180 degrees C, trace quantities of formaldehyde may be released, and adequate ventilation is required.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions. For further information regarding aerosol inhalation toxicity, please refer to the guidance document regarding the use of silicone-based materials in aerosol applications that has been developed by the silicone industry ([www.SEHSC.com](http://www.SEHSC.com)) or contact the Dow Corning customer service group.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>9.1 Physical Form:</b>	Liquid
<b>9.2 Color:</b>	Black
<b>9.3 Odor:</b>	Not available
<b>9.4 pH:</b>	Not determined.
<b>9.5 Solubility in Water:</b>	Not determined.
<b>9.6 Boiling Point:</b>	> 137 °C
<b>9.7 Melting Point:</b>	Not determined.
<b>9.8 Flash Point:</b>	102 °C (Seta Closed Cup)
<b>9.9 Autoignition temperature:</b>	Not determined.
<b>9.10 Explosive properties:</b>	No
<b>9.11 Oxidizing properties:</b>	No
<b>9.12 Vapor Pressure @ 25°C:</b>	Not determined.
<b>9.13 Specific Gravity:</b>	1.05
<b>9.14 Octanol/water partition coefficient:</b>	Not determined.
<b>9.15 Vapour Density (air=1):</b>	Not determined.
<b>9.16 Viscosity:</b>	1800 cSt
<b>9.17 Molecular Weight:</b>	Not determined.

**勝特力材料 886-3-5753170**  
**勝特力电子(上海) 86-21-34970699**  
**勝特力电子(深圳) 86-755-83298787**  
[Http://www.100y.com.tw](http://www.100y.com.tw)

The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

**Dow Corning Silicone Trading (Shanghai) Co., Ltd.**  
**Material Safety Data Sheet**

Page No.: 5/7  
Version No. 1.6  
Revision Date: 05.09.2008

**SYLGARD(R) 577 PRIMERLESS SILICONE ADHESIVE KIT (CURING AGENT information is below)**

## 10. STABILITY AND REACTIVITY

- 10.1 Stability:** Stable under normal usage conditions. Material may decompose (generating heat and gas) if exposed to temperatures in excess of 250 degree C.
- 10.2 Reactivity**
- Conditions to Avoid:** None.
- Materials to Avoid:** Water, alcohols, acidic or basic materials, and many metals or metallic compounds, when in contact with product, liberate flammable hydrogen gas, which can form explosive mixtures in air. Can react with strong oxidising agents.
- Hazardous Decomposition Products:** Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde. Silicon dioxide. Hydrogen.
- Hazardous Polymerization:** Hazardous polymerization will not occur.

## 11. TOXICOLOGICAL INFORMATION

- 11.1 Possible Health Effects:** Refer to Section 3.4
- 11.2 Sensitizing Effects:** None known.
- 11.3 Mutagenic Effects:** None known.
- 11.4 Reproductive Effects:** None known.
- 11.5 Carcinogenic Effects:** None known.
- 11.6 Other Health Hazard Information:** No known applicable information.

**勝特力材料 886-3-5753170**  
**胜特力电子(上海) 86-21-34970699**  
**胜特力电子(深圳) 86-755-83298787**  
[Http://www.100y.com.tw](http://www.100y.com.tw)

The above listed potential effects of overexposure are based on actual data, the results of studies performed upon similar compositions, component data, and/or expert review of the products.

## 12. ECOLOGICAL INFORMATION

- 12.1 Environmental Fate and Distribution:**
- Siloxanes are removed from water by sedimentation or binding to sewage sludge. In soil, siloxanes are degraded.
- 12.2 Environmental Effects:**
- No adverse effects on aquatic organisms.
- Bioaccumulation:** No bioaccumulation potential.
- 12.3 Fate and Effects in Waste Water Treatment Plants:**
- Removed > 90% by binding onto sewage sludge. No adverse effects on bacteria. The siloxanes in this product do not contribute to the BOD.
- 12.4 Additional Environmental Information:**
- Degradation:** Additional environmental information on the silicone component is available on request.

**Dow Corning Silicone Trading (Shanghai) Co., Ltd.  
Material Safety Data Sheet**Page No.: 6/7  
Version No. 1.6  
Revision Date: 05.09.2008**SYLGARD(R) 577 PRIMERLESS SILICONE ADHESIVE KIT (CURING  
AGENT information is below)****13. DISPOSAL CONSIDERATIONS**

- 13.1 Product Disposal:** Dispose of in accordance with local regulations.
- 13.2 Packaging Disposal:** Dispose of in accordance with local regulations.

**14. TRANSPORT INFORMATION****14.1 Road and Rail Transport:**

Not applicable.

**14.2 Sea Transport (IMDG):**

Not subject to IMDG code.

**14.3 Air Transport (IATA):**

Not subject to IATA regulations.

Remarks: VENTED PACKAGES ARE FORBIDDEN FOR AIR TRANSPORT.

勝 特 力 材 料 886-3-5753170  
勝特力电子(上海) 86-21-34970699  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

**15. REGULATORY INFORMATION****15.1 Applicable Laws:**

Provisions of the Regulations for the Safe Handling of Chemicals in the Workplace, particularly those relating to the safe use, production, storage and transportation of dangerous chemicals.

**15.2 Chemical Inventories:**

**AICS:** All ingredients listed or exempt.

**DSL:** All chemical substances in this material are included on or exempted from the DSL.

**IECSC:** All ingredients listed or exempt.

**EINECS:** All ingredients listed or exempt.

**MITI:** All components are listed on ENCS or its exempt rule.

**KECL:** All ingredients listed, exempt or notified.

**PICCS:** All ingredients listed or exempt.

**TSCA:** All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

**16. OTHER INFORMATION**

Contact Point: Technical Information Center (86 21)37747110  
Prepared by: Dow Corning Silicone Trading (Shanghai) Co., Ltd.

**Dow Corning Silicone Trading (Shanghai) Co., Ltd.  
Material Safety Data Sheet**Page No.: 7/7  
Version No. 1.6  
Revision Date: 05.09.2008**SYLGARD(R) 577 PRIMERLESS SILICONE ADHESIVE KIT (CURING  
AGENT information is below)**

This information is offered in good faith as typical values and not as a product specification. No warranty, expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

(R) indicates Registered Trademark

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-34970699  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)