

Dow Corning (Shanghai) Management Co. Ltd.
Material Safety Data Sheet

Page No.: 1/8
Version No. 2.7
Revision Date: 21.04.2009

**DOW CORNING(R) SILICONE 780 PLUMBERS' & ROOFERS'
SEALANT - TRANSLUCENT**

1. IDENTIFICATION OF THE PRODUCT AND OF THE COMPANY

- 1.1 **Product Name:** DOW CORNING(R) SILICONE 780 PLUMBERS' & ROOFERS' SEALANT - TRANSLUCENT
- 1.2 **Manufacturer's Product Code:** 02968835
- 1.3 **Chemical Classification:** Silicone Sealant
- 1.4 **Dangerous Goods Classification:** Not applicable.

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

2. COMPOSITION / INFORMATION ON INGREDIENTS

- 2.1 **Chemical characterization:** Mixture
- 2.2 **Physical Form:** Paste
- 2.3 **Color:** Colorless
- 2.4 **Use:** Sealant and adhesive, Sealant
- 2.5 **Hazardous Ingredients*:**

<u>Chemical Name</u>	<u>CAS No.</u>	<u>% (w/w)</u>	<u>Symbols & Health Risk Phrases</u>
----------------------	----------------	----------------	--

**Dow Corning (Shanghai) Management Co. Ltd.
Material Safety Data Sheet**

**DOW CORNING(R) SILICONE 780 PLUMBERS' & ROOFERS'
SEALANT - TRANSLUCENT**

Hydrotreated middle petroleum distillates	64742-46-7	<10	Harmful. Harmful: May cause lung damage if swallowed.
Methyl tri(ethylmethylketoxime) silane	22984-54-9	<10	Irritant. Irritating to eyes and skin. May cause sensitization by skin contact.
Methylethylketoxime	96-29-7	<10	Harmful. Irritant. Harmful in contact with skin. Limited evidence of a carcinogenic effect. Risk of serious damage to eyes. May cause sensitization by skin contact.
Di (ethylmethylketoxime) methoxymethyl silane	83817-72-5	<10	Highly flammable. Harmful. Irritant. Highly flammable. Harmful if swallowed. Irritating to eyes. May cause sensitization by skin contact.

*According to European Commission Directive 1999/45/EC (Article 3 [3])

3. HAZARDS IDENTIFICATION

3.1 Overall Hazard Classification:	Irritant. Harmful.
3.2 Hazard Information:	Limited evidence of a carcinogenic effect. May cause sensitization by skin contact. Avoid contact with eyes. Wear suitable protective clothing and gloves. Use only in well-ventilated areas.
3.3 Route of Exposure:	Skin contact and accidental ingestion.
3.4 Possible Health Effects:	
<u>Acute</u>	
Eyes:	Direct contact may cause mild irritation.
Skin:	May cause moderate irritation.
Inhalation:	Irritates respiratory passages very slightly. Vapor overexposure may cause drowsiness.
Ingestion:	Low ingestion hazard in normal use. Overexposure by ingestion may cause drowsiness, dizziness, confusion or loss of coordination.
<u>Chronic</u>	
Skin:	Repeated skin contact may cause allergic skin reaction. Repeated or prolonged contact may cause defatting and drying of skin which may result in skin irritation and dermatitis.
Inhalation:	Overexposure by inhalation may injure the following organ(s): Blood. Liver.
Ingestion:	Repeated ingestion or swallowing large amounts may injure internally.

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Dow Corning (Shanghai) Management Co. Ltd.
Material Safety Data Sheet

Page No.: 3/8
 Version No. 2.7
 Revision Date: 21.04.2009

**DOW CORNING(R) SILICONE 780 PLUMBERS' & ROOFERS'
 SEALANT - TRANSLUCENT**

3.5 Signs and Symptoms of Overexposure: Limited evidence of a carcinogenic effect.
 May cause allergic reaction to skin after skin contact.

4. FIRST AID MEASURES

4.1 Eyes: Immediately flush with water for 15 minutes.
4.2 Skin: Remove from skin and immediately flush with water for 15 minutes. Get medical attention if irritation or ill effects develop or persist.
4.3 Inhalation: Remove to fresh air. Get medical attention if ill effects persist.
4.4 Ingestion: Get medical attention.
4.5 Comments: Treat according to person's condition and specifics of exposure.
4.6 Note to physicians: Treat symptomatically. For further information, the medical practitioner should contact Dow Corning (Shanghai) Management Co., Ltd.

5. FIRE-FIGHTING MEASURES

5.1 Flammability: Non-flammable.
5.2 Flash Point: 100 °C (Closed Cup)
5.3 Autoignition temperature: Not determined.
5.4 Lower Flammability Limit: Not determined.
5.5 Upper Flammability Limit: Not determined.
5.6 Hazardous Properties: None.

5.7 Extinguishing Media: On large fires use dry chemical or foam. On small fires use CO2 or dry chemical. Water can be used to cool fire exposed containers.

5.8 Special Fire Fighting Procedures and Equipment: Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool. Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals.

5.9 Hazardous Combustion Products: Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide. Formaldehyde. Nitrogen oxides.

5.10 Unsuitable Extinguishing Media: Water. Do not allow extinguishing medium to contact container contents.

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions: Avoid skin and eye contact. Avoid breathing vapor. Keep container closed. Do not take internally.

6.2 Environmental Precautions: Do not allow large quantities to enter drains or surface waters.

Dow Corning (Shanghai) Management Co. Ltd.
 Material Safety Data Sheet

Page No.: 4/8
 Version No. 2.7
 Revision Date: 21.04.2009

**DOW CORNING(R) SILICONE 780 PLUMBERS' & ROOFERS'
 SEALANT - TRANSLUCENT**

- 6.3 Methods for Cleaning up:** Observe all personal protective equipment recommendations described in this MSDS. If diked material can be pumped, store recovered material in appropriate container. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which laws and regulations are applicable.

7. HANDLING AND STORAGE

- 7.1 Handling Precautions:** Use with adequate ventilation. Product evolves methyl ethyl ketoxime (MEKO) when exposed to water or humid air. Provide ventilation during use to control methyl ethyl ketoxime (MEKO) within exposure guidelines or use respiratory protection. Product evolves flammable methyl alcohol when exposed to water or humid air. Provide ventilation during use to control methyl alcohol exposures within exposure guidelines or use air-supplied or self-contained breathing apparatus. Avoid skin and eye contact. Avoid breathing vapor. Keep container closed. Do not take internally. Remove contaminated clothing immediately. Exercise good industrial hygiene practice. Wash after handling, especially before eating, drinking or smoking.
- 7.2 Storage Conditions:** Use reasonable care and store away from oxidizing materials. Keep container closed and store away from water or moisture.
- 7.3 Unsuitable Packaging Materials:** None established.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Industrial Hygiene Standards:

<u>Ingredients</u>	<u>CAS No.</u>	<u>Exposure Limits</u>
Hydrotreated middle petroleum distillates	64742-46-7	Observe oil mist limits. OSHA PEL (final rule) and ACGIH TLV: TWA 5 mg/m ³ ; ACGIH STEL 10 mg/m ³ .
Methyl tri(ethylmethylketoxime) silane	22984-54-9	See ethyl methyl ketoxime comments.
Methylethylketoxime	96-29-7	Vendor guide: TWA 3 ppm, STEL 10 ppm.
Di (ethylmethylketoxime) methoxymethyl silane	83817-72-5	See methyl alcohol and ethyl methyl ketoxime comments.

Ethyl methyl ketoxime is formed upon contact with water or humid air. Provide adequate ventilation to control exposures within the following exposure guidelines: Vendor guide TWA: 3 ppm, STEL: 10 ppm. Methyl alcohol forms on contact with water or humid air. Provide adequate ventilation to control exposures within guidelines of OSHA PEL: TWA 200 ppm and ACGIH TLV-skin: TWA 200 ppm, STEL 250 ppm.

Dow Corning (Shanghai) Management Co. Ltd.
Material Safety Data Sheet

Page No.: 5/8
Version No. 2.7
Revision Date: 21.04.2009

**DOW CORNING(R) SILICONE 780 PLUMBERS' & ROOFERS'
SEALANT - TRANSLUCENT**

8.2 Engineering Controls

Local Ventilation: Recommended.
General Ventilation: Recommended.

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

8.3 Personal Protective Equipment for Routine Handling

Respiratory protection: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. IH personnel can assist in judging the adequacy of existing engineering controls.

Suitable Respirator: Organic Vapor Type.

Eye protection: Use proper protection - safety glasses as a minimum.

Hand protection: Butyl Rubber. Natural Rubber. Neoprene Rubber(R). Nitrile Rubber.

Skin protection: Wash at mealtime and end of shift. If skin contact occurs, change contaminated clothing as soon as possible and thoroughly flush affected areas with cool water. Chemical protective gloves are recommended.

Hygiene Measures: Remove contaminated clothing immediately. Exercise good industrial hygiene practice. Wash after handling, especially before eating, drinking or smoking.

8.4 Personal Protective Equipment for Spills

Respiratory protection: Use self-contained breathing apparatus (SCBA) or other supplied-air respirator.

Eye protection: Use full face respirator.

Skin protection: Wash at mealtime and end of shift. If skin contact occurs, change contaminated clothing as soon as possible and thoroughly flush affected areas with cool water. Chemical protective gloves are recommended.

Precautionary Measures: Avoid skin and eye contact. Avoid breathing vapor. Keep container closed. Do not take internally. Use reasonable care.

Comments: Product evolves methyl ethyl ketoxime (MEKO) when exposed to water or humid air. Provide ventilation during use to control methyl ethyl ketoxime (MEKO) within exposure guidelines or use respiratory protection.

Product evolves flammable methyl alcohol when exposed to water or humid air. Provide ventilation during use to control methyl alcohol exposures within exposure guidelines or use air-supplied or self-contained breathing apparatus.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

DOW CORNING(R) SILICONE 780 PLUMBERS' & ROOFERS'
SEALANT - TRANSLUCENT

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1	Physical Form:	Paste
9.2	Color:	Colorless
9.3	Odor:	Some odor
9.4	pH:	Not determined.
9.5	Solubility in Water:	Not determined.
9.6	Boiling Point:	Not determined.
9.7	Melting Point:	Not determined.
9.8	Flash Point:	100 °C (Closed Cup)
9.9	Autoignition temperature:	Not determined.
9.10	Explosive properties:	No
9.11	Oxidizing properties:	No
9.12	Vapor Pressure @ 25°C:	Not determined.
9.13	Specific Gravity:	0.985
9.14	Octanol/water partition coefficient:	Not determined.
9.15	Vapour Density (air=1):	Not determined.
9.16	Viscosity:	Not determined.
9.17	Molecular Weight:	Not determined.

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

10. STABILITY AND REACTIVITY

10.1	Stability:	Stable.
10.2	Reactivity	
	Conditions to Avoid:	None.
	Materials to Avoid:	Can react with strong oxidising agents. Water, moisture or humid air can cause hazardous vapors to form.
	Hazardous Decomposition Products:	Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide. Formaldehyde. Nitrogen oxides.
	Hazardous Polymerization:	Hazardous polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

11.1	Possible Health Effects:	Refer to Section 3.4
11.2	Sensitizing Effects:	
	% (w/w)	Ingredients
	<10	Methyl tri(ethylmethylketoxime) silane
	<10	Methylethylketoxime
	<10	Di (ethylmethylketoxime) methoxymethyl silane
11.3	Mutagenic Effects:	None known.

Dow Corning (Shanghai) Management Co. Ltd.
Material Safety Data Sheet

Page No.: 7/8
Version No. 2.7
Revision Date: 21.04.2009

**DOW CORNING(R) SILICONE 780 PLUMBERS' & ROOFERS'
SEALANT - TRANSLUCENT**

11.4 Reproductive Effects:	None known.
11.5 Carcinogenic Effects:	None known.
11.6 Other Health Hazard Information:	Contains Methyl Ethyl Ketoxime (MEKO). Male rodents exposed to MEKO vapor throughout their lifetime developed liver cancer. Additional testing is planned by the MEKO supplier to determine any relevance to humans. Until more data is known, exposure levels should be maintained as low as achievable.

The above listed potential effects of overexposure are based on actual data, the results of studies performed upon similar compositions, component data, and/or expert review of the products.

12. ECOLOGICAL INFORMATION

12.1 Environmental Fate and Distribution:

Solid material, insoluble in water. No adverse effects are predicted.

12.2 Environmental Effects:

No adverse effects on aquatic organisms are predicted.

Bioaccumulation: No bioaccumulation potential.

12.3 Fate and Effects in Waste Water Treatment Plants:

No adverse effects on bacteria are predicted.

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

13. DISPOSAL CONSIDERATIONS

13.1 Product Disposal: Dispose of in accordance with local regulations.

13.2 Packaging Disposal: Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

14.1 Road and Rail Transport:

Not applicable.

14.2 Sea Transport (IMDG):

Not subject to IMDG code.

14.3 Air Transport (IATA):

Not subject to IATA regulations.

**Dow Corning (Shanghai) Management Co. Ltd.
Material Safety Data Sheet**Page No.: 8/8
Version No. 2.7
Revision Date: 21.04.2009**DOW CORNING(R) SILICONE 780 PLUMBERS' & ROOFERS'
SEALANT - TRANSLUCENT****15. REGULATORY INFORMATION****15.1 Applicable Laws:**

Provisions of the Regulations for the Safe Handling of Chemicals in the Workplace, particularly those relating to the safe use, production, storage and transportation of dangerous chemicals.

15.2 Chemical Inventories:

EINECS:	All ingredients listed or exempt.
TSCA:	All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.
AICS:	All ingredients listed or exempt.
IECSC:	All ingredients listed or exempt.
KECL:	All ingredients listed, exempt or notified.
HSNO:	All ingredients listed or exempt.
PICCS:	All ingredients listed or exempt.
DSL:	All chemical substances in this material are included on or exempted from the DSL.
ENCS/ISHL:	All components are listed on ENCS/ISHL or its exempt rule.

16. OTHER INFORMATION

Contact Point: Technical Information Center (86 21)37747110
Prepared by: Dow Corning (Shanghai) Management Co. Ltd.

This information is offered in good faith as typical values and not as a product specification. No warranty, expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

(R) indicates Registered Trademark

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)