

1、Metal Glass Level EP-ML01



Details:

Material	Lead-free glass, Aluminum alloy
Diamter	25mm±0.1
Wall Thickness	0.9mm
High	9mm±0.1
Precision	4S-30M/2mm (Tolerance±1')
Bubble Size	XY mm (Tolerance±0.1) /20°C
Liquid in Side	ROHS purity solvents
Work Temputer	-40°C — +60°C
Store Temputer	-50°C — +70°C
Bubble change	0.02mm/°C
Bubble hit time	5S

2、EPOCH Round Level EP-WX3207



Details:

Material	PMMA
Accuracy	30' ± 5'
Discription	Round Bubble level · Clear import good material · Yellow Green Liquid · Dark Black Line (We can produce as your order information) .
Where Use	Picture Farme,Photographic Equipment, Sight, Weighing, Surveying Instruments and others.
Guarantee Period	Six Year

ITEM NUMBER	D1(mm)	D2(mm)	D3(mm)	D4(mm)	H(mm)	Precision
EP-WX0805	2	4	8		5.5	30' - 2°

EP-WX1006	3	5	10		6	30° - 2°
EP-WX1185	2.5	5	11		8.5	30° - 2°
EP-WX1206	2.5	5	12		6	30° - 2°
EP-WX1207	2.5	5	12		7	30° - 2°
EP-WX1275	2.5	5	12		7.5	30° - 2°
EP-WX1506	3.5	6	15		6	30° - 2°
EP-WX1508	3.5	6	15		8	30° - 2°
EP-WX1608	3.5	7	16		8	30° - 2°
EP-WX1809	3.5	5	18		9	30° - 2°
EP-WX2510	5	10	25		10	30° - 2°
EP-WX3010	5.5	9	30		10	30° - 2°
EP-WX3207	5.5	9	32		7	30° - 2°
EP-WX4312	5.5	9	30	43	12	30° - 2°
EP-WX5017	5.5	8	32	50	17	30° - 2°
EP-WX6610	7.5	10	66		10	30° - 2°
EP-WX8013	9.5	15	60	80	13	30° - 2°
EP-WX8520	10	17	70	85	20	30° - 2°
EP-WX2508	3.5	5	19*19	25*25	8	30° - 2°

3、Axis Camera Level EP-CL1818



Details:1. beautiful design


2. single axis bubble level

3. for canon/nikon hotshoe

4.Size: 18*18*18±1mm

This Single Bubble Level is a single axis tubular style level that offers two hotshoe mounts for allowing perpendicular attachment positions on your camera, letting you level your camera in either left-to-right or front-to-back.

4、Axis Camera Level EP-CL1933



Details:Spirit level / bubble level for camera's hot shoe

Crystal clear housing slips on a camera shoe mount or tripod thread

Triple axis provides precise leveling

Size: 33*19*19±1mm

5、Axis Camera Level EP-CL2529



Details:

Spirit level / bubble level for camera's hot shoe

Crystal clear housing slips on a camera shoe mount or tripod thread

Triple axis provides precise leveling

Triple 3 Axis Bubble Spirit Level on Camera Hot Shoe

Size: 29*25*25mm±1mm

Introduction

Is it hard to determine whether the photo taken is straight and level? If you have this problem, this gadget is designed for you.

This Triple Bubble Level spirit level mounts into any flash shoe (except for Sony or Minolta camera) and features three joined spirit levels providing better direction information.

This will help the photographer achieve a finer degree of accuracy in capturing image content.

It is particularly useful when you mount your camera on a tripod. This is very nice for doing panoramic series too. It helps make sure that your photos will actually stitch together when all is done.

Contains

Quantity: Triple Axis Spirit Level x1

Suitable For:Fits almost all DSLR/SLR cameras with a standard flash hot shoe (except for Minolta and SONY SLR as they use their own flash mount).

6、Blue Aluminum Level EP-ML11



Details:

Material	Lead-free glass; Aluminum alloy
Diamter	35mm±0.1
Wall Thickness	0.9mm
High	13mm
Total Leagth	Add: 5-22.5mm
Precision	4S-30M/2mm (Tolerance±1')
Liquid in Side	ROHS purity solvents
Work Temputer	-40°C — +60°C
Store Temputer	-50°C — +70°C
Bubble change	0.02mm/°C
Bubble hit time	5S

7、High-Accuracy Metal Level EP-ML12



Details:

Long glass vial technical parameters

Material	Lead-free glass
Diamter	60mm±0.1
Wall Thickness	0.9mm
High	12±0.1mm
Precision	4S-30M/2mm (Tolerance±1')
Bubble Size	XY mm (Tolerance±0.1) /20°C

Liquid in Side	ROHS purity solvents
Work Temputer	-40°C — +60°C
Store Temputer	-50°C — +70°C
Bubble change	0.02mm/°C
Bubble hit time	5S

8、Compass Aluminum Level EP-ML10



Details:

Long glass vial technical parameters

Material Lead-free glass : Aluminum alloy

Diamter 20.8mm±0.1

Wall Thickness 0.9mm

High 17.6mm±0.1

Precision 4S-30M/2mm (Tolerance±1')

Bubble Size XY mm (Tolerance±0.1) /20°C

Liquid in Side ROHS purity solvents

Work Temputer -40°C — +60°C

Store Temputer -50°C — +70°C

Bubble change 0.02mm/°C

Bubble hit time 5S

Temputer Blisters at minus 40 ° C or zero on the 70 ° C, do the 24 hours temperature, recovery at room temperature, the constant bubble size, liquid flow unabated.

9、Aluminum Level EP-AL21



Details:ALUMINUM LEVEL

50CM metre long, made from ribbed section aluminium for strength and lightness, milled for accuracy and featuring three vials - vertical, horizontal and 45° angle: this is one affordable tool that works at the very highest level.

STRONG RIBBED SECTION ALUMINIUM BODY

VERSATILE PLUMB, LEVEL AND 45° VIALS

SUPER FLAT MILLED BOTTOM EDGE - ACCURATE TO WITHIN 1mm PER METRE

1 Aluminum alloy frame thickness=0.9±0.05mm ,and oxidized. Milled finish on datum plane;

23 pcs of acrylic vial indicate level,plumb and 45°,tolerance of accuracy: 0.057°=1mm/m;

3ABS plastic part shockproof

4With magnet and with two hand (you can choose)

5Milled finish on datum edge(you can choose)

6Heavy duty ALU. alloy frame frost oxidized.

10、鐳射水平儀



主要由鐳射模組和無柱水準泡構成，使用該產品能使使用者很方便、簡單，而準確的判斷出物品是否處於水準或垂直。可用於掛壁畫、家庭裝飾等，使用該產品可使你的家庭、辦公室等等裝飾更加的美觀、工整。

1.外觀尺寸(長*寬*高): 123×40×60mm

2.鐳射光形:在地上成直線

3.波長:630~660nm

4. 輸出功率:1mW(CE)<5mW(FDA)

5.精准度:±2mm/5m

6.有效距離: 20m

7.電池: 3V (AAA 1.5V×2)

8.電池壽命:可連續工作 10 小時

9.操作溫度: -10~45℃