

300 g x 0.01 g

DIGITAL BALANCE

Model : GM-300P

ISO-9001, CE, IEC1010



勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



Lutron

LUTRON ELECTRONIC

The Art of Measurement

DIGITAL BALANCE, 300 g x 0.01 g

Model : GM-300P

FEATURES

- * Microprocessor circuit with high accuracy & better performance.
- * High resolution & wide measuring capacity, 300 g x 0.01 g, 9.9995 oz x 0.0005 oz.
- * Large LCD display, 18 mm (0.7") digit size, easy read out.
- * Built-in gram & oz display unit, select by the internal slide switch.
- * Built-in self calibration system, the calibration value can memorize into EEPROM circuit permanently even power off.
- * Counting scale function.
- * RS232 computer interface.
- * Accept battery or AC/DC adapter power source, two way power supply.
- * Heavy duty ABS housing plastic case.

SPECIFICATIONS

Display	LCD, 18 mm (0.7") digit size, 5 digits with annunciator.		
Function	Weighting & counting.		
Weighting range & resolution	Unit	Range	Resolution
	g	0.10 g to 300 g	0.01 g
	oz	0.005 oz to 9.9995 oz 10.000 oz to 10.581 oz	0.0005 oz 0.001 oz
Min. display weight	g	0.10 g	
	oz	0.005 oz	
Unit select	g or oz, select by internal slide switch.		
Accuracy	$\pm (0.05 \% + 0.04 \text{ g})$ <i>* Within two hours after self calibration be executed at $23 \pm 5^{\circ} \text{C}$.</i>		
Sampling time	Approx. 1 second.		
Tare control	Approx. 300 g max.		
Transducer	Load cell.		
Circuit	Microprocessor circuit.		
Auto self calibration	Use 100 g or 200 g standard weight to execute self calibration automatically.		
Counting sample no.	10 PCs, 20 PCs, 50 PCs or 100 PCs.		
Operating temperature	0 to 50°C (32 to 122°F).		
Operating humidity	Less than 80% RH.		
Size	Cabinet	250 x 188 x 70 mm.	
	Platform	Round, 120 mm Dia.	
Power Supply	6 x 1.5V AA (UM-3) battery x 6 PCs, or DC 9V adapter (optional).		
Power Consumption	Approx. DC 25 mA.		
Accessory Included	Operation Manual.....1 PC.		
Optional Accessories	* Software (Windows version), SW-U801-WIN. * RS232 cable, UPCB-01. * 200 g calibration weight, WT-200.		

勝 特 力 材 料 886-3-
勝特力电子(上海) 86-21-
勝特力电子(深圳) 86-755
[Http://www.100y.com](http://www.100y.com)

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

* Appearance and specifications listed in this brochure are subject to change without notice. 051206-GM300P