500 g x 0.1 g, RS-232 DIGITAL BALANCE

Model: GM-5000

ISO-9001, CE, IEC1010



特力材料886-3-5753170 胜特力电子(上海) 86-21-34970699 胜特力电子(深圳) 86-755-83298787 Http://www. 100y. com. tw





The Art of Measurement

DIGITAL SCALE (5,000 g x 1 g)

Model: GM-5000

VI	FEATURES
 Microprocessor circui 	it with high accuracy & better performance.
* High resolution & wid	de measuring capacity, 5,000 g x 1 g.
* Large LCD display, 1	8 mm (0.7") digit size, easy read out.
* Built-in gram & oz di	splay unit, select by the internal slide switch.
* GM-501 built-in self	calibration system, high precision.
* With computer series	s data output.
* Heavy duty ABS hous	sing plastic case.

333	SF	PECIFICATIONS	
COM. TWY	LCD, 18 mn	n (0.7") digit size, 5 digits with annunciator.	W
Measuring Capacity	5,000 g		
Resolution	1g ON COMMENT WWW. 1907 COMMENT		
Min. Display Weight	3 g WWW.COMTW		
Unit Select	g or oz, select by internal slide switch.		
Accuracy (23 5 °C)	± (0.3 % + 1 d) * After the moment when the self-calibration		
W.100Y.		xecuted.	V.COM
Sampling time	Approx. 0.8 second.		
Tare Control	1	Full capacity.	
Transducer	Load cell.		
Circuit	Microprocessor circuit.		
Data Bus	RS-232 serial output, 9600 bud rate.		
Operating Temperature	0 ℃ to 50 ℃ (32 °F to 122 °F).		
Operating Humidity	Max. 80% RH.		
Data Bus	RS-232 serial output, 9600 bud rate.		
Size	Cabinet	250 x 188 x 70 mm	WW.
WW.1007.C	Platform	185 x 185 mm.	N N
Power Supply	6 x 1.5V AA (UM-3) BATTERY, or DC 9V adapter.		
Power Consumption	Approx. DC 27 mA.		
Accessory Included	Operation N	Operation Manual1 PC.	
Optional Accessories	*RS232 Interface cable for connecting between scale & the computer (COM port), Model : UPCB-02		
MMM	*USB Interface cable for connecting between scale & the computer (USB port), Model : USB-01		
材料 886-3-5753170 ·(上海) 86-21-34970699 ·(深圳) 86-755-83298787 www. 100y. com. tw	*Application	on Software, Model: SCALE-U002, After setup rdware system (Scale + RS-232 cable + Perso r), then can use the software SCALE-U002 car	onal

勝特力 胜特力电子 胜特力电子 Http://

execute the whole system as the counting scale.

^{*} Appearance and specifications listed in this brochure are subject to change without notice.