

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
 Http://www.100y.com.tw

Bulletin I2718 rev. E 05/02

International IOR Rectifier

6GBU Series

6.0 Amps Single Phase Full Wave

Bridge Rectifier

Features

- Diode chips are glass passivated
- Suitable for Universal hole mounting
- Easy to assemble & install on P.C.B.
- High Surge Current Capability
- High Isolation between terminals and molded case (1500 V_{RMS})
- Lead free terminals solderable as per MIL-STD-750 Method 2026
- Terminals suitable for high temperature soldering at 260°C for 8-10 secs
- UL E160375 approved

$$I_{O(AV)} = 6A$$


$$V_{RRM} = 50/800V$$

Description

These GBU Series of Single Phase Bridges consist of four glass passivated silicon junction connected as a Full Wave Bridge. These four junctions are encapsulated by plastic molding technique. These Bridges are mainly used in Switch Mode power supply and in industrial and consumer equipment.

Major Ratings and Characteristics

Parameters	6GBU	Units
I_o	6	A
@ T_c	100	°C
I_{FSM}	175	A
@ 50Hz	182	A
@ 60Hz	154	A ² s
I^2t	138	A ² s
@ 50Hz		
@ 60Hz		
V_{RRM} range	50 to 800	V
T_j	- 55 to 150	°C



6GBU

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

6GBU Series

Bulletin I2718 rev. E 05/01

International
IRF Rectifier

ELECTRICAL SPECIFICATIONS

Voltage Ratings

Type number	Voltage Code	V_{RRM} , max repetitive peak rev. voltage $T_J = T_J \text{ max.}$ V	V_{RMS} , max RMS voltage $T_J = T_J \text{ max.}$ V	I_{RRM} max. @ rated V_{RRM} $T_J = 25^\circ\text{C}$ μA	I_{RRM} max. @ rated V_{RRM} $T_J = 150^\circ\text{C}$ μA
6GBU	005	50	35	5	400
	01	100	70	5	400
	02	200	140	5	400
	04	400	280	5	400
	06	600	420	5	400
	08	800	560	5	400

Forward Conduction

Parameters	6GBU	Unit	Conditions
I_O Maximum DC output current	6.0	A	$T_C = 100^\circ\text{C}$, Resistive & inductive load $T_C = 100^\circ\text{C}$, Capacitive load
	4.8		
I_{FSM} Maximum peak, one-cycle non-repetitive surge current, following any rated load condition and with rated V_{RRM} reapplied	175		$t = 10\text{ms}$
	182		$t = 8.3\text{ms}$
I^2t Maximum I^2t for fusing, initial $T_J = T_J \text{ max}$	154	A^2s	$t = 10\text{ms}$
	138		$t = 8.3\text{ms}$
V_{FM} Maximum peak forward voltage per diode	1.0	V	$T_J = 25^\circ\text{C}$, $I_{FM} = 6\text{A}$
I_{RM} Typical peak reverse leakage current per diode	5.0	μA	$T_J = 25^\circ\text{C}$, 100% V_{RRM} $T_J = 150^\circ\text{C}$, 100% V_{RRM}
	400		
V_{RRM} Maximum repetitive peak reverse voltage range	50 to 800	V	

Thermal and Mechanical Specifications

Parameters	6GBU	Unit	Conditions
T_J Operating and storage temperature range	-55 to 150	$^\circ\text{C}$	
R_{thJC} Max. thermal resistance junction to case	2.2	$^\circ\text{C}/\text{W}$	DC rated current through bridge (1)
R_{thJA} Thermal resistance, junction to ambient	7.4	$^\circ\text{C}/\text{W}$	DC rated current through bridge (1)
W Approximate weight	4 (0.14)	g (oz)	
T Mounting Torque	1.0	Nm	Bridge to Heatsink
	9.0	Lb.in	

Note (1): Bridge mounted on Aluminum heat sink of dim 65 x 35 x 1.5mm, use silicon thermal compound heat transfer and bolt down using 3mm screw


勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

International
IR Rectifier


6GBU Series

Bulletin I2718 rev. E 05/02

Ordering Information Table



Outline Table



6GBU Series

Bulletin I2718 rev. E 05/01

International
IR Rectifier




Fig. 1 - Current Ratings Characteristics




Fig. 2 - Forward Voltage Drop Characteristics




Fig. 3 - Total Power Loss Characteristics




Fig. 4 - Maximum Non-Repetitive Surge Current

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)