

除鏽-潤滑劑

除鏽潤滑劑



EPE200H

用途：電子、電器、金屬及機械製品最佳解銹、防銹保養劑。
 特點：1.兼具有清潔、潤滑及滲透功效、迅速解腐蝕形成保護層。
 2.直接噴拭保養延長使用壽命。
 3.潤滑性能優異、適用各種機械潤滑。



Displaces water, moisture and damp from all surfaces because of its acute angle of contact against the relatively high angle presented by water, its very low surface tension and high capillary action drives water away from the surfaces and fills the pores as the water disperses.

Stops rust and corrosion by ensuring that water and moisture cannot penetrate where rust and corrosion originate. For long term protection, if items are to be stored in aggressive environments, Permard 40 should be applied at regular intervals as part of a maintenance schedule.

Penetrates seized parts and enables them to be freed more easily, thereby preventing damage due to excessive forces that would have to be used if it was not applied, as well as the time that can be saved.

Good lubricant - its deep penetration reduces coefficient of friction between surfaces and it can be used with confidence on small diameter load bearing surfaces in accessible locations. For heavy duty bearings which have seized, Permard 40 can be used to release them prior to being re-greased or oiled with the suitable Electrolube mechanical lubricant.

Stops electrical leakage by removing damp and moisture which provide leakage paths for current flow.

| Part No | Product No | Manuf. | Description | 容量 |
|---------|------------|-------------|-------------|---------|
| 2528 | EPE200H | ELECTROLUBE | 電子除銹劑 | 200ml/罐 |



消除噪音
 排除濕氣
 清潔及防銹
 鬆解生銹機件
 解化黏固雜質

Stops Squeaks
 Drives Out Moisture
 Cleans and Protects
 Loosens Rusted Parts
 Frees Sticky Mechanisms



用法說明：適當的搖動瓶罐。以WD-40浸濕所有需處理方並容其浸濕。想達到最佳保護效果。請別抹去。



| Part No. | Product No. | Description | 容量 |
|----------|-------------|-------------|------|
| 5089 | WD-40-2 | 防銹潤滑劑 | 2盎司 |
| 5090 | WD-40-6 | 防銹潤滑劑 | 6盎司 |
| 5130 | WD-40-12 | 防銹潤滑劑 | 12盎司 |

防銹-潤滑油

防銹潤滑油



16-401

特性：
 1.防銹、防腐蝕。做所有金屬不運轉時的長效防腐蝕保護。
 2.符合美軍規Mil-C-16173。棕色內含物。



用途：
 1.保護電氣和機械設備如升降機、齒輪、模型鑄模和其它大面積金屬表面。
 2.可以石油溶劑清除本劑。

| Part No. | Product No. | Manuf. | Description | 容量 |
|----------|-------------|--------|-------------|------|
| 11943 | 16-401 | 3M | 3 M防銹保護漆 | 11盎司 |



16-501

特性：
 1.內含97%純鋅，有效防銹、防腐蝕。
 2.物體表面噴上後，可形成如鍍鋅般灰色保護層(大約0.038公釐厚)。
 3.快乾。
 4.符合北軍規：
 Mil-P-21035, Mil-P-26915C
 Mil-P-46105, Mil-T-26433



用途：
 1.保護發電機、輸配電設備如電塔、變壓器、角架及其它金屬免於腐蝕。
 2.最適防護處於易生銹、腐蝕區域(如海邊)之金屬。

| Part No. | Product No. | Manuf. | Description | 容量 |
|----------|-------------|--------|-------------|------|
| 11941 | 16-501 | 3M | 3 M鋅漆保護劑 | 14盎司 |



16-703

特性：
 1.防銹、防潮、潤滑用。防止機械設備在運轉或儲存時遭受腐蝕(可長達3~5年)。
 2.不含氟氯碳(CFC)化合物。
 3.無腐蝕性。
 4.符合美軍規Mil-C-81309。



用途：使用於各種電機和機械設備如馬達、永浦、發電機、升降機、電梯、齒輪和壓縮等長期儲存防潮保護。

| Part No. | Product No. | Manuf. | Description | 容量 |
|----------|-------------|--------|---------------|------|
| 11940 | 16-703 | 3M | 3M儲存防潮潤滑劑(黃油) | 14盎司 |