

|                   |                           |  |
|-------------------|---------------------------|--|
| U.I. Lapp<br>GmbH | <b>DATASHEET</b>          |  |
|                   | <b>EPIC® H-B 16 TG-RO</b> | 10080900<br>12.09.2012   |

Housing design H-B. The industry standard.  
The housing standard. Wide choice for all applications



#### Application range

Plant engineering  
Light & sound technology  
Plastics industry

#### Product features

Hood, low version  
Reels for single lever  
Straight cable entry  
Versions with / without neck

#### Remark

Photographs are not to scale and do not represent detailed images of the respective products.

#### Technical Data

|                    |  |
|--------------------|--|
| Pieces / PU:       | 5  |
| Neck:              | yes  |
| PG:                | 21   |
| Article:           | H-B 16 TG-RO 21  |
| Material:          | Housing: powder-coated aluminium alloy, grey<br>Lever: zinc-plated steel<br>Sealing: NBR |
| Protection rating: | IP 65 (latched)  |
| Temperature range: | -40 °C to +100 °C, short-term up to +125 °C  |



勝特力材料 886-3-5753170  
 胜特力电子(上海) 86-21-34970699  
 胜特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

|                    |                              |       |
|--------------------|------------------------------|-------|
| Product Management | Document: EPIC® H-B 16 TG-RO | 1 / 2 |
|--------------------|------------------------------|-------|

## EPIC® H-B 16 TG-RO

10080900

12.09.2012

