

# CONDUCTIVITY TRANSMITTER

Model : TR-CDT1A4

ISO-9001, CE, IEC1010



勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-34970699  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

**Lutron**



**LUTRON ELECTRONIC**

**The Art of Measurement**

# CONDUCTIVITY TRANSMITTER

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-34970699  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

Model : TR-CDT1A4

|                              |  |
|------------------------------|--|
| <i>Measure Range</i>         | <p><i>Range 1 :</i><br/>0 - 200 uS</p> <p><i>Range 2:</i><br/>0.2 - 2 mS</p> <p><i>Range 3 :</i><br/>2 - 20 mS</p>   |
| <i>Output</i>                | <p>4 - 20 mA</p> <p><i>Range 1 :</i><br/>0 uS = 4 mA<br/>20 uS = 5.6mA<br/>200uS = 20mA</p> <p><i>Range 2 :</i><br/>0 mS = 4 mA<br/>0.2 mS = 5.6mA<br/>2 mS = 20 mA</p> <p><i>Range 3 :</i><br/>0 mS = 4 mA<br/>2 mS = 5.6mA<br/>20 mS = 20 mA</p> |
| <i>External Adjustment</i>   | ZERO VR<br>SPAN VR   |
| <i>Power Supply</i>          | 90 - 260 ACV<br>50 Hz/60 Hz  |
| <i>Operation Temperature</i> | 0 - 50 °C<br>32 - 122 °F   |
| <i>Operation Humidity</i>    | Less than 80 %RH   |
| <i>Accessory Included</i>    | Conductivity Prob  |
| <i>Optional Accessories</i>  | 1.413 mS standard solution   |
| <i>Mounting</i>              | Din rail or Wall   |
| <i>Case</i>                  | ABS plastic  |
| <i>Others</i>                | Separate probe with plug   |

\* Appearance and specifications listed in this brochure are subject to change without notice.