



Standard grease gun, HHFP

with ZBH, connection G 1/8"

Item number: 12 632 125
EAN: 4103810127328
Discount group: A

technical data

grease gun connection,
pressure-side: G 1/8"
capacity: 500 cm³
loading: 400 g grease cartridge, DIN 1284, or bulk grease
diameter of piston: 8 mm
actuation grease piston: manually lever operated
delivery rate / stroke: 1,2 cm³, at a counter-pressure of 400 bar
discharge pressure (bar): up to 400 bar
burst pressure (system): 850 bar
burst pressure (grease gun head): 1200 bar
operation of plunger rod: with L-design handle
Sealing cover: loose
wall thickness of grease gun tube: 1,0 mm
colour: silver
package: polybag, printed, with Bar code
dimensions packaging LxWxH (mm): 380 x 125 x 70
weight including package (kg): 1,25 kg

specification

- With 1 spout, angled, G 1/8", 150 mm
- With 1 coupler, 4 jaws G 1/8"

notes

- The unit operates with greases up to NLGI grade 2.
- plunger with exactly fitting when using bulk grease or cartridge
- Acc. to DIN 1283
- Pump piston with high accuracy of fit to the cylinder (no dummy apparent lubrication)
- Performance unchanged after 5000 actuating cycles
- grease gun head, zinc die casting Z 410
- Sure grip handling due to deep band knurls
- Safe handle on the plunger rod
- Slip resistant handle on grease gun lever
- Plunger rod clamp on end cap enables manual pressure to be applied to spring to compress bulk grease, or to force in the plunger in damaged cartridges.
- Low effort required for lubrication due to optimum lever efficiency
- High-speed ventilation, by half a rotation of the grease gun tube

packaging

dimensions LWH (mm): 400 x 360 x 145
weight (kg): 13,2
Packing unit: 10.0

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)